

Scilab Manual for
Numerical and Statistical Methods Laboratory
by Dr Keval Chandrakant Nikam
Mechanical Engineering
Savitribai Phule Pune University¹

Solutions provided by
Dr Keval Chandrakant Nikam
Mechanical Engineering
Savitribai Phule Pune University

July 2, 2025

¹Funded by a grant from the National Mission on Education through ICT,
<http://spoken-tutorial.org/NMEICT-Intro>. This Scilab Manual and Scilab codes
written in it can be downloaded from the "Migrated Labs" section at the website
<http://scilab.in>

Contents

List of Scilab Solutions	4
1 Program for roots of Equation using Bisection Method accuracy criteria	5
2 Program for roots of Equation using Newton Raphson Method accuracy criteria	7
3 Program for Simultaneous equations using Gauss Elimination Method	9
4 Program for Ordinary differential equation using Euler Method	12
5 Program for Ordinary differential equation using Runge Kutta 4th order	14
6 Program for Ordinary differential equation using Simultaneous equations using Runge Kutta 2nd order method	16
7 Program for Partial differential equation using Simple Laplace method	19
8 Program for Numerical Integration using Trapezoidal rule	22
9 Program for Numerical Integration using Simpsons 1/3rd Rule	24
10 Program for Numerical Integration using Simpsons 3/8th Rule.	26

11 Program for Numerical Integration using Gauss Quadrature 2-point and 3-point method	28
12 Program for Numerical Double Integration using Trape- zoidal rule	31
13 Program for Curve fitting using least square technique for first order equation	34
14 Program for Curve fitting using least square technique for power equation	36
15 Program for Curve fitting using least square technique for exponential equation	38

List of Experiments

Solution 1.1	Bisection Method	5
Solution 2.2	Newton Raphson Method	7
Solution 3.3	Gaussian Elimination method	9
Solution 4.4	Euler method	12
Solution 5.5	RK4ORDER	14
Solution 6.6	RK2Order Simultaneous	16
Solution 7.7	Laplace Method	19
Solution 8.8	TrapezoidalRule	22
Solution 9.9	Simpson 1 3rd Rule	24
Solution 10.10	Simpson 3 8th Rule	26
Solution 11.11	Gauss 2 and 3 Point Method	28
Solution 12.12	Trapezoidal Double Rule	31
Solution 13.13	First Order Equation	34
Solution 14.14	Power Equation	36
Solution 15.15	Exponential Equation	38

Experiment: 1

Program for roots of Equation using Bisection Method accuracy criteria

Scilab code Solution 1.1 Bisection Method

```
1 // Scilab code Solution 1 Program for roots of
   Equation using Bisection Method accuracy criteria
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 1
5 // Program for roots of Equation using Bisection
   Method accuracy criteria
6 // Example – Write a computer program in SCILAB
   to find root of equation as  $x^2 - 8x + 2$ ..
7 // Take Accuracy as 0.01 using Bisection Method. Take
    $x_1 = 0$  and  $x_2 = 1$ 
8 // Input  $x_1 = 0, x_2 = 1, acc = 0.01, f(x) = x^2 - 8x + 2$ 
9 clc;
10 clear;
11 close;
```

```

12 def(f('y=f(x)', 'y=x^2-8*x+2'))
13 x1=input('Enter First Initial Guess = ');
14 x2=input('Enter Second Initial Guess = ');
15 acc=input('Enter the value of Accuracy = ');
16 i=0;
17 printf('Iteration \t x1 \t \t x2 \t \t z \t \t f(z)\n',
18      n, )
18 while abs(x1-x2)>acc // Condition of Accuracy
19      z=(x1+x2)/2
20 printf ('%i\t %f \t%f \t%f \t%f \n ',i,x1,x2,z,f(z)
21 ))// Print in form of Table
21 if f(z)*f(x1)>0 // Substitution of initial guess
22      for next iteration
22      x1=z
23 else
24      x2=z
25 end
26      i=i+1 // Increment in Iteration by 1 for each
27      step
27 end
28 printf(' \n\n The solution of this equation is %g
29      after %i Iterations ',z,i-1)// Display final
30      answe to User

```

Experiment: 2

Program for roots of Equation using Newton Raphson Method accuracy criteria

Scilab code Solution 2.2 Newton Raphson Method

```
1 // Scilab code Solution 2 Program for roots of
   Equation using Newton Raphson Method accuracy
   criteria
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 2
5 // Program for roots of Equation using Newton
   Raphson Method accuracy criteria
6 // Example – Solve using Newton Raphson Method  $x - \exp(-x) = 0$ 
7 //Take accuracy as 0.001 . Take  $x_0=1$ 
8 //Input  $x_0=1, acc=0.001, f(x)=x - \exp(-x)$ 
9 clc;
10 clear;
11 close;
```

```

12 deff( 'y=f(x)' , 'y=x-exp(-x)' )
13 deff( 'y=f1(x)' , 'y=1+exp(-x)' )
14 x0 =input( 'Enter Initial Guess =' );
15 acc =input( 'Enter the value of Accuracy =' );
16 i=0;
17 printf('i \t\t x0 \t\t x1 \n')
18 x1=x0-(f(x0)/f1(x0))
19 printf('%i\t\t%0.5f\t\t%0.5f \n' ,i,x0 ,x1 )
20 while abs(x1-x0)>acc // Condition of Accuracy
21 x0=x1;
22 x1=x0-(f(x0)/f1(x0)) // Formula of finding root of
    Equation
23 i=i+1
24 printf ('%i\t\t%f\t\t%f \n' ,i,x0,x1) // Print in
    form of Table
25 end
26 printf('\n\n The root of equation is %0.5f' ,x1) //
    Display final answer to User

```

Experiment: 3

Program for Simultaneous equations using Gauss Elimination Method

Scilab code Solution 3.3 Gaussian Elimination method

```
1 // Scilab code Solution 3 Program for Simultaneous
   equations using Guass Elimination Method
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 3
5 // Program for Simultaneous equations using Guass
   Elimination Method
6 // Example – Write a computer program in SCILAB
   to solve following set of simultaneous
   equations using Gauss Elimination method .
7 //3 X + 2Y + Z = 10
8 //2 X + 3 Y + 2Z = 14
9 //X + 2Y + 3Z = 14
10 // Input coeffienct matrix a and solution matrix b
11 clc;
```

```

12 clear all;
13 disp('OUTPUT:');
14 a=input('Enter coefficient matrix a:=');
15 b=input('Enter matrix b:=');
16 [m,n]=size(a);
17 if m~=n // Check condition of square matrix
18     error('Matrix A must be square');
19 end
20 //Perform Partial Pivoting
21 for i=1:1:n-1
22     for u=i+1:1:n
23         if (abs(a(u,i))>abs(a(i,i))) // Comparison
            of Pivot Element
24             for v=1:1:n
25                 temp=a(i,v); // Replacement of Pivot
                    Element
26                 a(i,v)=a(u,v);
27                 a(u,v)=temp;
28             end
29             temp=b(i);
30             b(i)=b(u);
31             b(u)=temp;
32         end
33     end
34 //Gauss Elimination - operation of Rows
35     for k=i+1:1:n
36         factor=a(k,i)/a(i,i);
37         for j=1:1:n
38             a(k,j)=a(k,j)-factor*a(i,j); // Formula to
                make Coefficient Matrix in Upper
                Triangular Matrix
39         end
40         b(k)=b(k)-factor*b(i); // Formula also
            applicable to solution matrix
41     end
42 end
43 disp('Final augmented matrix is:');
44 disp([a,b]); //Display formed Upper Triangular Matrix

```

```
45 // Back Substitution
46 for i=n:-1:1
47     temp=b(i);
48     for j=i+1:1:n
49         temp=temp-a(i,j)*x(j);
50     end
51     x(i)=temp/a(i,i); // Calculating the value of x
52         (3),x(2) and x(1) resp.
52 end
53 disp('Answer is :');
54 disp(x);
```

Experiment: 4

Program for Ordinary differential equation using Euler Method

Scilab code Solution 4.4 Euler method

```
1 // Scilab code Solution 4 Program for Ordinary  
    differential equation using Euler Method  
2 // Operating System Windows 7  
3 // SCILAB version 6.1.1  
4 // Experiment No 4  
5 // Program for Ordinary differential equation using  
    Euler Method  
6 // Example – Write a computer program in SCILAB to  
    solve the ODE  
7 //dy/dx=-x*y^2 using Eulers method under the  
    condition x=0,y=2.Find y at x=1 with h=0.1.  
8 //Input function -xy^2,x0=0,y0=2,xn=1,h=0.1  
9 clc;  
10 close;  
11 clear;
```

```

12 def(f('y=f(x,y)', 'y=-x*y^2'); // Enter the Function
13 x0=input('Enter the value of x0=');
14 y0=input('Enter the value of y0=');
15 xn=input('Enter the value of xn=');
16 h=input('Enter the value of h=');
17 n=(xn-x0)/h; // Formuale for finding number of Step
    Size
18 disp(n)
19 for i=1:1:n
20     yn=y0+h*f(x0,y0); // Formulae use in Euler Method
21     x0=x0+h; // Increment in Step size
22     y0=yn; // Replacement of y0 as yn for next
        iteration
23     printf('Value of y(%f)=%f\n', x0, y0);
24 end

```

Experiment: 5

Program for Ordinary differential equation using Runge Kutta 4th order

Scilab code Solution 5.5 RK4ORDER

```
1 // Scilab code Solution 5 Program for Ordinary  
    differential equation using Runge-Kutta 4th order  
2 // Operating System Windows 7  
3 // SCILAB version 6.1.1  
4 // Experiment No 5  
5 // Program for Ordinary differential equation using  
    Runge-Kutta 4th order  
6 // Example – Write a computer program in SCILAB to  
    obtain the numerical solution of  
7 //  $dy/dx = x^2 + y^2$ ,  $y(0) = 0$ ,  $h = 0.2$ . Estimate  $y(0.4)$  using  
    Runge Kutta 4 order method  
8 // Input function  $x^2 + y^2$ ,  $x_0 = 0$ ,  $y_0 = 0$ ,  $h = 0.2$ ,  $x_n = 0.4$   
9 clc;  
10 close;  
11 clear;
```

```

12 def(f ('y=f(x,y,z)', 'y=x*x+y*y')) // Enter the Function
13 x0=input('Enter the value of x0=');
14 y0=input('Enter the value of y0=');
15 xn=input('Enter the value of xn=');
16 h=input('Enter the value of h=');
17 n=(xn-x0)/h; // Formuale for finding number of Step
    Size
18 disp(n)
19 for i=1:1:n
20     k1=h*f(x0,y0); // Calculate value of k1
21     k2=h*f(x0+h/2,y0+k1/2); // Calculate value of k2
22     k3=h*f(x0+h/2,y0+k2/2); // Calculate value of k3
23     k4=h*f(x0+h,y0+k3); // Calculate value of k4
24     k=(k1+2*k2+2*k3+k4)/6.0; // Calculate value of k
25     yn=y0+k; // Increment in Step size
26     x0=x0+h; // Increment in Step size
27     y0=yn; // Replacement of z0 as z1 for next
        iteration
28     printf('Value of y(%f)=%f\n',x0,y0); // Display y(
        n)
29 end

```

Experiment: 6

Program for Ordinary differential equation using Simultaneous equations using Runge Kutta 2nd order method

Scilab code Solution 6.6 RK2Order Simultaneous

```
1 // Scilab code Solution 6 Program for Ordinary
   differential equation using Simultaneous
   equations using Runge-Kutta 2nd order method
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 6
5 // Program for Ordinary differential equation using
   Simultaneous equations using Runge-Kutta 2nd
   order method
6 // Example – Write a computer program in SCILAB to
   to solve the equation
7 //dy/dx=-0.5*y,dz/dx=4-0.3*z-0.1*y Using runge kutta
   second order simultaneous method where at x = 0,
   y =4, z =6.
8 //Find y & z at x = 0.5 (take h=0.5)
```

```

9 //Input function f(x,y,z)=-0.5*y, g(x,y,z)= 4-0.3*z
   -0.1*y ,x0=0,y0=4,z0=6,h=2,xn=0.5
10 clc;
11 clear;
12 def(f,'y=f(x,y,z)', 'y=-0.5*y'); // Enter the Function
13 def(g,'z=g(x,y,z)', 'z=4-0.3*z-0.1*y'); // Enter the
   Function
14 x0=input('Enter the value of x0=');
15 y0=input('Enter the value of y0=');
16 z0=input('Enter the value of z0=');
17 xn=input('Enter the value of xn=');
18 h=input('Enter the value of h=');
19 n=(xn-x0)/h; // Formuale for finding number of Step
   Size
20 for i=1:1:n
21   k1=h*f(x0,y0,z0); // Calculate value of k1
22   L1=h*g(x0,y0,z0); // Calculate value of L1
23   k2=h*f(x0+h,y0+k1,z0+L1); // Calculate value of k2
24   L2=h*g(x0+h,y0+k1,z0+L1); // Calculate value of L2
25   k=(k1+k2)/2.0; // Finding out increment in y
   direction
26   y1=y0+k; // Increment in Step size
27   L=(L1+L2)/2.0; // Finding out increment in z
   direction
28   z1=z0+L; // Increment in Step size
29   x0=x0+h; // Increment in Step size
30   y0=y1; // Replacement of y0 as y1 for next
   iteration
31   z0=z1; // Replacement of z0 as z1 for next
   iteration
32   printf('value of y(%f)=%f\n',x0,y0); // Display y(n
   )
33   printf('value of z(%f)=%f\n',x0,z0); // Display z(n
   )
34 end

```

Experiment: 7

Program for Partial differential equation using Simple Laplace method

Scilab code Solution 7.7 Laplace Method

```
1 // Scilab code Solution 7      Program for Partial  
2 // differential equation using Simple Laplace method  
3 // Operating System Windows 7  
4 // SCILAB version 6.1.1  
5 // Experiment No 7  
6 // Program for Partial differential equation using  
7 // Simple Laplace method  
8 // Example – A steel Plate of 750x750mm has its two  
// adjancent sides maintained at  
7 //100 C .While the two other sides are maintained at  
// 0 C .What will be the  
8 //steady state temperature at interior assuming a  
// grid size of 250mm.Solve upto 11 iteration
```

```

9 //Input function n1=11,n=4,m=4,u(1,1)=0,u(2,1)=0,u
10 (3,1)=0,u(4,1)=0
11 //u(4,2)=0,u(4,3)=0,u(4,4)=0,u(3,4)=100,u(2,4)=100,u
12 (1,4)=100
13 //u(1,3)=100,u(1,2)=100
14 clc;
15 clear;
16 n1=input('Enter the no. of iteration to solve
    simultaneous eqn:');
17 n=input(' Enter the no.of mesh point(No. of B.V.
    values) in x-direction:');
18 m=input(' Enter the no.of mesh point(No. of B.V.
    values) in y-direction:');
19 printf(' Enter boundary value(B.V.) in anticlockwise
    direction Starting from bottom left corner\n');
20 u=zeros(m,n); //to create matrix of total size and
    to take initial guess as 0,0,0...
21 for i=1:n// to take input as a boundary value at
    bottom side
22     printf('Enter u(%d,1)=' ,i);
23     u(i,1)=input(' ');
24 end
25 for j=2:m //to take I/P at Right hand side B.V.
    bottom to top
26     printf('Enter u(%d,%d)=' ,n,j);
27     u(n,j)=input(' ');
28 end
29 for i=n-1:-1:1 // to take I/P at top side B.V. right
    to left
30     printf('Enter u(%d,%d)=' ,i,m);
31     u(i,m)=input(' ');
32 end
33 for j=m-1:-1:2 //to take I/P at left hand side B.V.
    top to bottom
34     printf('Enter u(1,%d)=' ,j);
35     u(1,j)=input(' ');
36 end
37 for k=1:n1 // To repeat n1 iterations

```

```

36     for j=2:m-1 //To calculate value at intermediate
        point by Gauss Seidal method
37         for i=2:n-1
38             u(i,j)=1/4*(u(i-1,j)+u(i,j+1)+u(i+1,j)+u(i,
                j-1)); // Formula for finding Internal
                  Elements
39         end
40     end
41     printf('Value after iteration no.:%d\n',k);
42     for j=m:-1:1 //To print value after each
        Iteration in Tabulated form
43         for i=1:n
44             printf('\t %0.4f \t',u(i,j));
45         end
46         printf('\n');
47     end
48 end

```

Experiment: 8

Program for Numerical Integration using Trapezoidal rule

Scilab code Solution 8.8 TrapezoidalRule

```
1 // Scilab code Solution > 8 Program for Numerical
   Integration using Trapezoidal rule
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 8
5 // Program for Numerical Integration using
   Trapezoidal rule
6 // Example – Write a computer program in SCILAB to
   solve integration 4*x+2
7 //limits x0=0,xn=1 by using Trapezoidal Method .
8 //Take h=0.5.
9 //Program on Trapezoidal Rule
10 clc;
11 close;
12 clear;
```

```
13 def(f('y=f(x)', 'y=4*x+2')) // Enter the Function
14 x0=input('Enter lower limit :') // Enter Lower Limit
15 xn=input('Enter upper limit :') // Enter Upper Limit
16 h=input('Enter step Size h:') // Enter Step Size
17 x=x0;
18 n=(xn-x0)/h; // Enter number of Step size
19 s=0;
20 for i=1:n-1
21     x=x+h;
22     s=s+2*f(x);
23 end
24 s=f(x0)+s+f(xn);
25 I=h/2*s; // Formula for finding Area by using
            Trapezoidal Rule
26 printf('Integration of given function is=%f\n', I);
```

Experiment: 9

Program for Numerical Integration using Simpsons 1/3rd Rule

Scilab code Solution 9.9 Simpson 1 3rd Rule

```
1 // Scilab code Solution 9      Program for Numerical
   Integration using Simpsons 1/3 rd Rule
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 9
5 // Program for Numerical Integration using
   Simpsons 1/3 rd Rule
6 // Example – Write a Program in Scilab for finding
   area of function  $(\sin(x))/(2+3*\sin(x))$  for
7 // upper limit of 1 and lower limit of 0. Take n=6 by
   using Simpson's 1/3 Rule
8 //Program on Simpson's 1/3rd Rule
9 clc;
10 clear;
11 deff('y=f(x)', 'y=(sin(x))/(2+3*sin(x))'); // Enter
```

```

    the Function
12 x0=input('Enter lower limit :');// Enter the lower
   limit of x
13 xn=input('Enter upper limit :');// Enter the upper
   limit of x
14 n=input('Enter number of steps :');// Enter the
   number of steps
15 x=x0;
16 h=(xn-x0)/n;// Calculate step size
17 s=0;
18 for i=1:n-1
19     x=x+h;
20     if modulo(i,2)==0 // Calculating Even Term of
       Simpson 1/3rd Formula
21         s=s+2*f(x);
22     else
23         s=s+4*f(x);
24     end
25 end
26 s=f(x0)+s+f(xn);
27 I=(h/3)*s;// Finding Integrating value
28 printf('\nIntegration of given function is=%f\n',I);
   // Display Value

```

Experiment: 10

Program for Numerical Integration using Simpsons 3/8th Rule.

Scilab code Solution 10.10 Simpson 3 8th Rule

```
1 // Scilab code Solution 10    Program for Numerical
   Integration using Simpsons 3/8 Rule
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 10
5 // Program for Numerical Integration using
   Simpsons 3/8 Rule
6 // Example – Write a Program in Scilab for finding
   area of function exp(x)/x for
7 // upper limit of 2 and lower limit of 1. Take n=6 by
   using Simpson's 3/8 Rule
8 //Program on Simpson's 3/8th Rule
9 clc;
10 close;
11 clear;
```

```
12 def('y=f(x)', 'y=exp(x)/x'); // Enter function
13 x0=input('Enter lower limit :'); // Enter lower limit
    of x
14 xn=input('Enter upper limit :'); // Enter upper limit
    of x
15 n=input('Enter number of steps :'); // Enter number of
    step
16 x=x0;
17 h=(xn-x0)/n; // Finding out of step size
18 s=0;
19 for i=1:n-1
20     x=x+h;
21     if modulo(i,3)==0 // Condition for adding the odd
        value together
22         s=s+2*f(x);
23     else
24         s=s+3*f(x);
25     end
26 end
27 s=f(x0)+f(xn)+s;
28 I=((3*h)/8)*s; // Calculating Area
29 printf('\nIntegration of given function is=%f\n',I);
```

Experiment: 11

Program for Numerical Integration using Gauss Quadrature 2-point and 3-point method

Scilab code Solution 11.11 Gauss 2 and 3 Point Method

```
1 // Scilab code Solution 11    Program for Numerical
   Integration using Gauss Quadrature 2-point and 3-
   point method
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 11
5 // Program for Numerical Integration using Gauss
   Quadrature 2-point and 3-point method
6 // Example – Write a Program in Scilab to solve
   using two-point or three point Gauss quadrature
   rule to
7 //approximate the distance covered by a rocket from
   t = 8 to t = 30 as given by
8 //x=(2000*log(140000/(140000-2100*t))-9.8*t)
9 // Enter a=lower limit=8,b=upper limit=30,n=Enter 2
```

```

        or 3 depend upon Guass 2 point or 3 point formula
10 //Program on Gauss Quadrature 2-point and 3-point
    method
11 clc;
12 clear;
13 def('x=f(t)', 'x=(2000*log(140000/(140000-2100*t))
    -9.8*t)'); // Enter the function
14 a=input('Enter lower limit:'); // Enter the lower
    limit of Integration
15 b=input('Enter upper limit:'); // Enter the upper
    limit of Integration
16 n=input('Enter 2 point or 3 point method:'); // Enter
    which method you are suppose to use
17 if n==2 // For executing 2 Point Method
18     c=(b-a)/2;
19     d=(b+a)/2;
20     z1=-1/sqrt(3);
21     z2=1/sqrt(3);
22     x1=c*z1+d;
23     x2=c*z2+d;
24     I=c*(f(x1)+f(x2)); // Formula for finding
        Integration value
25 else // For executing 3 Point Method
26     c=(b-a)/2;
27     d=(b+a)/2;
28     z1=sqrt(3/5);
29     z2=-sqrt(3/5);
30     x1=c*z1+d;
31     x2=c*z2+d;
32     x3=d;
33     I=c*(5/9*f(x1)+5/9*f(x2)+8/9*f(x3)); // Formula
        for finding Integration value
34 end
35 printf('\n Integration of given function is=%f\n',I)
    ;// Display the Integration

```

Experiment: 12

Program for Numerical Double Integration using Trapezoidal rule

Scilab code Solution 12.12 Trapezoidal Double Rule

```
1 // Scilab code Solution 12 Program for Numerical
   Double Integration using Trapezoidal rule
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 12
5 // Program for Numerical Double Integration using
   Trapezoidal rule
6 // Example – Write a Program in Scilab for finding
   area of function  $x+y$  for
7 // upper limit of 0 and lower limit of 1 for x,y. Take
   n=m=6 by using Numerical Double Integration
   using Trapezoidal rule
8 //Take  $f(x,y)=x+y$ ,  $x_0=0$ ,  $x_n=1$ ,  $y_0=0$ ,  $y_n=1$ ,  $n=m=6$ 
9 // Program for Numerical Double Integration using
   Trapezoidal rule
```

```

10 clc;
11 close;
12 clear;
13 def('y=f(x,y)', 'y=x+y'); // Enter function
14 x0=input('Enter x0 lower limit of x:'); // Enter
    lower limit of x
15 xn=input('Enter xn upper limit of x:'); // Enter
    upper limit of x
16 n=input('Enter no. of steps in x-direction:'); // Enter
    number of step size in x axis
17 y0=input('Enter y0 lower limit of y:'); // Enter
    lower limit of y
18 ym=input('Enter ym upper limit of y:'); // Enter
    upper limit of y
19 m=input('Enter no. of steps in y-direction:'); // Enter
    number of step size in y axis
20 h=(xn-x0)/n; // Enter step size in x axis
21 k=(ym-y0)/m; // Enter step size in y axis
22 s=0;
23 x=x0; // Replacement of x by x0
24 y=y0; // Replacement of y by y0
25 for i=1:1:m+1
26     for j=1:1:n+1
27         a(i,j)=f(x,y); // Alloting pivot point by
            putting value in function
28         x=x+h; // Increment in x axis
29     end
30     y=y+k; // Increment in y axis
31     x=x0;
32 end
33 disp([a]);
34 for i=1:1:m
35     for j=1:1:n
36         s=s+a(i,j)+a(i,j+1)+a(i+1,j)+a(i+1,j+1);
37     end
38 end
39 I=h*k/4*s; // Calculating the Area
40 printf('Integration of given function is=%f\n',I);

```

// Display the Area

Experiment: 13

Program for Curve fitting using least square technique for first order equation

Scilab code Solution 13.13 First Order Equation

```
1 // Scilab code Solution 13    Program for Curve
   fitting using least square technique for first
   order equation
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 13
5 // Program for Curve fitting using least square
   technique for first order equation
6 // Example – Write a computer program in SCILAB to
   fit a straight line to the data given below :
7 // x=[1 2 3 4 5 6 7];
8 //y=[0.5 2.5 2.0 4.0 3.5 6.0 5.5];
9
10 clc;
11 close;
```

```

12 clear;
13 //x=input('enter value of x matrix')
14 x=[1 2 3 4 5 6 7]; // Enter the x values (Dependent
    Variables)
15 disp([x]);
16 //y=input('enter value of y matrix')
17 y=[0.5 2.5 2.0 4.0 3.5 6.0 5.5]; // Enter the y
    values(Independent Variables)
18 disp([y]);
19 n=length(x); // Enter the data in x values
20 Y=y;
21 X=x;
22 X2=X.*X;// Calculating X*X Values( .* indicates that
    multiplication between respective value of x)
23 XY=X.*Y;// Calculating X*y Values( .* indicates that
    multiplication between respective value of x and
    y)
24 a0=(sum(Y)*sum(X2)-sum(X)*sum(XY))/(n*sum(X2)-(sum(X
    )^2)); // Calculating coefficient a0
25 a1=((n*sum(XY)-sum(X)*sum(Y))/(n*sum(X2)-(sum(X))^2)
    ); // Calculating coefficient a1
26 a=a1;//Replacement value of a
27 b=a0;//Replacement value of b
28 printf('\n y=%f*x+%f',a,b); // Display y=ax+b

```

Experiment: 14

Program for Curve fitting using least square technique for power equation

Scilab code Solution 14.14 Power Equation

```
1 // Scilab code Solution 14    Program for Curve
   fitting using least square technique for power
   equation
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 14
5 // 14    Program for Curve fitting using least square
   technique for power equation
6 // Example – Write a computer program in SCILAB to
   fit a power equation  $y=ax^b$  to the data given
   below :
7 // x=[1 2 3 4 5];
8 //y=[0.5 1.7 3.4 5.7 8.4];
9 //  Program for Curve fitting using least square
   technique for power equation
```

```

10 clc;
11 close;
12 clear;
13 //x=input('enter value of x matrix')
14 x=[1 2 3 4 5];// Enter X values( Dependent Variables
    )
15 disp([x]);
16 //y=input('enter value of y matrix')
17 y=[0.5 1.7 3.4 5.7 8.4];// Enter Y Values(
    Independent variables)
18 disp([y]);
19 n=length(x); // calculate length of x
20 Y=log(y); // Calculate valur of Y
21 X=log(x); // Calculate valur of X
22 X2=X.*X; // Calculate valur of X*X
23 XY=X.*Y // Calculate valur of X*Y
24 a0=(sum(Y)*sum(X2)-sum(X)*sum(XY))/(n*sum(X2)-(sum(X
    )^2)); // Calculating coeffienct a0
25 a1=((n*sum(XY)-sum(X)*sum(Y))/(n*sum(X2)-(sum(X))^2)
    ); // Calculating coefficient a1
26 a=exp(a0); // Replacement of value
27 b=a1;//Replacement of value
28 printf ('\n y=%f*x^%f',a,b); //Display y= ax^b

```

Experiment: 15

Program for Curve fitting using least square technique for exponential equation

Scilab code Solution 15.15 Exponential Equation

```
1 // Scilab code Solution 15 Program for Curve
   fitting using least square technique for
   exponential equation
2 // Operating System Windows 7
3 // SCILAB version 6.1.1
4 // Experiment No 15
5 // 15 Program for Curve fitting using least square
   technique for exponential equation
6 // Example – Write a computer program in SCILAB to
   fit a exponential equation  $y=ae^{bx}$  to the data
   given below :
7 // x=[1 3 5 7 9];
8 //y=[2.473 6.722 18.274 49.673 135.026];
9 // Program for Curve fitting using least square
   technique for exponential equation
10 clc;
11 close;
```

```

12 clear;
13 //x=input('enter value of x matrix')
14 x=[1.0 3.0 5.0 7.0 9.0]; // Enter x values(Dependent
   Variables)
15 disp([x]);
16 //y=input('enter value of y matrix')
17 y=[2.473 6.722 18.274 49.673 135.026]; // Enter y
   values(Indepent Variables)
18 disp([y]);
19 n=length(x); // Calculate number of data enter in x
20 Y=log(y); // Calculating Y Value
21 X=x;
22 X2=X.*X;// Calculating X*X Value( .* indicates
   respective value of x is multiplied with
   respective x value)
23 XY=X.*Y//// Calculating X*Y Value
24 a0=(sum(Y)*sum(X2)-sum(X)*sum(XY))/(n*sum(X2)-(sum(X
   )^2));// Calculating coefficient a0
25 a1=((n*sum(XY)-sum(X)*sum(Y))/(n*sum(X2)-(sum(X))^2));
   // Calculating coefficient a1
26 a=exp(a0); // Finding the value of a
27 b=a1; // Finding the value of a
28 printf ('\n y=%f*e^%f*x',a,b); //Displaying y=ae^b

```
