

Scilab Textbook Companion for  
Radar Engineering and Fundamentals of  
Navigational Aids  
by G. S. N. Raju<sup>1</sup>

Created by  
Garnapudi Vamsikrishna  
B.Tech  
Computer Engineering  
Sastra University  
College Teacher  
N. Raju  
Cross-Checked by  
Lavitha Pereira

May 27, 2016

<sup>1</sup>Funded by a grant from the National Mission on Education through ICT, <http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab codes written in it can be downloaded from the "Textbook Companion Project" section at the website <http://scilab.in>

# Book Description

**Title:** Radar Engineering and Fundamentals of Navigational Aids

**Author:** G. S. N. Raju

**Publisher:** I. k. International, New Delhi

**Edition:** 1

**Year:** 2010

**ISBN:** 978-81-906942-1-6

Scilab numbering policy used in this document and the relation to the above book.

**Exa** Example (Solved example)

**Eqn** Equation (Particular equation of the above book)

**AP** Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

# Contents

List of Scilab Codes	4
1 INTRODUCTION TO RADAR RADAR PARAMETERS AND THEIR DEFINITIONS	5
2 BASIC RADARS	9
3 ADVANCED RADARS	16
4 TRACKING RADAR	25
5 FACTORS AFFECTING RADAR OPERATION AND RADAR LOSSES	28
6 RADAR TRANSMITTERS	30
7 RADAR RECEIVERS	38
9 RADAR ANTENNAS	43
11 SOLVED PROBLEMS	66

# List of Scilab Codes

Exa 1.1	PEAK POWER DUTY CYCLE . . . . .	5
Exa 1.2	FINDING PRT PW . . . . .	6
Exa 1.3	FINDING AVERAGE POWER . . . . .	6
Exa 1.4	FINDING DUTY CYCLE AND PRT . . . . .	7
Exa 1.5	FINDING DOPPLER FREQUENCY . . . . .	8
Exa 2.1	FINDING RANGE OF TARGET . . . . .	9
Exa 2.2	FINDING DUTY CYCLE PRT PULSE WIDTH PULSE ENERGY . . . . .	9
Exa 2.3	FINDING PRF PRT RANGE RESOLUTION AND PULSE WIDTH . . . . .	10
Exa 2.4	FINDING DUTY CYCLE AVERAGE POWER . . . . .	11
Exa 2.5	FINDING PRF AVERAGE POWER DUTY CYCLE AND RADAR RANGE . . . . .	12
Exa 2.6	FINDING RANGE RESOLUTION AND UNAMBIGU- OUS RANGE . . . . .	12
Exa 2.7	FINDING PRF . . . . .	13
Exa 2.8	FINDING MIN RECEIVABLE SIGNAL . . . . .	13
Exa 2.9	FINDING MAX RADAR RANGE . . . . .	14
Exa 3.1	FINDING LOWEST BLIND SPEED . . . . .	16
Exa 3.2	FINDING SPEED OF AUTOMOBILE . . . . .	17
Exa 3.3	FINDING LOWEST THREE BLIND SPEEDS . . . . .	17
Exa 3.4	FINDING LOWEST THREE BLIND SPEEDS . . . . .	18
Exa 3.5	FINDING PRF . . . . .	19
Exa 3.6	FINDING MAX UNAMBIGUOUS RANGE . . . . .	20
Exa 3.7	FINDING RATIO OF OPERATING FREQ . . . . .	20
Exa 3.8	FINDING RATIO OF PRFs . . . . .	21
Exa 3.9	FINDING BLIND SPEEDS . . . . .	22
Exa 3.10	FINDING PEAK TX POWER . . . . .	23

Exa 4.1	FINDING PHASE DIFFERENCE BETWEEN ECHOS	25
Exa 4.2	FINDING SPACING BETWEEN ANTENNAS . . . . .	26
Exa 5.1	FINDING RCS . . . . .	28
Exa 5.4	FINDING RCS . . . . .	29
Exa 6.1	FINDING MAX POWER . . . . .	30
Exa 6.2	FINDING GAIN PARAMETER OUTPUT POWER GAIN AND Be . . . . .	31
Exa 6.3	FINDING CYCLOTRON ANGULAR FREQ AND CUT- OFF VOLTAGE . . . . .	32
Exa 6.4	FINDING ELECTRON VELOCITY TRANSIT ANGLE AND BEAM COUPLING COEFFICIENT . . . . .	32
Exa 6.5	FINDING EFFICIENCY . . . . .	33
Exa 6.6	FINDING FREQ OF IMPATT DIODE . . . . .	34
Exa 6.7	FINDING FREQ OF IMPATT DIODE . . . . .	34
Exa 6.8	FINDING AVALANCHE ZONE VELOCITY . . . . .	35
Exa 6.9	FINDING FREQ OG GUNN DIODE OSCILLATOR . . . . .	36
Exa 6.10	FINDING MIN OPERATING GUNN DIODE VOLT- AGE . . . . .	36
Exa 7.1	FINDING PROBABILTY OF FALSE ALARM . . . . .	38
Exa 7.2	FINDING RADAR INTEGRATION TIME . . . . .	39
Exa 7.5	FINDING RANGE RESOLUTION . . . . .	39
Exa 7.8	RANGE RESOLUTION BEFORE AND AFTER COM- PRESSION . . . . .	40
Exa 7.9	FINDING MIN RECEIVABLE SIGNAL . . . . .	41
Exa 9.1	FINDING BEAMWIDTHS . . . . .	43
Exa 9.2	FINDING GAIN OF PARABOLIC REFLECTOR . . . . .	44
Exa 9.3	FINDING NNBW HPBW AND POWER GAIN OF ANTENNA . . . . .	44
Exa 9.4	FINDING POWER GAIN . . . . .	45
Exa 9.5	FINDING MOUTH DIAMETER HPBW AND POWER GAIN OF PARABOLOID . . . . .	46
Exa 9.6	FINDING BEAMWIDTH DIRECTIVITY AND CAP- TURE AREA . . . . .	47
Exa 9.7	FINDING MIN DISTANCE REQUIRED BETWEEN TWO ANTENNAS . . . . .	48
Exa 9.8	FINDING MOUTH DIAMETER AND BEAM WIDTH OF ANTENNA . . . . .	49

Exa 9.9	FINDING CAPTURE AREA AND BEAMWIDTH OF ANTENNA . . . . .	50
Exa 9.10	FINDING BEAMWIDTH AND POWER GAIN . . . . .	51
Exa 9.11	FINDING POWER GAIN . . . . .	52
Exa 9.12	FINDING MOUTH DIAMETER AND CAPTURE AREA . . . . .	52
Exa 9.13	FINDING MOUTH DIAMETER AND POWER GAIN . . . . .	53
Exa 9.14	FINDING BEAMWIDTH AND POWERGAIN . . . . .	54
Exa 9.15	FINDING POWER GAIN . . . . .	55
Exa 9.16	FINDING BEAMWIDTH AND DIRECTIVITY OF ANTENNA . . . . .	56
Exa 9.17	FINDING BEAMWIDTH POWERGAIN AND DIRECTIVITY . . . . .	57
Exa 9.18	FINDING POWER GAIN OF HORN ANTENNA . . . . .	58
Exa 9.19	FINDING POWER GAIN AND DIRECTIVITY . . . . .	58
Exa 9.20	FINDING COMPLEMENTARY SLOT IMPEDANCE . . . . .	59
Exa 9.21	FINDING RADIATION RESISTANCE OF HERTZIAN DIPOLE . . . . .	61
Exa 9.22	DIRECTIVITY OF HALFWAVE DIPOLE . . . . .	62
Exa 9.23	FINDING RADIATED POWER . . . . .	63
Exa 9.24	FINDING EFFECTIVE AREA OF HALF WAVE DIPOLE . . . . .	63
Exa 9.25	FINDING EFFECTIVE AREA OF HERTZIAN DIPOLE . . . . .	64
Exa 11.1	FINDING RECEIVED SIGNAL POWER . . . . .	66
Exa 11.2	FINDING TARGET DISTANCE FROM RADAR . . . . .	67
Exa 11.3	FINDING MAX AND MIN RANGES OF RADAR . . . . .	67
Exa 11.4	FINDING DUTY CYCLE . . . . .	68
Exa 11.5	FINDING AVERAGE TX POWER . . . . .	69
Exa 11.6	FINDING RANGE RESOLUTION . . . . .	69
Exa 11.7	FINDING TARGET RANGE . . . . .	70
Exa 11.8	FINDING DOPPLER SHIFT . . . . .	71
Exa 11.9	FINDING DOPPLER SHIFT FREQUENCY . . . . .	71
Exa 11.10	FINDING DOPPLERSHIFT FREQUENCY AND FREQUENCY OF RELECTED ECHO . . . . .	72
Exa 11.11	FINDING DOPPLER SHIFT FREQUENCY AND FREQUENCY OF REFLECTED SIGNAL . . . . .	73
Exa 11.12	FINDING AVERAGE POWER . . . . .	74
Exa 11.13	FINDING DUTY CYCLE AVERAGE POWER AND MAX RANGE OF RADAR . . . . .	75
Exa 11.14	FINDING PRF . . . . .	76

Exa 11.15	FINDING RANGE . . . . .	76
Exa 11.16	FINDING FREQUENCIES . . . . .	77
Exa 11.17	FINDING BEAMWIDTH . . . . .	78
Exa 11.18	FINDING MIN TIME REQUIRED TO RESOLVE AIR- CRAFTS . . . . .	78
Exa 11.19	FINDING DUTY CYCLE CORRECTION FACTOR . . . . .	79
Exa 11.20	FINDING AVERAGE POWER DUTY CYCLE AND PULSE ENERGY . . . . .	80
Exa 11.21	FINDING NOISE POWER SPECTRAL DENSITY . . . . .	81
Exa 11.22	FINDING RANGE OF TARGET . . . . .	82
Exa 11.23	FINDING RANGE OF TARGET . . . . .	82
Exa 11.24	FINDING TARGET BLIND SPEED . . . . .	83
Exa 11.25	RATIO OF OPERATING FREQUENCIES . . . . .	84
Exa 11.26	RATIO OF OPERATING FREQUENCIES . . . . .	84
Exa 11.27	FINDING COMPRESSION RATIO AND COMPRESSED PULSE WIDTH . . . . .	85
Exa 11.28	FINDING COMPRESSION PULSEWIDTH AND RA- TIO . . . . .	86
Exa 11.29	FINDING COMPRESSED PULSE WIDTH AND BAND- WIDTH . . . . .	86
Exa 11.30	FINDING RANGE RESOLUTION . . . . .	87
Exa 11.31	FINDING CLOSEST FREQUENCIES . . . . .	88
Exa 11.32	FINDING SPECTRUM CENTRE BANDWIDTH AND COMPRESSED PULSE WIDTH . . . . .	88
Exa 11.33	FINDING MINIMUM RECEIVABLE SIGNAL . . . . .	89
Exa 11.34	FINDING MAXIMUM RANGE OF RADAR . . . . .	90
Exa 11.35	FINDING PEAK TX POWER . . . . .	91
Exa 11.36	FINDING MAX RANGE OF RADAR . . . . .	92
Exa 11.37	FINDING LOWEST BLIND SPEEDS . . . . .	93
Exa 11.38	FINDING RANGE OF BEACON . . . . .	94
Exa 11.39	FINDING DOPPLER SHIFT . . . . .	95
Exa 11.40	FINDING RX SIGNAL POWER . . . . .	96
Exa 11.41	FINDING DISTANCE OF TARGET . . . . .	97
Exa 11.42	FINDING MIN AND MAX TARGET RANGE . . . . .	98
Exa 11.43	FINDING DOPPLER SHIFT FREQUENCY . . . . .	99
Exa 11.44	FINDING DISTANCE OF TARGET . . . . .	99
Exa 11.45	FINDING DUTY CYCLE AND AVERAGE POWER . . . . .	100
Exa 11.46	FINDING PRF . . . . .	101



Exa 11.47	FINDING DUTY CYCLE AND MAX UNAMBIGUOUS RANGE . . . . .	102
Exa 11.48	FINDING MAX UNAMBIGUOUS RANGE AND RANGE RESOLUTION . . . . .	103
Exa 11.49	CALCULATING RADAR PARAMETERS . . . . .	103
Exa 11.50	FINDING AVERAGE POWER . . . . .	105
Exa 11.51	FINDING MIN RECEIVABLE SIGNAL . . . . .	106
Exa 11.52	FINDING MAX RANGE OF RADAR . . . . .	106
Exa 11.53	FINDING MAX RANGE OF RADAR . . . . .	107
Exa 11.54	FINDING BEAMWIDTH OF ANTENNA . . . . .	108
Exa 11.55	FINDING OPERATING FREQ PEAK POWER AND RANGE OF RADAR . . . . .	109
Exa 11.56	FINDING RADIAL VELOCITY OF TARGET . . . . .	110
Exa 11.57	FINDING DOPPLER SHIFT FREQUENCY . . . . .	111
Exa 11.58	FINDING DOPPLER SHIFT FREQUENCIES . . . . .	111
Exa 11.59	FINDING BLIND SPEED . . . . .	112
Exa 11.61	FINDING PULSE WIDTH AND PULSE ENERGY . . . . .	113
Exa 11.62	FINDING PRT PRF RANGE RESOLUTION AND PULSE WIDTH . . . . .	114
Exa 11.63	FINDING DOPPLER FREQUENCY . . . . .	115
Exa 11.64	FINDING MAX RANGE OF RADAR . . . . .	116
Exa 11.65	FINDING APERTURE SIZE AND PEAK POWER OF TXR . . . . .	117

# Chapter 1

## INTRODUCTION TO RADAR RADAR PARAMETERS AND THEIR DEFINITIONS

Scilab code Exa 1.1 PEAK POWER DUTY CYCLE

```
1 //Chapter –1, Example 1.1, Page 34
2 //


---


3 clc;
4 clear;
5
6 //INPUT DATA
7 PRF= 1000;//pulse repetitive frequency in Hz
8 PW = 2*10^-6;//pulse width 2us
9 Pav=100;//average power in watts
10
11 //Calculations
12
13 Ppeak = (Pav)/(PW*PRF);//Peak power in watts
```

```

14 D      = Pav/Ppeak; //Duty cycle
15
16 //Output
17 mprintf('Peak power is %g KW\n Duty cycle is %e',
          Ppeak/1000,D);

```

---

### Scilab code Exa 1.2 FINDING PRT PW

```

1 //Chapter –1, Example 1.2, Page 35
2 //

```

---

```

3 clc;
4 clear;
5
6 //INPUT DATA
7 PRF= 1.2*10^3; //pulse repetitive frequency in Hz
8 PI = 0.6*10^-3; //pulse interval in sec
9
10 //Calculations
11
12 PRT = 1/PRF; //pulse repetition frequency in Hz
13 PW  = PRT-PI; //pulse width in sec;
14
15 //Output
16 mprintf('Pulse repetitive time is %3.3f ms\n Pulse
          width is %3.3f ms',PRT*1000,PW*1000);

```

---

### Scilab code Exa 1.3 FINDING AVERAGE POWER

```

1 //Chapter –1, Example 1.3, Page 35

```

```

2 //


---


3 clc;
4 clear;
5
6 //INPUT DATA
7 D = 0.001; //Duty Cycle
8 Ppeak=500*103; //Peak Power in Watts
9
10 //Calculations
11
12 Pav = D * Ppeak; // D=averagepower/Peakpower;
13
14 //Output
15 mprintf('Average power is %g Watts',Pav);


---



```

#### Scilab code Exa 1.4 FINDING DUTY CYCLE AND PRT

```

1 //Chapter –1, Example 1.4, Page 35
2 //


---


3 clc;
4 clear;
5
6 //INPUT DATA
7 PRF = 1000; //pulse repetitive frequency in Hz
8 Ppeak =10*106; //peak power in watts
9 Pav =100*103; //average power in watts
10
11 //Calculations
12
13 D = Pav/Ppeak; //Duty cycle
14 PRT = 1/PRF; //pulse repetitive time;

```

```
15
16 //Output
17 mprintf('Duty cycle is %g\n pulse repetitive time is
           %g ms',D,PRT*1000);
```

---

### Scilab code Exa 1.5 FINDING DOPPLER FREQUENCY

```
1 //Chapter -1, Example 1.5, Page 36
2 //


---



---



```
3 clc;
4 clear;
5
6 //INPUT DATA
7 F= 6*10^9; //frequency in Hz
8 Vo = 3*10^8; //velocity in m/s;
9 Vr = 200; //Radial velocity in kmph
10
11 //Calculations
12
13 lamda = Vo/F; //wavelength = vel/freq;
14 Fd = (2*Vr/lamda)*(5/18); //doppler frequency in
    Hz;
15 //5/18 is multiplied to convert kmph to m/s
16
17 //Output
18 mprintf('Doppler Frequency is %3.2 f KHz',Fd/1000);
```



---


```

## Chapter 2

# BASIC RADARS

Scilab code Exa 2.1 FINDING RANGE OF TARGET

```
1 //Chapter-2 example 2.1
2 //


---


3 clc;
4 clear;
5 Tdelay=200*10-6; //time delay in sec
6 Vo=3*108; //velocity in m/s
7 //Calculations
8 R=(Vo*Tdelay)/2; //Range of the target in kms
9
10
11 //Output
12 mprintf('Range of the target is %3.1f Kms',R/1000);
13 //
```

---

**Scilab code Exa 2.2** FINDING DUTY CYCLE PRT PULSE WIDTH PULSE ENERGY

```
1 //Chapter-2 example 2.2
2 //


---


3 clc;
4 clear;
5 Pt=5000; //Peak tx power in watts
6 Pav=1000; //Average Power
7 PRF1 = 10; //Pulse repetition frequency in khz
8 PRF2 = 20; //Pulse repetition frequency in khz
9 //Calculations
10 D=Pav/Pt; //Duty cycle
11 PRI1=1/PRF1; //Pulse repetitive interval in msec
12 PRI2=1/PRF2; //Pulse repetitive interval in msec
13 PW1=D*PRI1; //Pulse Width in msec
14 PW2=D*PRI2; //Pulse Width in msec
15 PE1=Pt*PW1; //Pulse Energy in joules
16 PE2=Pt*PW2; //Pulse Energy in joules
17 //Output
18 mprintf('Duty cycle is %3.2f \n pulse repetition
    interval 1 is %3.2f msec\n pulse repetition
    interval 2 is %3.2f msec\n Pulse Width1 is %3.2f
    usec\n Pulse Width2 is %3.2f usec\n Pulse Energy1
    is %3.2f J \n Pulse Energy2 is %3.2f J',D,PRI1,
    PRI2 ,PW1*1000 ,PW2*1000 ,PE1/1000 ,PE2/1000);
```

---

**Scilab code Exa 2.3** FINDING PRF PRT RANGE RESOLUTION AND PULSE WIDTH

```
1 //Chapter-2 example 2.3
2 //
```

---

```

3  clc;
4  clear;
5  UR=200; //unambiguous range in kms
6  BW=1*10^6; //bandwidth in hz
7  V0=3*10^8; //velocity in m/s
8  //Calculations
9  PRF=V0/(2*UR*10^3); //pulse repetition frequency in
    hz
10 PRI=1/PRF; //pulse repetition interval in sec
11 RR=V0/(2*BW); //Range Resolution in mts
12 PW=(2*RR)/(V0); //pulse width
13 //Calculations
14 mprintf('pulse repetition frequency is %3.2f Hz\n
    pulse repetition interval is %3.2f msec\n Range
    Resolution is %3.2f m\n pulse width is %3.1f usec',
    ,PRF ,PRI*1000 ,RR ,PW*10^6);

```

---

#### Scilab code Exa 2.4 FINDING DUTY CYCLE AVERAGE POWER

```

1  //Chapter-2 example 2.4
2  //

```

---

```

3  clc;
4  clear;
5  Pt=50000; //peal power in watts
6  PRF=1000; //pulse repetitive frequency in hz
7  PW=0.8; //pulse width in usec
8  //Calculations
9  D=PW*PRF*10^-6; //duty cycle
10 Pav=Pt*D; //average power
11 //output
12 mprintf('Duty cycle is %g\n Average power is %g
    Watts',D,Pav);

```



---

**Scilab code Exa 2.5** FINDING PRF AVERAGE POWER DUTY CYCLE  
AND RADAR RANGE

```
1 //Chapter-2 example 2.5
2 //


---


3 clc;
4 clear;
5 Vo=3*10^8; //velocity in m/s
6 Pt=1*10^6; //peak power in watts
7 PW=1.2*10^-6; //pulse width in sec
8 PRI=1*10^-3; //pulse repetition interval in sec
9 //Calculations
10 PRF=1/PRI; //pulse repetition frequency in hz
11 Pav=Pt*PW*PRF; //average power in watts
12 D=Pav/Pt; //Duty cycle;
13 Rmax=Vo/(2*PRF); //maximum range of the radar in m
14 mprintf('pulse repetition frequency is %g KHz\n
    average power is %g KW\n Duty cycle = %e\n
    maximum range of the radar is %g Km',PRF/1000,Pav
    /1000,D,Rmax/1000 );
```

---

**Scilab code Exa 2.6** FINDING RANGE RESOLUTION AND UNAMBIGU-  
OUS RANGE

```
1 //Chapter-2 example 2.6
2 //


---


3 clc;
```

```

4 clear;
5 PW = 2*10^-6; //pulse width in sec
6 PRF=800; //pulse repetition frequency in
  KHz
7 V0=3*10^8; //velocity in m/s
8 //Calculations
9 Ru=V0/(2*PRF); //unambiguous range in mts
10 RR=(V0*PW)/2; //Range resolution in m
11 //output
12 mprintf('unambiguous range is %g Km\n Range
  resolution is %g m',Ru/1000,RR);

```

---

#### Scilab code Exa 2.7 FINDING PRF

```

1 //Chapter-2 example 2.7
2 //

```

---

```

3 clc;
4 clear;
5 Rmax=500; //maximum range in kms
6 V0=3*10^8; //velocity in m/s;
7 //calculations
8 PRF=(V0/(2*Rmax*10^3)); //pulse repetitive frequency
  in Hz
9 //output
10 mprintf('pulse repetitive frequency is %g Hz',PRF);

```

---

#### Scilab code Exa 2.8 FINDING MIN RECEIVABLE SIGNAL

```

1 //Chapter-2 example 8

```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 F          = 9;           //Noise figure in dB
7 BW         = 3*10^6;     // Bandwidth
8 To         = 290;       // Temperature in kelvin
9 K          = 1.38*10^-23; // Boltzman constant
10
11 //Calculations
12
13 F1         = 10^(F/10)   // antilog calculation
14 Pmin      = (K*To*BW)*(F1-1); //minimum receivable
    power
15
16 //Output
17 mprintf('Minimum receivable power Pmin = %3.4f pW',
    Pmin*10^12);
18 mprintf('\\n Calculation error at Pmin in textbook');
19
20
21 //


---



```

### Scilab code Exa 2.9 FINDING MAX RADAR RANGE

```

1 //Chapter-2 example 2.9
2 //


---



```

```

3 clc;
4 clear;

```

```
5 Pt=500000; //peal power in watts
6 F=10*10^9; //operating frequency in hz
7 MRP=0.1*10^-12; //minimum receivable power in pico
  watts
8 Ac=5; //capture area of antenna in m^2;
9 RCS=20; //radar cross sectional area in m^2;
10 Vo=3*10^8 //velocity in m/s
11 // calculations
12 lamda =Vo/F
13 Rmax=((Pt*Ac*Ac*RCS)/(4*%pi*lamda*lamda*MRP))^0.25
14
15 //output
16 mprintf('Maximum Radar Range is %3.1f kms',Rmax
  /1000);
```

---

# Chapter 3

## ADVANCED RADARS

Scilab code Exa 3.1 FINDING LOWEST BLIND SPEED

```
1 //Chapter –3, Problem 3.1 , Page104
2 //


---


3 clc;
4 clear;
5
6 //INPUT DATA
7 PRF= 1500;//pulse repetitive frequency in Hz
8 lamda = 3*10^-2;//wavelength in m;
9
10 //Calculations
11 //n =1 gives lowest blind speed
12 n=1;
13
14 Vb = n*(lamda/2)*PRF;//blind speed in m/s
15
16
17 //Output
18 mprintf('Lowest Blind Speed is %g m/s ',Vb);
```

---

### Scilab code Exa 3.2 FINDING SPEED OF AUTOMOBILE

```
1 //Chapter –3, Problem 3.2 , Page105
2 //


---


3 clc;
4 clear;
5
6 //INPUT DATA
7 PRF= 1000;//pulse repetitive frequency in Hz
8 Fd = 1000;//doppler frequency in Hz;
9 F = 10*109;//operating frequency of radar in Hz;
10 Vo = 3*108;//velocity in m/s
11
12 //Calculations
13 lamda = Vo/F;
14 Va = (Fd*lamda)/2;//speed of automobile in m/s
15 Va1 = Va*18/5; //speed of automobile in kmph
16
17 //Output
18 mprintf('Speed of automobile is %g m/s or %g kmph\n',
    ,Va,Va1 );
```

---

### Scilab code Exa 3.3 FINDING LOWEST THREE BLIND SPEEDS

```
1 //Chapter –3, Problem 3.3 , Page105
2 //


---


3 clc;
4 clear;
```

```

5
6 //INPUT DATA
7 PRF= 1000; //pulse repetitive frequency in Hz
8 F = 10*10^9; //operating frequency of radar in Hz;
9 Vo = 3*10^8; //velocity in m/s
10
11 //Calculations
12 lamda = Vo/F;
13 // Blind Frequency is given by Fn = n*PRF;
14 n1 = 1;
15 n2 = 2;
16 n3 = 3;
17 F1 =n1*PRF; //blind frequency for n=1 in Hz;
18 F2 =n2*PRF; //blind frequency for n=2 in Hz;
19 F3 =n3*PRF; //blind frequency for n=3 in Hz;
20
21 //Output
22 mprintf('Lowest three Blind Frequencies are %g KHz ,
          %g KHz and %g KHz\n',F1/1000 ,F2/1000 ,F3/1000 );

```

---

### Scilab code Exa 3.4 FINDING LOWEST THREE BLIND SPEEDS

```

1 //Chapter –3, Problem 3.4 , Page105
2 //


---


3 clc;
4 clear;
5
6 //INPUT DATA
7 F = 10*10^9; //operating frequency in Hz
8 PRF= 800; //pulse repetitive frequency in Hz
9 Vo = 3*10^8; //velocity in m/s;
10 n1 = 1;
11 n2 = 2;

```

```

12 n3 = 3;
13 // Calculations
14
15 lamda = Vo/F; //Wavelength in m
16
17 // blind speed Vb = n*(lamda/2)*PRF in m/s
18
19 Vb1 = n1*(lamda/2)*PRF; // first blind speed in m/s;
20 Vb2 = n2*(lamda/2)*PRF; //second blind speed in m/s;
21 Vb3 = n3*(lamda/2)*PRF; //third blind speed in m/s;
22
23 //Output
24 mprintf('First Blind Speed is %g m/s\n Second Blind
    Speed is %g m/s\n Third Blind Speed is %g m/s\n',
    Vb1, Vb2, Vb3);
25 mprintf('NOTE: IN TEXT BOOK THIRD BLIND SPEED IS
    WRONGLY PRINTED AS 48 m/s ');

```

---

### Scilab code Exa 3.5 FINDING PRF

```

1 //Chapter –3, Problem 3.5 , Page106
2 //

```

---

```

3 clc;
4 clear;
5
6 //INPUT DATA
7 F = 10*109; //operating frequency in Hz
8 Vo = 3*108; //velocity in m/s;
9 Vb1 = 20; //lowest(first) blind speed in m/s
10 n = 1; //since first blindspeed
11 // Calculations
12
13 lamda = Vo/F; //Wavelength in m

```



```

14
15 // blind speed Vb = n*(lamda/2)*PRF in m/s
16
17 PRF = (2*Vb1)/(n*lamda); //pulse repetitive frequency
    in Hz
18
19 //Output
20 mprintf('Pulse Repetitive Frequency is %3.2f KHz',
    PRF/1000);

```

---

### Scilab code Exa 3.6 FINDING MAX UNAMBIGUOUS RANGE

```

1 //Chapter –3, Problem 3.6 , Page106
2 //

```

---

```

3 clc;
4 clear;
5
6 //INPUT DATA
7 lamda = 3*10^-2; //wavelength in m
8 PRF = 1000; //pulse repetitive frequency in Hz
9 Vo = 3*10^8; // velocity in m/s
10
11 //Calculations
12
13 Ruamb = (Vo)/(2*PRF); //max unambiguous range in m
14 //Output
15 mprintf('Maximum unambiguous range is %g Kms',Ruamb
    /1000);

```

---

### Scilab code Exa 3.7 FINDING RATIO OF OPERATING FREQ

```

1 //Chapter -3, Problem 3.7 , Page106
2 //

```

---

```

3 clc;
4 clear;
5
6 //INPUT DATA
7
8 n1    = 1 ; //since first blindspeed
9 n3    = 3 ; //since third blindspeed
10
11 //Calculations
12
13
14 // blind speed Vb1 = n1*(lamda_1/2)*PRF1 in m/s
15 // blind speed Vb3 = n3*(lamda_2/2)*PRF2 in m/s
16 //here PRF1 = PRF2 = PRF
17 //if Vb1=Vb3 then
18 //1*(lamda_1/2)*PRF = 3*(lamda_2/2)*PRF
19 //lamda_1/lamda_2 = 3/1;
20 //lamda = C/F;
21 //therefore F1/F2 = 1/3 ;
22
23
24 //Output
25 mprintf('Ratio of Operating Frequencies of two
    Radars are (F1/F2) = 1/3 ');

```

---

### Scilab code Exa 3.8 FINDING RATIO OF PRFs

```

1 //Chapter -3, Problem 3.8 , Page107
2 //

```

---

```

3  clc;
4  clear;
5
6  //INPUT DATA
7
8  Vb1 = 20; //first blind speed in m/s
9  Vb2 = 30; //second blind speed in m/s
10 n1 = 1; //since first blindspeed
11 n1 = 2; //since second blindspeed
12 lamda = 3*10^-2; //wavelength in m;
13 //Calculations
14
15 PRF1 = (2*Vb2)/(n1*lamda); //pulse repetitive
    frequency in Hz of First Radar;
16
17 PRF2 = (2*Vb2)/(n1*lamda); //pulse repetitive
    frequency in Hz of Second Radar;
18
19
20 //Output
21 mprintf('Ratio of pulse repetitive frequencies of
    the Radars is PRF1/PRF2 = %g',PRF1/PRF2);

```

---

### Scilab code Exa 3.9 FINDING BLIND SPEEDS

```

1 //Chapter-3, Problem 3.9 , Page107
2 //

```

---

```

3  clc;
4  clear;
5
6  //INPUT DATA
7  F = 6*10^9; //operating frequency in Hz
8  PRF= 1000; //pulse repetitive frequency in Hz

```

```

 9 Vo = 3*10^8;    //velocity in m/s;
10 n2 = 2;        // n value for second blind speed
11 n3 = 3;        // n value for third blind speed
12 //Calculations
13
14 lamda = Vo/F//Wavelength in m
15
16 // blind speed Vb = n*(lamda/2)*PRF in m/s
17
18 Vb2 = n2*(lamda/2)*PRF //second blind speed in m/s;
19 Vb21 = Vb2*18/5 ;      //second blind speed in kmph
    ;
20 Vb3 = n3*(lamda/2)*PRF //third blind speed in m/s;
21 Vb31 = Vb3*18/5;      //third blind speed in kmph;
22
23 //Output
24 mprintf('Second Blind Speed is %g kmph\n Third Blind
    Speed is %g kmph\n',Vb21,Vb31);

```

---

### Scilab code Exa 3.10 FINDING PEAK TX POWER

```

1 //Chapter-3 example 10
2 //


---


3 clc;
4 clear;
5 //input data
6 r          = 0.5;           //Antenna Radius in
    m
7 f          = 8*10^9        //operating
    frequency in Hz
8 Vo        = 3*10^8;        //vel. of EM wave in
    m/s
9 RCS       = 5;            // Radar cross

```

```

    section in m^2
10 D          = 1;           // antenna diameter
    in m
11 F          = 4.77;       // noise figure
    in dB
12 Rmax       = 12*10^3     // Radar range
13 BW         = 500*10^3;   // bandwidth
14
15 // Calculation
16 F1         = 10^(F/10)   // antilog
    calculation
17 lamda      = Vo/f        // wavelength
18
19 //Rmax      = 48*((Pt*D^4*RCS)/(BW*lamda*lamda*(F
    -1)))^0.25
20
21 Pt         = ((Rmax/48)^4)*((BW*lamda*lamda*(F1
    -1))/(D^4*RCS))
22
23 //Output
24 mprintf('Peak Transmitted Power is %e',Pt);
25 mprintf('\n Note: Calculation error in textbook at
    Pt 10^12 missing')
26 //

```

---

# Chapter 4

## TRACKING RADAR

Scilab code Exa 4.1 FINDING PHASE DIFFERENCE BETWEEN ECHOS

```
1 //Chapter-4 example 4.1
2 //


---


3 clc;
4 clear;
5 //input data
6 //d = lamda/2
7 theta_d = 5//angle blw los and perpendicular
   bisector of line joining two antennas
8
9 // calculations
10
11 //PD = (2*%pi/lamda)*(d*sin(theta));
12 //PD = (2*%pi/lamda)*(lamda/2*sin(theta));
13 theta_r = theta_d*(%pi/180)
14 PD_r = (2*%pi)*((sin(theta_r))/2);//phase
   difference in radians
15 PD_d = PD_r*(180/%pi);//phase difference in
   radians
16 //output
```

```

17 mprintf('Phase difference b/w two echo signals is %3
    .2f degrees; %3.3f radians ',PD_d,PD_r);
18
19 //=====end of the program
    =====

```

---

### Scilab code Exa 4.2 FINDING SPACING BETWEEN ANTENNAS

```

1 //Chapter-4 example 4.2
2 //
    =====

3 clc;
4 clear;
5 //input data
6 F      = 1*10^9;      //operating frequency of
    monopulse radar in Hz
7 Vo     = 3*10^8;     //velocity of EM wave in m/s
8 theta_d = 10        //angle blw los and
    perpendicular bisector of line joining two
    antennas
9 PD_d   = 20;        //phase difference in
    degrees
10
11 // calculations
12 lamda = Vo/F        //wavelength in m
13 //PD   = (2*%pi/lamda)*(d*sin(theta));
14 theta_r = theta_d*(%pi/180) //degree to radian
    conversion
15 PD_r    = PD_d*(%pi/180) //degree to radian
    conversion
16 d       = (PD_r*lamda)/(2*%pi*sin(theta_r));
17
18 //output
19 mprintf('Spacing between the antennas is %3.2f cms',

```

```
    d*100);  
20  
21 //=====end of the program  
    =====  


---


```



## Chapter 5

# FACTORS AFFECTING RADAR OPERATION AND RADAR LOSSES

Scilab code Exa 5.1 FINDING RCS

```
1 //Chapter-5 example 1
2 //


---


3 clc;
4 clear;
5 //input data
6 mprintf('mathematically ellipsoid is represented by
   \n((x/a)^2)+((y/b)^2)+((z/c)^2) = 1\n ');
7 mprintf(' \n The approximate expression for ellipsoid
   backscattered RCS is given by\n ');
8 mprintf(' \n      = ( *a^2 b^2 c^2) / [ a^2 (sin )^2 (
   cos )^2+ b^2 (sin )^2 (sin )^2+c^2 (cos )^2
   ]^2\n ');
9 mprintf(' \n if a = b ,the ellipsoid becomes Roll
   symmetric ,above eqn becomes\n ');
10 mprintf(' \n      = ( * b^4 c^2) / [ a^2 (sin )^2 + c^2
```

```

11      (cos )^2 ]^2\n');
12 //=====end of the program
=====

```

---

#### Scilab code Exa 5.4 FINDING RCS

```

1 //Chapter-5 example 4
2 //
=====

3 clc;
4 clear;
5 //input data
6 lamda = 0.03; //wavelength in m
7 Pt     = 250*10^3; //transmitter power
8 G      = 2000; //antenna gain
9 R      = 50*10^3; //maximum range
10 Pr    = 10*10^-12; //minimum detectable power
11 //Calculations
12 Ae    = (lamda*lamda*G)/(4*%pi); //effective
      aperture area
13 RCS   = (Pr*(4*%pi*R*R)^2)/(Pt*G*Ae); //Radar cross
      section of the target
14
15 //output
16 mprintf('Radar cross section of the target is %3.2f
      m^2 ',RCS);
17
18 //=====end of the program
=====

```

---

# Chapter 6

## RADAR TRANSMITTERS

Scilab code Exa 6.1 FINDING MAX POWER

```
1 //Chapter-6 example 1
2 //


---


3 clc;
4 clear;
5 //input data
6 F      = 9*10^9; //Reflex Klystron operating frequency
           in hz
7 Va     = 300; //beam voltage in volts
8 I      = 20; //Beam current in mA
9 n      = 1; // for 7/4 mode
10
11 //Calculations
12 //transit time for reflector space = n+3/4
13 I1     = I*10^-3; //beam current in mA
14 Prfmax = (0.3986*I1*Va)/(n+3/4); //maximum RF
           power
15 //Output
16 mprintf('Maximum R-F power is %3.3f Watts',Prfmax);
17
```

```
18 //=====end of the program
```

---

**Scilab code Exa 6.2** FINDING GAIN PARAMETER OUTPUT POWER  
GAIN AND Be

```
1 //Chapter-6 example 2
2 //
3 clc;
4 clear;
5 //input data
6 Vdc = 2.5*10^3; //Beam voltage
7 Idc = 25*10^-3; //beam current in A;
8 Zo = 10; //charecteristic impedance
9 F = 9.5*10^9; //TWT operating frequency in hz
10 N = 40; //circuit length
11
12 //Calculations
13 C = ((Idc*Zo)/(4*Vdc))^(1/3); //gain parameter
14 Ap = -9.54+(47.3*N*C); //Output power gain of twt
15 w = 2*%pi*F;
16 vdc = 0.593*10^6*sqrt(Vdc);
17 Be = w/vdc;
18 //Output
19 mprintf('Gain parameter is %3.3f\n Output Power gain
        is %3.3f dB\n phase constant of electron beam is
        %e rad/m',C,Ap,Be);
20
21 //=====end of the program
```

---

**Scilab code Exa 6.3** FINDING CYCLOTRON ANGULAR FREQ AND CUTOFF VOLTAGE

```
1 //Chapter-6 example 3
2 //


---


3 clc;
4 clear;
5 //input data
6 e = 1.609*10^-19; //charge of electron
7 me = 9.109*10^-31; //mass of electron in kg
8 B = 0.40; //magnetic flux density
9 b = 10*10^-2; //Radius of vane edge from the centre
10 a = 4*10^-2; //radius of cathode
11
12 //Calculations
13 Wc = (e/me)*B; //cyclotron angular frequency in
    radians
14 Vc = (e/(8*me))*(B^2)*(b^2)*(1-(a/b)^2)^2; //cut-off
    voltage
15 //Output
16 mprintf('Cyclotron Angular Frequency is %g rad\n Cut
    -off voltage is %g V\n',Wc,Vc);
17 mprintf(' Note:Cut-off voltage obtained in textbook
    is wrongly calculated.Instead of (a/b)^2 ,(a/b)
    is calculated ');
18
19 //=====end of the program


---


```

**Scilab code Exa 6.4** FINDING ELECTRON VELOCITY TRANSIT AN-  
GLE AND BEAM COUPLING COEFFICIENT

```
1 //Chapter-6 example 4
```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 Va = 900 ;//Accelerating voltage in volts
7 F = 3.2*10^9;//operating frequency
8 d = 10^-3;
9 //Calculations
10 Ve = (0.593*10^6)*sqrt(Va);//electron velocity
11 w = 2*%pi*F;
12 theta = w*(d/Ve);//transit angle in radians
13 Be = sin(theta/2)/(theta/2);//Beam Coupling Co-
    efficient
14 //output
15 mprintf('Electron Velocity is %g m/s\n Transit Angle
    is %g rad\n Beam Coupling Co-efficient is %3.3f
    ',Ve,theta,Be);
16 //====end of the program


---



```

### Scilab code Exa 6.5 FINDING EFFICIENCY

```

1 //Chapter-6 example 5
2 //


---


3 clc;
4 clear;
5 //input data
6 I2 = 28*10^-3 ;//induced current in amperes
7 V2 = 850; //fundamental component of catcher-gap
    voltage
8 Vb = 900; //beam voltage

```

```

9 Ib = 26*10^-3; //beam current
10 Bc = 0.946; //beam coupling coefficient of catcher
    gap
11 // Calculations
12 n = ((Bc*I2*V2)/(2*Ib*Vb))*100; //efficiency of
    klystron
13 //output
14 mprintf('Efficiency of the klystron is %g \n',n);
15 mprintf(' Note:In textbook Bc value is taken as
    0.946 in calculation ')
16 //=====end of the program
    =====

```

---

#### Scilab code Exa 6.6 FINDING FREQ OF IMPATT DIODE

```

1 //Chapter-6 example 6
2 //
    =====

3 clc;
4 clear;
5 //input data
6 Vd = 2.2*10^5; //Carrier Drift Velocity in m/s
7 l = 5*10^-6; //drift region length
8 // Calculations
9 F = Vd/(2*l); //frequency of IMPATT Diode
10 //output
11 mprintf('Frequency of IMPATT Diode is %g Ghz ',F
    /10^9);
12 //=====end of the program
    =====

```

---

#### Scilab code Exa 6.7 FINDING FREQ OF IMPATT DIODE

```

1 //Chapter-6 example 7
2 //


---


3 clc;
4 clear;
5 //input data
6 Vd = 3*10^5; //Carrier Drift Velocity in m/s
7 l = 7*10^-6; //drift region length
8 //Calculations
9 F = Vd/(2*l); //frequency of IMPATT Diode
10 //output
11 mprintf('Frequency of IMPATT Diode is %3.2f Ghz',F
    /10^9);
12 //=====end of the program


---



```

#### Scilab code Exa 6.8 FINDING AVALANCHE ZONE VELOCITY

```

1 //Chapter-6 example 8
2 //


---


3 clc;
4 clear;
5 //input data
6 Na = 1.8*10^15; //Doping Concentration
7 J = 25*10^3; //current density in A/cm^2
8 q = 1.6*10^-19; //charge of electron
9 //Calculations
10 Vaz = J/(q*Na); //Avalanche Zone Velocity
11 //output
12 mprintf('Avalanche Zone Velocity of TRAPATT is %g\n',
    Vaz);
13 mprintf(' Note: wrong calculation done in Textbook')

```



```
14 ;  
//=====end of the program  
=====
```

---

### Scilab code Exa 6.9 FINDING FREQ OG GUNN DIODE OSCILLATOR

```
1 //Chapter-6 example 9  
2 //  
=====
```

```
3 clc;  
4 clear;  
5 //input data  
6 l = 12*10^-3; //gunn diode oscillator length in m  
7 Vd = 2*10^8; //Drift velocity in gunn diode  
8 //Calculations  
9 F = Vd/l; //Frequency of Gunn Diode Oscillator  
10 //output  
11 mprintf('Frequency of Gunn Diode Oscillator is %3.2 f  
Ghz', F/10^9);  
12  
13 //=====end of the program  
=====
```

---

### Scilab code Exa 6.10 FINDING MIN OPERATING GUNN DIODE VOLT-AGE

```
1 //Chapter-6 example 10  
2 //
```

---

```
3 clc;  
4 clear;
```

```
5 //input data
6 l = 2.5*10^-6;//Drift length of gunn diode in m
7 Vd = 2*10^8;//Drift velocity in gun diode
8 Vgmin = 3.3*10^3;//minimum voltage gradient required
   to start the diode
9 //Calculations
10 Vmin = Vgmin*l;
11
12 //output
13 mprintf('Minimum Voltage required to operate gunn
   diode is %g mV',Vmin*10^3);
14 //=====end of the program
```

---

# Chapter 7

## RADAR RECEIVERS

Scilab code Exa 7.1 FINDING PROBABILITY OF FALSE ALARM

```
1 //Chapter-7 example 1
2 //


---


3 clc;
4 clear;
5 //input data
6 BW = 0.5*109; //bandwidth of pulsed radar in hz
7 Tfa = 10; //false alarm time in minutes
8
9 //Calculations
10 Tfa1 = Tfa*60; //false alarm time in seconds
11 Pfa = 1/(BW*Tfa1)
12 //Output
13 mprintf('probability of false alarm is %g',Pfa);
14
15 //=====end of the program


---


```

### Scilab code Exa 7.2 FINDING RADAR INTEGRATION TIME

```
1 //Chapter-7 example 2
2 //


---


3 clc;
4 clear;
5 //input data
6 BW = 1*10^9; //bandwidth of pulsed radar in hz
7
8 //Calculations
9 Tint = 1/BW; //radar integration time in sec
10 //Output
11 mprintf('Radar integration time is %g nsec',Tint
    *10^9);
12
13 //=====end of the program


---


```

### Scilab code Exa 7.5 FINDING RANGE RESOLUTION

```
1 //Chapter-7 example 5
2 //


---


3 clc;
4 clear;
5 //input data
6 BW = 0.5*10^9; //Bandwidth of waveform in Hz
7 PW = 5*10^-3; //pulse width in sec
8 Vo = 3*10^8; //velocity of EM wave
9
10 //Calculations
11
```

```

12 RR      = (Vo*PW)/2 ; //Range Resolution in m before
      compression
13
14 //RR    = Vo*tn1/2 ;
15 tn1     = 1/BW ;
16 RRc     = (Vo*tn1)/2 ; //Range Resolution in m after
      compression
17
18 //output
19
20 mprintf('Range Resolution before compression = %e m\
      n Range Resolution before compression = %3.2 f m\n
      ',RR,RRc );
21 mprintf(' Note: Wrong Calculation in Textbook');

```

---

**Scilab code Exa 7.8** RANGE RESOLUTION BEFORE AND AFTER COMPRESSION

```

1 //Chapter-7 example 8
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 BW      = 0.3*10^9; //Bandwidth of waveform in Hz
7 PW      = 3*10^-3; //pulse width in sec
8 Vo      = 3*10^8; //velocity of EM wave
9
10 //Calculations
11
12 RR      = (Vo*PW)/2 ; //Range Resolution in m before
      compression
13
14 //RR    = Vo*tn1/2 ;

```

```

15 tn1      = 1/BW ;
16 RRc      = (Vo*tn1)/2 ; //Range Resolution in m after
      compression
17
18 //output
19
20 mprintf('Range Resolution before compression = %e m\
      n Range Resolution before compression = %3.2 f m\n
      ',RR,RRc );

```

---

### Scilab code Exa 7.9 FINDING MIN RECEIVABLE SIGNAL

```

1 //Chapter-7 example 9
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 BW      = 2*10^6;      //Radar Bandwidth in Hz
7 Fn      = 9;          //Noise Figure in dB
8 k       = 1.38*10^-23; //Boltzmann constant
9 To      = 290;        //Temperature in kelvin
10
11 //Antilog Calculation
12 // 10*log10(Fn) = 9
13 //Fn          = antilog(9/10) ;
14 Fn       = 10^(9/10)
15
16 MRS      = k*To*BW*(Fn-1); //Minimum Receivable signal
17
18 //Output
19
20 mprintf('Minimum Receivable signal(MRS) = %3.4 f PW'
      ,MRS*10^12);

```

```
21 mprintf('\n Note: Calculation error in Textbook');
```

---

# Chapter 9

## RADAR ANTENNAS

Scilab code Exa 9.1 FINDING BEAMWIDTHS

```
1 //Chapter-9 example 1
2 //


---


3 clc;
4 clear;
5 //input data
6 Da = 2.5; //diameter of parabolic antenna in m
7 F = 5*10^9; //radar operating frequency in hz
8 Vo = 3*10^8; //velocity of EM wave in m/s
9
10 //Calculations
11 lamda = Vo/F; //wavelength
12 NNBW = 140*(lamda/Da);
13 HPBW = 70*(lamda/Da); //half power beamwidth in deg
14
15 //Output
16 mprintf('NNBW of parabolic reflector is %g degrees\n
17         HPBW of parabolic reflector is %g degrees', NNBW,
18         HPBW);
```



```
18 //=====end of the program
```

---

### Scilab code Exa 9.2 FINDING GAIN OF PARABOLIC REFLECTOR

```
1 //Chapter-9 example 2
2 //
3 clc;
4 clear;
5 //input data
6 Da = 2.5; //diameter of parabolic antenna in m
7 F = 5*10^9; //radar operating frequency in hz
8 Vo = 3*10^8; //velocity of EM wave in m/s
9
10 //Calculations
11 lamda = Vo/F; //wavelength
12 Gp = 6.4*(Da/lamda)^2 //gain of parabolic
    reflector
13 G = 10*log10(Gp) //gain in dB
14 //Output
15 mprintf('Gain of parabolic reflector is %3.2f dB',G)
    ;
16
17 //=====end of the program
```

---

### Scilab code Exa 9.3 FINDING NNBW HPBW AND POWER GAIN OF ANTENNA

```
1 //Chapter-9 example 3
```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 Da    = 0.15; //diameter of parabolic antenna in m
7 F     = 9*10^9; //radar operating frequency in hz
8 Vo    = 3*10^8; //velocity of EM wave in m/s
9
10 //Calculations
11 lamda = Vo/F; //wavelength
12 Gp     = 6.4*(Da/lamda)^2 //gain of parabolic
    reflector
13 G      = 10*log10(Gp) //gain in dB
14 NNBW   = 140*(lamda/Da);
15 HPBW   = 70*(lamda/Da); //half power bandwidth in deg
16
17 //Output
18 mprintf('NNBW of parabolic reflector is %3.2f
    degrees\n HPBW of parabolic reflector is %3.2f
    degrees\n', NNBW, HPBW);
19
20 mprintf(' Gain of parabolic reflector is %3.2f dB', G
    );
21
22 //=====end of the program


---



```

#### Scilab code Exa 9.4 FINDING POWER GAIN

```

1 //Chapter-9 example 4
2 //


---



```

```

3  clc;
4  clear;
5  //input data
6  Da    = 2; //diameter of parabolic antenna in m
7  F     = 2*10^9; //radar operating frequency in hz
8  Vo    = 3*10^8; //velocity of EM wave in m/s
9
10 //Calculations
11 lamda = Vo/F; //wavelength
12 Gp     = 6.4*(Da/lamda)^2 //gain of parabolic
    reflector
13 G      = 10*log10(Gp) //gain in dB
14 //Output
15 mprintf('Gain of parabolic reflector is %3.2f dB',G)
    ;
16
17 //=====end of the program
    =====

```

---

**Scilab code Exa 9.5 FINDING MOUTH DIAMETER HPBW AND POWER GAIN OF PARABOLOID**

```

1  //Chapter-9 example 5
2  //
    =====

3  clc;
4  clear;
5  //input data
6  F     = 6*10^9; //radar operating frequency in hz
7  Vo    = 3*10^8; //velocity of EM wave in m/s
8  NNBW  = 5; //Null to Null beamwidth
9
10 //Calculations
11 lamda = Vo/F; //wavelength

```

```

12
13 Da = 140*(lamda/NNBW);
14 HPBW = 70*(lamda/Da); //half power beamwidth in deg
15 Gp = 6.4*(Da/lamda)^2 //gain of parabolic
    reflector
16 G = 10*log10(Gp) //gain in dB
17
18 //Output
19 mprintf('Mouth Diameter of paraboloid is %g m\n HPBW
    of parabolic reflector is %g degrees\n',Da,HPBW)
    ;
20
21 mprintf(' Gain of parabolic reflector is %g dB\n
    Gain of parabolic reflector is %g ',G,Gp);
22
23 //=====end of the program
    =====

```

---

**Scilab code Exa 9.6** FINDING BEAMWIDTH DIRECTIVITY AND CAPTURE AREA

```

1 //Chapter-9 example 6
2 //
    =====

3 clc;
4 clear;
5 //input data
6 F = 9*10^9; //radar operating frequency in hz
7 Vo = 3*10^8; //velocity of EM wave in m/s
8 NNBW = 5; //Null to Null beamwidth
9 Da = 5; //diameter of antenna in m
10
11 //Calculations
12 lamda = Vo/F; //wavelength

```

```

13 A      = (%pi*Da*Da)/4; //actual area of antenna
14 Ac     = 0.65*A; //Capture Area
15
16 D      = 6.4*(Da/lamda)^2; //directivity of antenna
17 D1     = 10*log10(D) //gain in dB
18 HPBW   = 70*(lamda/Da); //half power beamwidth in deg
19 NNBW   = 2*HPBW; //null to null beamwidth
20
21 //Output
22 mprintf('HPBW of parabolic reflector is %g degrees\n
          NNBW of parabolic reflector is %g degrees\n
          Directivity is %g dB\n Capture area is %g m^2',
          HPBW, NNBW, D1, Ac);
23
24
25 //=====end of the program

```

---

**Scilab code Exa 9.7** FINDING MIN DISTANCE REQUIRED BETWEEN TWO ANTENNAS

```

1 //Chapter-9 example 7
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 Da    = 5; //diameter of parabolic antenna in m
7 F     = 5*10^9; //radar operating frequency in hz
8 Vo    = 3*10^8; //velocity of EM wave in m/s
9
10 //Calculations
11 lamda = Vo/F; //wavelength
12 R     = (2*Da*Da)/lamda; //min distance b/w antennas

```

```

13 //Output
14 mprintf('Minimum distance Required is %g m',R);
15
16 //=====end of the program

```

---

**Scilab code Exa 9.8** FINDING MOUTH DIAMETER AND BEAM WIDTH OF ANTENNA

```

1 //Chapter-9 example 8
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6
7 F      = 4*10^9; //radar operating frequency in hz
8 Vo     = 3*10^8; //velocity of EM wave in m/s
9 Gp     = 500; //power gain of antenna
10 //Calculations
11 lamda  = Vo/F; //wavelength
12 Da     = lamda*(Gp/6.4)^0.5 //diameter of parabolic
      antenna in m
13
14 NNBW   = 140*(lamda/Da); //beamwidth b/w null to null
15 HPBW   = 70*(lamda/Da); //half power beamwidth in deg
16
17 //Output
18 mprintf('NNBW of parabolic reflector is %3.2f
      degrees\n HPBW of parabolic reflector is %3.2
      fdegrees\n ',NNBW,HPBW);
19
20 mprintf(' Mouth diameter of parabolic reflector is
      %3.2 f m',Da);

```

```

21
22 //=====end of the program

```

---

**Scilab code Exa 9.9 FINDING CAPTURE AREA AND BEAMWIDTH OF ANTENNA**

```

1 //Chapter-9 example 9
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6
7 F      = 9*10^9; //radar operating frequency in hz
8 Vo     = 3*10^8; //velocity of EM wave in m/s
9 Gp     = 100; //power gain of antenna in dB
10 //Calculations
11 lamda  = Vo/F; //wavelength
12 //antilog calculation
13 //100 = 10log10(Gp);
14 //10  = log(Gp);
15 G      = 10^10; //gain of antenna
16 Da     = lamda*sqrt(G/6.4) //diameter of parabolic
      antenna in m
17 A      = (%pi*Da*Da)/4; //Area of antenna
18 Ac     = 0.65*A; //capture area
19 NNBW   = 140*(lamda/Da); //beamwidth b/w null to null
20 HPBW   = 70*(lamda/Da); //half power beamwidth in deg
21
22 //Output
23 mprintf('NNBW of parabolic reflector is %g degrees\n
      HPBW of parabolic reflector is %g degrees\n',
      NNBW, HPBW);

```

```

24
25 mprintf(' \n Mouth diameter of parabolic reflector is
      %3.3f m\n Capture area is %3.2f m^2 ',Da,Ac);
26
27 //=====end of the program
      =====

```

---

### Scilab code Exa 9.10 FINDING BEAMWIDTH AND POWER GAIN

```

1 //Chapter-9 example 10
2 //
      =====

3 clc;
4 clear;
5 //input data
6 F      = 10*109; //radar operating frequency in hz
7 Vo     = 3*108; //velocity of EM wave in m/s
8 Da     = 5; //antenna diameter in m
9
10 //Calculations
11 lamda = Vo/F; //wavelength
12 Gp     = 6.4*(Da/lamda)2 //gain of parabolic
      reflector
13 G      = 10*log10(Gp) //gain in dB
14
15 BWFN   = 140*(lamda/Da); //beam width b/n nulls
16 HPBW   = 70*(lamda/Da); //half power beamwidth in deg
17
18
19 //Output
20 mprintf('BWFN of parabolic reflector is %g degrees\n
      HPBW of parabolic reflector is %g degrees\n',
      BWFN ,HPBW);
21

```



```

22 mprintf(' Gain of parabolic reflector is %g dB ',G);
23
24 //=====end of the program
=====

```

---

### Scilab code Exa 9.11 FINDING POWER GAIN

```

1 //Chapter-9 example 11
2 //
=====

3 clc;
4 clear;
5 //input data
6 F      = 10*10^9;//radar operating frequency in hz
7 Vo     = 3*10^8;//velocity of EM wave in m/s
8 IE     =0.6;//illumination efficiency
9 Da     =12;//diameter of antenna
10 //Calculations
11 lamda  = Vo/F;//wavelength
12 Gp     = IE*(Da/lamda)^2//gain of parabolic reflector
13 G      = 10*log10(Gp)//gain in dB
14
15 //Output
16 mprintf(' Gain of parabolic reflector is %3.2f dB',G
    );
17
18 //=====end of the program
=====

```

---

### Scilab code Exa 9.12 FINDING MOUTH DIAMETER AND CAPTURE AREA

```

1 //Chapter-9 example 12
2 //


---


3 clc;
4 clear;
5 //input data
6
7 F      = 4*109; //radar operating frequency in hz
8 Vo     = 3*108; //velocity of EM wave in m/s
9 NNBW   = 8; //Null to Null beamwidth in degrees
10 //Calculations
11 lamda  = Vo/F; //wavelength
12 Da     = (140*lamda)/NNBW;
13 A      = (%pi*Da*Da)/4; //Area of antenna
14 Ac     = 0.65*A; //capture area
15
16 //Output
17 mprintf(' \n Mouth diameter of parabolic reflector is
          %3.3f m \n Capture area is %3.2f m2 ',Da,Ac);
18
19 //=====end of the program


---



```

### Scilab code Exa 9.13 FINDING MOUTH DIAMETER AND POWER GAIN

```

1 //Chapter-9 example 13
2 //


---


3 clc;
4 clear;
5 //input data
6 F      = 4*109; //radar operating frequency in hz
7 Vo     = 3*108; //velocity of EM wave in m/s

```

```

8 NNBW = 2; // Null to Null Beamwidth in degrees
9
10 // Calculations
11 lamda = Vo/F; // wavelength
12 Da = (140*lamda)/2; // diameter of antenna in m
13 Gp = 6.4*(Da/lamda)^2 // gain of parabolic
    reflector
14 G = 10*log10(Gp) // gain in dB
15
16
17 // Output
18 mprintf('Gain of parabolic reflector is %g dB\n
    mouth diameter of the antenna is %g m ',G, Da);
19
20 //=====end of the program
    =====

```

---

#### Scilab code Exa 9.14 FINDING BEAMWIDTH AND POWERGAIN

```

1 // Chapter-9 example 14
2 //
    =====
3 clc;
4 clear;
5 //input data
6
7 HPBW = 6; // Half power Beamwidth in degrees
8
9 // Calculations
10 NNBW = 2*HPBW; // Null to Null beamwidth in degrees
11 //HPBW = 70*(lamda/Da);
12 //(70/HPBW)= (Da/lamda);
13 Gp = 6.4*(70/HPBW)^2 // gain of parabolic reflector
14 G = 10*log10(Gp) // gain in dB

```

```

15
16
17 //Output
18 mprintf('Gain of parabolic reflector is %3.2f dB\n
        NNBW of the antenna is %g degrees',G,NNBW);
19
20 //=====end of the program

```

---

### Scilab code Exa 9.15 FINDING POWER GAIN

```

1 //Chapter-9 example 15
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 //Da = 6*lamda;
7
8 //Calculations
9
10 //Gp = 6.4*(Da/lamda)^2; //power gain
11
12 //Gp = 6.4*(6*lamda/lamda)^2 //power gain of
    parabolic reflector
13 Gp = 6.4*(6)^2;
14 G = 10*log10(Gp)//gain in dB
15
16
17 //Output
18 mprintf('Gain of parabolic reflector is %3.2f dB\n',
        G);
19
20 //=====end of the program

```

---

---

**Scilab code Exa 9.16** FINDING BEAMWIDTH AND DIRECTIVITY OF ANTENNA

```
1 //Chapter-9 example 16
2 //
3 clc;
4 clear;
5 //input data
6 //Da = 7*lamda; diameter of antenna
7
8 //Calculations
9 //HPBW = 70*(lamda/Da)
10 //HPBW = 70*(lamda/(7*lamda));
11 HPBW = 70/7; //half power beamwidth
12 NNBW = 2*HPBW; //null to null beamwidth
13 //Gp = 6.4*(Da/lamda)^2; //power gain
14
15 //Gp = 6.4*((7*lamda)/lamda)^2 ; power gain of
    parabolic reflector
16 Gp = 6.4*(7)^2;
17 G = 10*log10(Gp) //gain in dB
18
19
20 //Output
21 mprintf('Gain of parabolic reflector is %3.1f \n
    HPBW of Antenna is %3.1f degrees\n NNBW of
    Antenna is %3.1f degrees ', Gp, HPBW, NNBW);
22
23 //=====end of the program
```

---

---

**Scilab code Exa 9.17 FINDING BEAMWIDTH POWERGAIN AND DIRECTIVITY**

```
1 //Chapter-9 example 17
2 //


---


3 clc;
4 clear;
5 //input data
6 F      = 8*10^9;//radar operating frequency in hz
7 Vo     = 3*10^10;//velocity of EM wave in cm/s
8 D      = 9;//pyramida horn diameter in cm
9 W      = 4;//pyramida horn width in cm
10 //Calculations
11 lamda = Vo/F//wavelength in cm
12 HPBW_E = 56*(lamda/D)//halfpower beamwidth in E-
    plane;
13 HPBW_H = 67*(lamda/W)//halfpower beamwidth in H-
    plane;
14 Gp      = (4.5*W*D)/(lamda*lamda);//power gain
15 G       = 10*log10(Gp);//power gain in dB
16 Di      = (7.5*W*D)/(lamda*lamda);//directivity
17
18
19 //Output
20 mprintf('Halfpower beamwidth in E-plane is %3.2f
    degrees\n Halfpower beamwidth in H-plane is %3.2f
    degrees\n Powergain is %3.2f dB\n Directivity is
    %3.2f ',HPBW_E,HPBW_H,G,Di);
21
22
23 //=====end of the program


---


```

### Scilab code Exa 9.18 FINDING POWER GAIN OF HORN ANTENNA

```
1 //Chapter-9 example 18
2 //


---


3 clc;
4 clear;
5 //input data
6 //Aperture size = 10*lamda
7 //Calculations
8 //Gp = (4.5*W*D)/(lamda*lamda);
9 //Gp = (4.5*(10*lamda)*(10*lamda))/(lamda*lamda);
10 Gp = (4.5*10*10); //power gain of square horn
    antenna
11 G = 10*log10(Gp); //power gain in dB
12
13 //Output
14 mprintf('Power Gain of Square Horn Antenna is %3.2f
    dB',G);
15 //=====end of the program


---


```

### Scilab code Exa 9.19 FINDING POWER GAIN AND DIRECTIVITY

```
1 //Chapter-9 example 19
2 //


---


3 clc;
4 clear;
5 //input data
```

```

6 F      = 8*10^9; //radar operating frequency in hz
7 Vo     = 3*10^10; //velocity of EM wave in cm/s
8 D      = 10; //pyramida horn diameter in cm
9 W      = 5; //pyramida horn width in cm
10 //Calculations
11 lamda = Vo/F //wavelength in cm
12 Gp     = (4.5*W*D)/(lamda*lamda); //power gain
13 G      = 10*log10(Gp); //power gain in dB
14 Di     =(7.5*W*D)/(lamda*lamda); //directivity
15 DI     =10*log10(Di); //Directivity in dB
16
17
18 //Output
19 mprintf('Powergain is %3.2f dB\n Directivity is %3.2
        f dB',G,DI);
20
21
22 //=====end of the program
=====

```

---

### Scilab code Exa 9.20 FINDING COMPLEMENTARY SLOT IMPEDANCE

```

1 //Chapter-9 example 20
2 //
=====

3 clc;
4 clear;
5 //input data
6 no     = 377; //Free space intrinsic impedance in ohms
7 Zd1    = 73+50*i; //dipole impedance;
8 Zd2    = 70; //dipole impedance;
9 Zd3    = 800; //dipole impedance;
10 Zd4   = 400 //dipole impedance;
11 Zd5   = 50+10*i; //dipole impedance;

```



```

12 Zd6    = 50-30*i; //dipole impedance;
13 Zd7    = 350; //dipole impedance;
14
15 //Calculations
16 K      = (no^2)/4;
17 //Zs   = (no*no)/(4*Zd); slot impedance
18 Zs1    = K/Zd1 //slot impedance
19 Zs2    = K/Zd2; //slot impedance
20 Zs3    = K/Zd3; //slot impedance
21 Zs4    = K/Zd4; //slot impedance
22 Zs5    = K/Zd5; //slot impedance
23 Zs6    = K/Zd6; //slot impedance
24 Zs7    = K/Zd7; //slot impedance
25
26 //output
27
28 mprintf('slot impedance if Zd = 73+i50 ohm is '),
    mprintf( prettyprint(Zs1)),mprintf(' ohm \n');
29 mprintf(' slot impedance if Zd = 70      ohm is '),
    mprintf( prettyprint(Zs2)),mprintf(' ohm \n');;
30 mprintf(' slot impedance if Zd = 800      ohm is '),
    mprintf( prettyprint(Zs3)),mprintf(' ohm \n');;
31 mprintf(' slot impedance if Zd = 400      ohm is '),
    mprintf( prettyprint(Zs4)),mprintf(' ohm \n');;
32 mprintf(' slot impedance if Zd = 50+i10 ohm is '),
    mprintf( prettyprint(Zs5)),mprintf(' ohm \n');;
33 mprintf(' slot impedance if Zd = 50-i30 ohm is '),
    mprintf( prettyprint(Zs6)),mprintf(' ohm \n');;
34 mprintf(' slot impedance if Zd = 350      ohm is '),
    mprintf( prettyprint(Zs7)),mprintf(' ohm \n');;
35
36
37
38 //=====end of the program

```

---

**Scilab code Exa 9.21** FINDING RADIATION RESISTANCE OF HERTZIAN  
DIPOLE

```
1 //Chapter-9 example 21
2 //


---


3 clc;
4 clear;
5 //input data
6
7 //dl1 = lamda/20;
8 //dl2 = lamda/30;
9 //dl3 = lamda/40;
10
11 //Calculations
12 //Rr = 80*(pi*pi)*(dl/lamda)^2 Radiation Resistance
    in ohms
13 //Rr1 = 80*(pi*pi)*(dl1/lamda)^2 Radiation
    Resistance in ohms
14 //Rr1 = 80*(pi*pi)*((lamda/20)/lamda)^2 Radiation
    Resistance in ohms
15 Rr1 =80*(%pi*%pi)*(1/20)^2 ;
16 //Rr2 = 80*(pi*pi)*(dl2/lamda)^2 Radiation
    Resistance in ohms
17 //Rr2 = 80*(pi*pi)*((lamda/30)/lamda)^2 Radiation
    Resistance in ohms
18 Rr2 =80*(%pi*%pi)*(1/30)^2 ;
19 //Rr3 = 80*(pi*pi)*(dl3/lamda)^2 Radiation
    Resistance in ohms
20 //Rr3 = 80*(pi*pi)*((lamda/40)/lamda)^2 Radiation
    Resistance in ohms
21 Rr3 =80*(%pi*%pi)*(1/40)^2 ;
22
```

```

23
24 //Output
25 mprintf('If Hertzian dipole length is lamda/20 then
    Radiation Resistance = %3.3f ohm\n If Hertzian
    dipole length is lamda/30 then Radiation
    Resistance = %3.3f ohm\n If Hertzian dipole
    length is lamda/40 then Radiation Resistance = %3
    .3 f ohm\n',Rr1,Rr2,Rr3) ;
26
27 //=====end of the program
=====

```

### Scilab code Exa 9.22 DIRECTIVITY OF HALFWAVE DIPOLE

```

1 //Chapter-9 example 22
2 //
=====

3 clc;
4 clear;
5 disp('For half wave dipole Emax = 60I/r');
6 disp('But Pr = 73 I^2 Watts');
7 disp('For Pr = 1 W');
8 disp('I = 1/sqrt(73)');
9 disp('Emax = (60/r)*I');
10 disp('Gdmax = (4*pi*phi)/Pr'),disp('as Pr =1 and phi
    = (r^2)*(E^2)/no')
11 disp('Gdmax = 4*pi*(r^2)*(E^2)/no');
12 disp('      = (4*pi*(r^2)*60*60)/(no*r*r*73)');
13 disp('      = (4*pi*60*60)/(120*pi*73)');
14 Gdmax      = 120/73;
15
16 mprintf('Directivity of half wave dipole is %3.2f',
    Gdmax );
17 //=====end of program

```

---

---

**Scilab code Exa 9.23 FINDING RADIATED POWER**

```
1 //Chapter-9 example 23
2 //
3 clc;
4 clear;
5 //input data
6 F = 12*10^9; //operating frequency in Ghz
7 I = 2; //current in amperes
8 Rr = 300; //radiation resistance in ohms
9
10 //Calculations
11 Pr = I*I*Rr;
12
13 //output
14 mprintf('Radiated Power is %3.1f Watts',Pr);
15
16 //=====end of the program
```

---

**Scilab code Exa 9.24 FINDING EFFECTIVE AREA OF HALF WAVE  
DIPOLE**

```
1 //Chapter-9 example 24
2 //
3 clc;
```

```

4 clear;
5 //input data
6 F      = 600*10^6; //radar operating frequency in hz
7 Vo     = 3*10^8; //velocity of EM wave in m/s
8 D      = 1.644; //Directivity of the half wave dipole
9 //Calculations
10 lamda = Vo/F; //wavelength
11 Ae     = (lamda^2*D)/(4*pi); //effective area of
        antenna
12 //Output
13 mprintf('Effective Area of the antenna is %3.4f m^2',
        ,Ae);
14
15 //=====end of the program
        =====

```

---

#### Scilab code Exa 9.25 FINDING EFFECTIVE AREA OF HERTZIAN DIPOLE

```

1 //Chapter-9 example 25
2 //
        =====

3 clc;
4 clear;
5 //input data
6 F      = 200*10^6; //radar operating frequency in hz
7 Vo     = 3*10^8; //velocity of EM wave in m/s
8 D      = 1.5; //Directivity of the Hertzian dipole
9 //Calculations
10 lamda = Vo/F; //wavelength
11 Ae     = (lamda^2*D)/(4*pi); //effective area of
        antenna
12 //Output
13 mprintf('Effective Area of the antenna is %3.4f m^2',
        ,Ae);

```

```
14  
15 //====end of the program
```

---

# Chapter 11

## SOLVED PROBLEMS

Scilab code Exa 11.1 FINDING RECEIVED SIGNAL POWER

```
1 //Chapter-11 example 1
2 //


---


3 clc;
4 clear;
5 //Given data
6 F = 10*109; //radar operating frequency in Hz
7 Vo = 3*108; //vel in m/s;
8 G = 20; //antenna gain in dBi;
9 R = 20*103; //distance of radar reflected signal
    from target
10 Pt = 10*103 //Tx power in watts
11 CS = 10; //cross sectional area in m2
12 // Calculations
13 Gain = 10(G/10) //G = 10log(Gain) ==>gain -
    antilog(20/10);
14 Gr = Gain; //gain of tx antenna and Rx antenna
15 Gt = Gain
16 lamda = Vo/F
17 Pr= (lamda*lamda*Pt*Gt*Gr*CS)/((4*4*4*%pi*%pi*%pi)*()
```

```

    R^4))//received power in watts
18
19 // Output
20 mprintf('Received signal Power is %g',Pr);
21 mprintf('\n Note : Calculation error in Textbook');

```

---

### Scilab code Exa 11.2 FINDING TARGET DISTANCE FROM RADAR

```

1 //Chapter-11 example 2
2 //
=====
3 clc;
4 clear;
5 Vo = 3*10^8;//velocity of EM wave in m/s
6 t = 20*10^-6;//echo time in sec
7 // calculations
8
9 R = (Vo*t)/2;//distance b/n target and Radar in m
10
11 // Output
12 mprintf('Distance of Target from the Radar is %g Km'
    ,R/1000 );
13
14 //=====end of program
=====

```

---

### Scilab code Exa 11.3 FINDING MAX AND MIN RANGES OF RADAR

```

1 //Chapter-11 example 3

```



```

2 //
=====

3 clc;
4 clear;
5 Vo = 3*10^8; //velocity of EM wave in m/s
6 F = 0.8*10^3; //pulse repetitive frequency
7 Tp = 1.2*10^-6; //pulse width in sec
8 //Calculations
9 Rmax = Vo/(2*F); //maximum Range of Radar in m
10 Rmin = (Vo*Tp)/2; //minimum Range of radar in m
11
12 //Output
13 mprintf('Maximum Range of Radar is %g Km\n Minimum
          Range of the Radar is %g m',Rmax/1000,Rmin);
14
15 //=====end of program
=====

```

---

#### Scilab code Exa 11.4 FINDING DUTY CYCLE

```

1 //Chapter-11 example 4
2 //
=====

3 clc;
4 clear;
5 PW = 1.5*10^-6; //pulse width in sec
6 PRF = 2000 //per second
7
8 //Calculations
9 Dc = PW*PRF; //duty cycle
10
11 //Output

```

```
12 mprintf('Duty Cycle is %e',Dc);
13 //=====end of program
```

---

### Scilab code Exa 11.5 FINDING AVERAGE TX POWER

```
1 //Chapter-11 example 5
2 //
//=====
3 clc;
4 clear;
5 PW = 2*10-6//pulse width in sec
6 PRF = 1000//pulse repetitive frequency
7 Pp = 1*106//peak power in watts
8
9 //Calculations
10 Dc = PW*PRF;//duty cycle
11 AvgTp = Pp*Dc;//average transmitted power in watts
12
13 //Output
14 mprintf('Average Transmitted power is %g KW',AvgTp
    /1000);
15
16 //=====end of program
```

---

### Scilab code Exa 11.6 FINDING RANGE RESOLUTION

```
1 //Chapter-11 example 6
```

```

2 //


---


3 clc;
4 clear;
5 PW = 2*10^-6; //pulse width in sec
6 Vo = 3*10^8; //velocity of EM wave in m/s
7
8 //Calculations
9
10 RR = (Vo*PW)/2; //Range Resolution in m
11
12 //Output
13 mprintf('Range Resolution is %g m',RR);
14
15 //=====end of program


---



```

### Scilab code Exa 11.7 FINDING TARGET RANGE

```

1 //Chapter-11 example 7
2 //


---


3 clc;
4 clear;
5 t = 50*10^-6; //echo time in sec
6 Vo = 3*10^8; //velocity of EM wave in m/s
7
8 //Calculations
9
10 R = (Vo*t)/2; //Range in m
11
12 //Output

```

```

13 mprintf('Target Range is %g Kms',R/1000);
14
15 //=====end of program

```

---

### Scilab code Exa 11.8 FINDING DOPPLER SHIFT

```

1 //Chapter-11 example 8
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 Tvel = 1000;//target speed in kmph
7 F     = 10*109;//radar operating frequency in hz
8 Vo    = 3*108;//velocity of EM wave in m/s
9
10 //Calculations
11 Vr    = 1000*(5/18);//target speed in m/s
12 Fd    = (2*Vr*F)/Vo;//Doppler Frequency shift in Hz
13
14 //Output
15 mprintf('Doppler Frequency shift Caused by aircraft
        is %3.2f KHz',Fd/1000);
16
17 //=====end of the program

```

---

### Scilab code Exa 11.9 FINDING DOPPLER SHIFT FREQUENCY

```

1 //Chapter-11 example 9

```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 F = 6*109; //Transmitting Frequency of Radar
7 Vr = 250; //velocity of automobile in Km/h
8 Vo = 3*108; //velocity of EM wave in m/s
9
10 //Calculations
11
12 Va = Vr*(5/18) //velocity of automobile in m/s
13 Fd = (2*Va*F)/Vo //Doppler Frequency shift in Hz
14
15 //Output
16 mprintf('Doppler Frequency shift is %3.3f KHz',Fd
17 /1000)
18 //=====end of the program


---



```

**Scilab code Exa 11.10 FINDING DOPPLERSHIFT FREQUENCY AND  
FREQ OF RELECTED ECHO**

```

1 //Chapter-11 example 10
2 //


---


3 clc;
4 clear;
5 //input data
6 F = 9*109; //Transmitting Frequency of Radar
7 Vr = 800; //velocity of aircraft in Km/h
8 Vo = 3*108; //velocity of EM wave in m/s

```

```

9
10 // Calculations
11
12 Va    = Vr*(5/18)//velocity of aircraft in m/s
13 Fd    = (2*Va*F)/Vo//Doppler Frequency shift in Hz
14 Fr    = F+Fd;//frequency of reflected echo in Hz
15 //Output
16 mprintf('Doppler Frequency shift is %g Hz\n
          frequency of reflected echo is %e Khz\n',Fd,Fr
          /1000)
17 mprintf('Note: doppler frequency shift wrongly
          printed in Text Book as 1333.3 Hz');
18 //=====end of the program
=====

```

---

**Scilab code Exa 11.11 FINDING DOPPLER SHIFT FREQUENCY AND FREQUENCY OF REFLECTED SIGNAL**

```

1 //Chapter-11 example 11
2 //
=====

3 clc;
4 clear;
5 //input data
6 F  = 2*10^9;//Transmitting Frequency of Radar
7 Vr = 350;//velocity of sports Car in Kmph
8 Vo = 3*10^8;//velocity of EM wave in m/s
9
10 // Calculations
11
12 Va    = Vr*(5/18)//velocity of aircraft in m/s
13 Fd    = (2*Va*F)/Vo//Doppler Frequency shift in Hz
14 //Car moving away from Radar
15 Fr    = F-Fd;//frequency of reflected signal in Hz

```

```

16
17 //Output
18 mprintf('Doppler Frequency shift is %g Hz\n
          frequency of reflected echo is %g Ghz - %g Hz\n',
          Fd,F/10^9,Fd)
19 mprintf(' Note: doppler frequency shift wrongly
          printed in Text Book as 129.6 Hz\n Vr is printed
          as 9.72 m/s instead of 97.2 m/s');
20 //=====end of the program

```

---

#### Scilab code Exa 11.12 FINDING AVERAGE POWER

```

1 //Chapter-11 example 12
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 PRF = 2000; //pulse repetition frequency per
           second
7 PW = 1*10^-6; //pulse width in sec
8 Pp = 500*10^3; //Peak power in watts
9
10 //Calculations
11 Dc = PW*PRF; //Duty Cycle
12 Pav = Pp*Dc; //average power in watts
13 pavdB = 10*log10(Pav);
14
15 //Output
16
17 mprintf('Average power is %g KW\n Average Power is
          %g dB',Pav/1000,pavdB);
18

```

```
19 //=====end of the program
```

---

**Scilab code Exa 11.13 FINDING DUTY CYCLE AVERAGE POWER AND MAX RANGE OF RADAR**

```
1 //Chapter-11 example 13
2 //
3 clc;
4 clear;
5 //input data
6 PRF = 1000; //pulse repetition frequency per
   second
7 PW = 0.8*10^-6; //pulse width in sec
8 Pp = 10*10^6; //Peak power in watts
9 Vo = 3*10^8; //velocity of EM wave in m/s;
10
11 //Calculations
12 Dc = PW*PRF; //Duty Cycle
13 Pav = Pp*Dc; //average power in watts
14 Rmax = Vo/(2*PRF);
15
16
17 //Output
18
19 mprintf('Average power is %g KW\n Maximum Radar
   Range is %g Km', Pav/1000, Rmax/1000);
20
21 //=====end of the program
```

---



### Scilab code Exa 11.14 FINDING PRF

```
1 //Chapter-11 example 14
2 //


---


3 clc;
4 clear;
5 //input data
6 Rmax = 500*103; //maximum Range of Radar in ms
7 Vo = 3*108; //Velocity of EM wave in m/s
8 //Calculations
9
10 PRF = Vo/(2*Rmax); //pulse repetitive frequency in
    Hz
11
12 //output
13 mprintf('Pulse repetitive frequency required for the
    range of 500km is %g Hz',PRF);
14
15 //====end of program


---


```

### Scilab code Exa 11.15 FINDING RANGE

```
1 //Chapter-11 example 15
2 //


---


3 clc;
4 clear;
5 //input data
6 Te = 0.2*10-3; //echo time in sec
7 PRF = 1000; //pulse repetitive Frequency in Hz
```

```

8 Vo      = 3*10^8; //Velocity of EM wave in m/s
9 //Calculations
10 R       = (Vo*Te)/2; //Range of the target in m
11 Runamb  = (Vo/(2*PRF)); //Maximum unambiguous Range
    in m
12
13 //Output
14 mprintf('Target range is %g Km\n Maximum Unambiguous
    Range is %g Km',R/1000,Runamb/1000);
15
16 //=====end of program
    =====

```

---

### Scilab code Exa 11.16 FINDING FREQUENCIES

```

1 //Chapter-11 example 16
2 //
    =====
3 clc;
4 clear;
5 //input data
6 F       = 10*10^9; //operating frequency of radar in Hz
7 Vo      = 3*10^8; //Velocity of EM wave in m/s
8 Vr      = 100; //velocity of car in kmph
9 //Calculations
10 lamda  = Vo/F; //wavelength in m
11 Vc     = Vr*(5/18); //velocity of car in m/s
12 Fd     = (2*Vc)/lamda; //doppler shift in Hz
13 //Output
14 mprintf('Doppler Shift is %g KHz\n Frequency of the
    Received echo when car is approaching radar is %g
    Ghz + %g Khz\n Frequency of the Received echo
    when car is moving away from radar is %g Ghz - %g
    Khz',Fd/1000,F/10^9,Fd/1000,F/10^9,Fd/1000);

```

```
15
16 //=====end of program
    =====
    =====
```

---

### Scilab code Exa 11.17 FINDING BEAMWIDTH

```
1 //Chapter-11 example 17
2 //
    =====
    =====

3 clc;
4 clear;
5 //input data
6 D = 200;//azimuth distance between two radars
7 R = 10*103;//Range of radar
8
9 //Calculations
10 BWdB = (D/R)*(180/%pi);//3dB beam width in degrees
11
12 //Output
13 mprintf('Maximum 3db beamwidth of radar resolving
    the target is %3.3f degrees ',BWdB);
14
15 //=====end of the program
    =====
    =====
```

---

### Scilab code Exa 11.18 FINDING MIN TIME REQUIRED TO RESOLVE AIRCRAFTS

```
1 //Chapter-11 example 18
2 //
    =====
    =====
```

---

```

3  clc;
4  clear;
5  //input data
6  F      = 10*109; //operating frequency of radar in Hz
7  Vo     = 3*108; //Velocity of EM wave in m/s
8  Vr1    = 100; //velocity of one aircraft in m/s
9  theta  = 45; //angle b/n velocity vector and radar
        axis for second aircraft
10 Vr     = 200; //vel in m/s
11 //Calculations
12 lamda  = Vo/F; //wavelength in m
13 Fd1    = (2*Vr1)/lamda //doppler shift due to 1st
        aircraft
14 Vr2    = Vr*cos(45*%pi/180) //radial velocity of the
        second aircraft
15 Fd2    = (2*Vr2)/lamda //doppler shift due to 2nd
        aircraft
16 Fd     = Fd2-Fd1 //difference in doppler shift in Hz
17 T      = 1/Fd; //time required to resolve the aircraft
        in sec
18
19 //Output
20 mprintf('Minimum time required to resolve the
        aircrafts is %g usec\n',T*106);
21 mprintf(' Note: in textbook there is a mistake in
        the calculation of doppler shift Fd1');
22 //=====end of the program
        =====

```

---

**Scilab code Exa 11.19 FINDING DUTY CYCLE CORRECTION FACTOR**

```

1 //Chapter-11 example 19
2 //

```

---

```

3  clc;
4  clear;
5  //input data
6  Pp  = 100*103; //peak power in watts
7  Pav = 100; //average power in watts
8
9  //Calculations
10 PdB = 10*log10(Pp); //peak power in dB
11 PavdB = 10*log10(Pav); //average power in dB;
12 DCC  = PdB-PavdB; //Duty Cycle Correction factor
13
14 //Output
15 mprintf('Duty Cycle Correction Factor is %g dB\n',
          DCC);
16 mprintf(' Note: In question given peak power is 100
          KW but while solving 1KW is taken instead of 100
          KW')
17
18 //=====end of the program

```

---

**Scilab code Exa 11.20 FINDING AVERAGE POWER DUTY CYCLE AND PULSE ENERGY**

```

1  //Chapter-11 example 20
2  //

```

---

```

3  clc;
4  clear;
5  //input data
6  Pp  = 1*106; //peak power in watts
7  PW  = 1*10-6; //pulse width in sec
8  NPd = 20; //pulses in one dwell period

```

```

9 PRF = 1000; //pulse repetitive frequency
10
11 //calculations
12 PE = Pp*PW; //pulse energy in joule
13 PED = NPd*PE; //pulse energy in one dwell period
14 D = PW*PRF; //Duty cycle
15 Pav = Pp*D; //average power in watts
16
17 //output
18 mprintf('Average Power is %g watts\n Duty Cycle is
    %e\n Pulse Energy is %g Joules\n Pulse Energy in
    one Dwell Period is %g Joules\n',Pav,D,PE,PED);
19 mprintf(' Note: In textbook Values of PRF and pulses
    in one dwell period are varied from given values
    in question while solving ' );
20 ;
21 //=====end of the program
    =====

```

---

### Scilab code Exa 11.21 FINDING NOISE POWER SPECTRAL DENSITY

```

1 //Chapter-11 example 21
2 //
    =====

3 clc;
4 clear;
5 //input data
6 Noise_power = -50; //noise power in dBm
7 Fl = 1*10^6; //lower cutoff frequency in Hz
8 Fh = 21*10^6; //upper cutoff frequency in Hz
9
10 //calculation
11 BW = Fh-Fl; //bandwidth
12 NP =10^-8 //noise power in watts; -50dBm = 10log10(NP

```

```

    ) =>10-5 mwatts
13 NPSD = NP/BW; //noise power spectral density in W/Hz
14
15 //output
16 mprintf('Noise Power Spectral Density is %3.0e W/Hz'
    ,NPSD);
17
18 //=====end of the program
    =====

```

---

#### Scilab code Exa 11.22 FINDING RANGE OF TARGET

```

1 //Chapter-11 example 22
2 //
    =====

3 clc;
4 clear;
5 //input data
6 Ra = 1000; //Range of target A in Kms
7 //Calculations
8 Rb =Ra*cos(45*%pi/180); //range of target B in kms
9
10 //output
11 mprintf('Range of target B is %g Kms\n',Rb);
12 mprintf(' Note:value of cos(45) is incorrectly taken
    as 1/2 in textbook ');
13
14 //=====end of the program
    =====

```

---

#### Scilab code Exa 11.23 FINDING RANGE OF TARGET

```

1 //Chapter-11 example 23
2 //


---


3 clc;
4 clear;
5 //input data
6 Az = 60;//azimuth angle of the target in degrees
7 Height = 10;//height of target in kms
8 //Calculations
9 R = 10/sin(Az*%pi/180);
10
11 //output
12 mprintf('Range of the Target is %g Kms',R);
13
14 //====end of the program


---



```

#### Scilab code Exa 11.24 FINDING TARGET BLIND SPEED

```

1 //Chapter-11 example 24
2 //


---


3 clc;
4 clear;
5 //input data
6 F = 10*109;//MTI radar operating Frequency
7 Vo = 3*108;//velocity of EM wave in m/s;
8 PRF = 2*103;//pulse repetitive frequency in hz
9 n=1;//for lowest blind speed
10 //Calculations
11 lamda = Vo/F;//wavelength in m
12 BS = (n*lamda/2)*PRF;//blind speed
13

```



```

14 //output
15 mprintf('Lowest Blind Speed is %g m/s',BS);
16
17 //=====end of the program

```

---

### Scilab code Exa 11.25 RATIO OF OPERATING FREQUENCIES

```

1 //Chapter-11 example 25
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 PRF = 2*10^3;//pulse repetitive frequency in Hz
7 Vo = 3*10^8;//velocity of EM wave in m/s
8 mprintf('f1 = first operating frequency of MTI Radar
   \n');
9 mprintf(' f2 = second operating frequency of MTI
   Radar\n');
10 mprintf(' 2nd blind speed of 1st radar = (2Vo/2f1)*
   PRF\n 5th blind speed of 2nd radar = (5Vo/2f2)*
   PRF\n');
11 mprintf(' PRF(V0/f1) = (5/2)*(Vo/f2)*PRF\n');
12 mprintf(' (f2/f1) = 5/2\n');
13
14 //=====end of the program

```

---

### Scilab code Exa 11.26 RATIO OF OPERATING FREQUENCIES

```

1 //Chapter-11 example 26

```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 mprintf(' (PRF1) = 2(PRF2)\n');
7 mprintf(' Vb3 = 4Vb5\n');
8 mprintf(' (3Vo/2F1)(PRF1)) = 4(5Vo/2F2)(2PRF2)\n');
9 mprintf(' 3/2F1 = 20/F2\n');
10 mprintf(' Ratio of operating frequencies is F2/F1 =
      40/3\n');
11
12 //=====end of the program


---



```

**Scilab code Exa 11.27 FINDING COMPRESSION RATIO AND COMPRESSED PULSE WIDTH**

```

1 //Chapter-11 example 27
2 //


---


3 clc;
4 clear;
5 //input data
6 PW = 5; //FM pulse width before compression in us
7 F1 = 40; //lower cut off Frequency in Mhz
8 Fh = 60; //upper cut off Frequency in Mhz
9
10 // Calculations
11 BW = Fh-F1; //bandwidth of signal in Mhz
12 CPW = 1/BW; //Compression pulse width in us
13 CR = PW/CPW; //compression ratio
14

```

```

15 //output
16 mprintf('Compression ratio is %g\n Compression Pulse
          Width is %g us\n',CR,CPW);
17 //=====end of the program

```

---

**Scilab code Exa 11.28** FINDING COMPRESSION PULSEWIDTH AND RATIO

```

1 //Chapter-11 example 28
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 BW = 100//band width in Mhz
7 PW = 4;//pulse width in us
8 //Calculations
9 CPW = 1/BW;//compressed pulse width in us
10 CR = PW/CPW;//compression ratio
11
12 //output
13 mprintf('compressed pulse width is %g us\n
          compression ratio is %g\n',CPW,CR);
14 mprintf(' Note: In textbook compression ratio is
          wrongly printed as 40');
15
16 //=====end of the program

```

---

**Scilab code Exa 11.29** FINDING COMPRESSED PULSE WIDTH AND BANDWIDTH

```

1 //Chapter-11 example 29
2 //


---


3 clc;
4 clear;
5 //input data
6 CR = 50;//compression ratio
7 PW = 2;//pulse width in us
8 //Calculations
9 CPW = PW/CR //compression pulse width in us
10 BW = 1/CPW //compression band width in Mhz
11
12 //output
13 mprintf('compressed pulse width is %g us\n
         compression Bandwidth is %g MHz\n',CPW,BW);
14
15
16 //=====end of the program


---



```

### Scilab code Exa 11.30 FINDING RANGE RESOLUTION

```

1 //Chapter-11 example 30
2 //


---


3 clc;
4 clear;
5 //input data
6 PW = 1*10^-6;//transmitted pulse width in sec
7 Vo = 3*10^8;//velocity of EM wave in m/s
8
9 //Calculations
10 RR = (Vo*PW)/2;

```

```

11 //output
12 mprintf('Range Resolution is %g m\n',RR);
13 mprintf(' As the targets are separated by 100m it is
    possible to resolve');
14 //=====end of program
    =====

```

---

### Scilab code Exa 11.31 FINDING CLOSEST FREQUENCIES

```

1 //Chapter-11 example 31
2 //
    =====

3 clc;
4 clear;
5 //input data
6 F = 10*10^9;//operating frequency in Hz
7 PRF = 1000;//pulse repetitive frequency in Hz
8 Fm = PRF;//modulating frequency
9 //Calculations
10 Fc1 = F+Fm;//closest frequency in Hz
11 Fc2 = F-Fm; //closest frequency in Hz
12 //output
13 mprintf('Closest Frequencies are %3.3f Mhz and %3.3f
    Mhz',Fc1/10^6,Fc2/10^6 );
14
15 //=====end of the program
    =====

```

---

### Scilab code Exa 11.32 FINDING SPECTRUM CENTRE BANDWIDTH AND COMPRESSED PULSE WIDTH

```

1 //Chapter-11 example 32

```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 F1 = 490; //freq shift lower limit in Mhz
7 F2 = 510; //freq shift upper limit in Mhz
8
9 //calculations
10
11 SC = (F1+F2)/2; //Spectrum Centre in Mhz
12 BW = F2-F1; //bandwidth in Mhz
13 CPW = 1/BW; //compressed bandwidth in us
14
15 //Output
16 mprintf('Spectrum centre is %g MHz\n BandWidth is %g
    MHz\n Compressed pulse Width is %g us',SC,BW,CPW
    );
17
18 //====end of the program


---



```

### Scilab code Exa 11.33 FINDING MINIMUM RECEIVABLE SIGNAL

```

1 //Chapter-11 example 33
2 //


---


3 clc;
4 clear;
5 //input data
6 F = 9; //Noise figure in dB
7 BW = 2*10^6; // Bandwidth
8 To = 300; // Temperature in kelvin

```

```

9 K          = 1.38*10^-23;    // Boltzman constant
10
11 // Calculations
12
13 F1         = 10^(F/10)      // antilog calculation
14 Pmin       = (K*To*BW)*(F1-1); // minimum receivable
    power
15
16 // Output
17 mprintf('Minimum receivable power Pmin = %e W',Pmin)
    ;
18
19 //

```

---

#### Scilab code Exa 11.34 FINDING MAXIMUM RANGE OF RADAR

```

1 //Chapter-11 example 34
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 Pt = 500*10^3; //peal pulse power in watts
7 Pmin = 1*10^-12; //minimum receivable power
8 Ac = 5; //area of capture in m^s
9 RCS = 16; //radar cross sectional area in m^2
10 F = 10*10^9; //radar operating frequency
11 Vo = 3*10^8; //vel of Em wave in m/s;
12
13 //calculations
14 lamda = Vo/F; //wavelength
15

```

```

16 Rmax = ((Pt*Ac*Ac*RCS)/(4*%pi*lamda*lamda*Pmin))
    ^0.25;
17
18 //output
19 mprintf('Maximum Radar range of the Radar system is
    %g Kms\n',Rmax/1000);
20 mprintf(' Note:Calculation mistake in textbook
    instead of RCS,RCS^2 is calculated');
21 //=====end of the program
    =====

```

---

### Scilab code Exa 11.35 FINDING PEAK TX POWER

```

1 //Chapter-11 example 35
2 //
    =====

3 clc;
4 clear;
5 //input data
6 lamda      = 0.03;           //wavelength in m
7 RCS        = 5;             // Radar cross
    section in m^2
8 D          = 1;             // antenna diameter
    in m
9 F          = 5;             // noise figure in
    dB
10 Rmax       = 10*10^3        // Radar range
11 BW         = 500*10^3;      // bandwidth
12
13 //Calculation
14 F1         = 10^(F/10)      // antilog
    calculation
15
16 //Rmax     = 48*((Pt*D^4*RCS)/(BW*lamda*lamda(F

```



```

-1)))^0.25
17
18 Pt = ((Rmax/48)^4)*((BW*lamda*lamda*(F1
-1))/(D^4*RCS))
19
20 //Output
21 mprintf('Peak Transmitted Power is %e',Pt);
22 mprintf('\n Note: Antilog Calculation error in
textbook at F')
23 //

```

---

### Scilab code Exa 11.36 FINDING MAX RANGE OF RADAR

```

1 //Chapter-11 example 36
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 Pt = 20*10^6; //peak pulse power in watts
7 RCS = 1; //radar cross sectional area in m^2
8 f = 3*(10^9); //radar operating frequency
9 Vo = 3*(10^8); //vel of Em wave in m/s;
10 D = 50; //diameter of antenna in m
11 F = 2; //receiver noise figure
12 BW = 5000; //receiver bandwidth
13
14 //calculations
15
16 lamda = Vo/f //wavelength in m
17 Rmax = 48*((Pt*(D^4)*RCS)/(BW*lamda*lamda*(F-1)))
^0.25;

```

```

18
19 //output
20 mprintf('Maximum Radar range of the Radar system is
    %g Kms\n ',Rmax/1000);
21 mprintf('Note:In textbook All values are correctly
    substituted in calculating Rmax.\n but incorrect
    final answer is printed in the book');
22
23 //=====end of the program
    =====

```

---

### Scilab code Exa 11.37 FINDING LOWEST BLIND SPEEDS

```

1 //Chapter-11 example 37
2 //
    =====

3 clc;
4 clear;
5 //Given data
6 lamda      = 6*10^-2;      //Wavelength in m
7 PRF        = 800;        //Pulse Repetitive frequency
    in Hz
8 n1         = 1 ;        //n value for first blind
    speed
9 n2         = 2 ;        //n value for first blind
    speed
10 n3        = 3 ;        //n value for first blind
    speed
11
12 //Calculations
13
14 //Vb      = (n*lamda/2)*PRF;    Blind speed of the
    Radar
15

```

```

16 //For n = 1
17
18 Vb1      = (n1*lamda/2)*PRF;    //Blind speed of the
    Radar in m/s
19 Vb2      = (n2*lamda/2)*PRF;    //Blind speed of the
    Radar in m/s
20 Vb3      = (n3*lamda/2)*PRF;    //Blind speed of the
    Radar in m/s
21
22 //multiply by 18/5 to convert from m/s to kmph
23
24 //Output
25 mprintf('The lowest Blind speeds are %3.1f, %3.2f
    and %3.2f Km/hr ',Vb1*(18/5),Vb2*(18/5),Vb3*(18/5)
    );
26
27 //=====end of program

```

---

### Scilab code Exa 11.38 FINDING RANGE OF BEACON

```

1 //Chapter-11 example 37
2 //

```

---

```

3 clc;
4 clear;
5 //Given data
6
7 Pt      = 500*103;    // Peak pulse power in Watts
8 pt      = 50;        // peak power transmitted by
    beacon in watts
9 f       = 2500*106;    // Radar Operating frequency
    in Hz

```

```

10 lamda      = 0.12;           // wavelength in m
11 D          = 64;           // antenna diameter in m
12 BW         = 5000;         // Radar Bandwidth
13 Ab         = 0.51;
14 k          = 1.38*10^-23;  // Boltzmann constant
15 F          = 20            // Noise figure
16 Fb         = 1.1          // Noise figure of beacon
17 To         = 290;         // Temperature in kelvin
18
19 // Calculations
20
21 Ar          = (0.65*pi*D*D)/4
22 Rmax        = sqrt((Ar*Pt*Ab)/(lamda*lamda*k*To*BW*(F
    -1))); // Max tracking range of radar
23
24 Rmax1       = sqrt((Ar*pt*Ab)/(lamda*lamda*k*To*BW*(
    Fb-1))); // Max tracking range of radar if Fb =
    1.1
25
26 //output
27 mprintf('Maximum Tracking Range of Radar is %3.3e Km
    \n Range of beacon if noise figure is 1.1 = %3.3e
    Km\n ',Rmax/1000,Rmax1/1000);
28 mprintf('Note: Calculation mistake in textbook in
    calculating Range of beacon\n instead of
    1.36*10^9 km range is wrongly printed as 136*10^6
    km')
29
30 //=====end of program
    =====

```

---

### Scilab code Exa 11.39 FINDING DOPPLER SHIFT

```

1 //Chapter-11 example 39
2 //

```

---

```

3  clc;
4  clear;
5  //Given data
6  lamda      = 0.06;           // wavelength in m
7  Vr        = 100 ;           // Radial velocity of target
                                in kmph
8
9  //Calculations
10 Vr1       = Vr*(5/18);      //Radial vel. in m/s
11 fd        = (2*Vr1)/lamda; //doppler shift
12
13 //output
14
15 mprintf('Doppler Shift is %3.3f Khz',fd/1000);
16
17 //

```

---

#### Scilab code Exa 11.40 FINDING RX SIGNAL POWER

```

1 //Chapter-11 example 40
2 //

```

---

```

3  clc;
4  clear;
5  //Given data
6  F  = 9.5*10^9;           //radar operating frequency in
                                Hz
7  Vo = 3*10^8;            //vel in m/s;
8  G  = 20;                //antenna gain in dBi;
9  R  = 50*10^3;           //distance of radar reflected

```

```

    signal from target
10 Pt = 10*10^3           //Tx power in watts
11 CS = 10;              //cross sectional area in m^2
12
13 // Calculations
14 Gain = 10^(G/10)      //G = 10log(Gain) ==>gain -
    antilog(20/10);
15 Gr = Gain;           //gain of tx antenna and Rx
    antenna
16 Gt = Gain
17 lamda = Vo/F
18 Pr= (lamda*lamda*Pt*Gt*Gr*CS)/((4*4*4*%pi*%pi*%pi)*(
    R^4))//received power in watts
19
20 // Output
21 mprintf('Received signal Power is %g Watts',Pr);
22 //

```

---

#### Scilab code Exa 11.41 FINDING DISTANCE OF TARGET

```

1 //Chapter-11 example 41
2 //
3 clc;
4 clear;
5 //Given data
6
7 Vo = 3*10^8;           // vel of EM wave m/s;
8 t = 10*10^-6;        // time taken to rx echo
9
10 //Calculations
11

```

```

12 R      = (Vo*t)/2;      // Distance of the Target
13
14 //output
15
16 mprintf('Distance of the target is %3.2f Km',R/1000)
17      ;
18 //

```

---

#### Scilab code Exa 11.42 FINDING MIN AND MAX TARGET RANGE

```

1 //Chapter-11 example 42
2 //

```

---

```

3 clc;
4 clear;
5 //Given data
6
7 PW      = 10^-6;      // Pulse Width in sec
8 PRF     = 1000;      // Pulse Repetitive Freq in
9          Hz
10 Vo      = 3*10^8;    // vel of EM wave m/s;
11
12 //Calculations
13 Rmax    = Vo/(2*PRF); // max range of radar
14 Rmin    = (Vo*PW)/2 ; // min range of radar
15
16 //output
17 mprintf('Maximum Range of radar is %e m\n Minimum
18         Range of radar is %d m',Rmax,Rmin );

```

19 //

---

---

### Scilab code Exa 11.43 FINDING DOPPLER SHIFT FREQUENCY

```
1 //Chapter-11 example 43
2 //
3 clc;
4 clear;
5 //Given data
6 Vr      = 100;           // speed of car in kmph
7 f       = 10*10^9;      // Radar operating frequency
8 Vo      = 3*10^8;       // vel. of EM wave
9
10 //Calculations
11
12 Vr1     = Vr*(5/18);    // kmph to m/s conversion
13 fd      = (2*Vr1*f)/Vo; // Doppler shift in Hz
14
15 //Output
16 mprintf('Doppler shift = %3.2 f Khz',fd/1000);
17
18 //
```

---

---

### Scilab code Exa 11.44 FINDING DISTANCE OF TARGET

```
1 //Chapter-11 example 44
```



```

2 //


---


3 clc;
4 clear;
5 //Given data
6
7 Vo      = 3*10^8;           // vel of EM wave m/s;
8 t       = 200*10^-6;       // time taken to rx echo
9
10 //Calculations
11
12 R       = (Vo*t)/2;        // Distance of the Target
13
14 //output
15
16 mprintf('Distance of the target is %3.2 f Km',R/1000)
17     ;
18 //


---



```

#### Scilab code Exa 11.45 FINDING DUTY CYCLE AND AVERAGE POWER

```

1 //Chapter-11 example 45
2 //


---


3 clc;
4 clear;
5 //Given data
6 Pt      = 100*10^3;         // Peak tx. power
7 PRF     = 1000;            // pulse repetitive freq
8     . in Hz

```

```

8 PW      = 1.2*10^-6;          // Pulse Width in sec
9
10 // Calculations
11 DC      = PRF*PW             // Duty cycle
12 Pav     = Pt*DC              // Avg. power
13
14 // Output
15 mprintf('Duty cycle is %3.4f\n Average power is %3.0
        f Watts',DC,Pav);
16
17 //

```

---

#### Scilab code Exa 11.46 FINDING PRF

```

1 //Chapter-11 example 46
2 //

```

---

```

3 clc;
4 clear;
5 //Given data
6 Runamb   = 300*10^3;          // unambiguous range in
        m
7 Vo      = 3*10^8;            // Vel. of EM wave in m/
        s
8
9 // Calculations
10
11 PRF     = Vo/(2*Runamb);     // Pulse repetitive
        freq.
12
13 // Output
14 mprintf('Pulse repetitive frequency = %g Hz',PRF);

```

15 //

---

---

**Scilab code Exa 11.47 FINDING DUTY CYCLE AND MAX UNAM-  
BIGUOUS RANGE**

```
1 //Chapter-11 example 47
2 //
3 clc;
4 clear;
5 //Given data
6
7 Vo      = 3*10^8;           // vel of EM wave m/s;
8 PRF     = 1000;           // pulse repetitive freq. in
   Hz
9 PW      = 10^-6;          // Pulse width in sec
10
11 //Calculations
12
13 DC      = PRF*PW           // Duty cycle
14
15 Runamb  = Vo/(2*PRF);     // Distance of the Target
16
17 //output
18
19 mprintf('Duty cycle = %g\n Maximum unambiguous range
   = %g Km',DC,Runamb/1000 );
20
21 //
```

---

---

**Scilab code Exa 11.48 FINDING MAX UNAMBIGUOUS RANGE AND RANGE RESOLUTION**

```
1 //Chapter-11 example 48
2 //


---


3 clc;
4 clear;
5 //Given data
6
7 Vo      = 3*10^8;           // vel of EM wave m/s;
8 PRF     = 1000;           // pulse repetitive freq. in
   Hz
9 PW      = 4*10^-6;        // Pulse width in sec
10
11 //Calculations
12
13 Runamb  = Vo/(2*PRF);      // Distance of the Target
14 RR      = (Vo*PW)/2;      // Range Resolution
15 //output
16
17 mprintf('Maximum unambiguous range = %g Km\n Range
   Resolution = %g m', Runamb/1000, RR );
18
19 //
```

---

**Scilab code Exa 11.49 CALCULATING RADAR PARAMETERS**

```
1 //Chapter-11 example 49
```

```

2 //


---


3 clc;
4 clear;
5 //Given data
6 f      = 6*10^9;           // Radar operating freq. in
   Hz
7 Vo     = 3*10^8;         // vel of EM wave m/s;
8 PRF    = 1000;          // pulse repetitive freq. in
   Hz
9 PW     = 1.2*10^-6;     // Pulse width in sec
10 DC    = 10^-3;         // Duty Cycle
11 Smin  = 5*10^-12;     // min. detectable signal
12 R     = 60*10^3;      // Max. Range in m
13 G     = 4000;         // power gain of antenna
14 Ae    = 1             // effective area in m^2
15 RCS   = 2             // Radar cross sec. in m^2
16 //Calculations
17
18 lamda  = Vo/f;         // Wavelength in m
19 PRT    = PW/DC;       // pulse repetitive time
20 PRF    = 1/PRT;      // Pulse repetitive freq.
21 Pt     = ((Smin*(4*pi*R*R)^2)/(Ae*G*RCS)); //Peak
   power
22 Pav   = Pt*DC;       // average power
23
24 Runamb = Vo/(2*PRF);  // Distance of the Target
25 RR     = (Vo*PW)/2;  // Range Resolution
26 //output
27
28 mprintf('Operating Wavelength = %g m\n PRT = %3.2 f
   ms\n PRF = %3.1 f Hz\n Peak power = %3.3 f KW\n
   Average power = %3.3 f Watts\n unambiguous range =
   %g Km\n Range Resolution = %g m', lamda, PRT*1000,
   PRF, Pt/1000, Pav, Runamb/1000, RR );
29 mprintf(' \n Note: Calculation error in textbook for
   Pt and Pav ');

```

```
30
31 //
```

---

### Scilab code Exa 11.50 FINDING AVERAGE POWER

```
1 //Chapter-11 example 50
2 //
3 clc;
4 clear;
5 //Given data
6
7 Vo      = 3*10^8;           // vel of EM wave m/s;
8 PRT     = 1.4*10^-3;       // pulse repetitive time. in
    sec
9 PW      = 5 *10^-6;        // Pulse width in sec
10 Pt     = 1000*10^3;       //Peak power in watts
11
12 //Calculations
13
14 DC      = PW/PRT           // Duty cycle
15 Pav     = Pt*DC           // avg. power in W
16
17 //output
18
19 mprintf('Duty cycle = %e\n Average power = %g W',DC,
    Pav );
20
21 //
```

---

### Scilab code Exa 11.51 FINDING MIN RECEIVABLE SIGNAL

```
1 //Chapter-11 example 51
2 //


---


3 clc;
4 clear;
5 //Given data
6 F      = 5;           // Noise Figure in dB
7 BW     = 1.2*10^6;   // Bandwidth in Hz
8 T      = 290;        // Ambient temp in kelvin
9 K      = 1.38*10^-23; // boltzmann constant
10
11 //Calculations
12 F1     = 10^(5/10) ; // antilog calc of noise
    figure
13 Prmin  = K*(F1-1)*T*BW; // min. rx. signal
14
15 //Output
16 mprintf('Minimum Receivable signal = %3.4e W\n ',
    Prmin);
17 mprintf('Note:In textbook All values are correctly
    substituted in calculating Prmin.\n but incorrect
    final answer is printed in the book')
18
19 //
```

---

### Scilab code Exa 11.52 FINDING MAX RANGE OF RADAR

```

1 //Chapter-11 example 52
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 Pt    = 1*10^6;           //peak pulse power in watts
7 Pmin  = 1*10^-12;        //minimum receivable power
8 Ae    = 16;              //effective area in m^s
9 RCS   = 4;               //radar cross sectional area
    in m^2
10 F     = 9*10^9;         //radar operating frequency
11 Vo    = 3*10^8;         //vel of Em wave in m/s;
12 G     = 5000;           //Power gain of antenna
13
14 //calculations
15
16 Rmax  = ((Pt*G*Ae*RCS)/(16*%pi*%pi*Pmin))^0.25;
17
18 //output
19 mprintf('Maximum Radar range of the Radar is %g Kms
    ',Rmax/1000);
20
21 //=====end of the program

```

---

### Scilab code Exa 11.53 FINDING MAX RANGE OF RADAR

```

1 //Chapter-11 example 53
2 //

```

---

```

3 clc;
4 clear;

```



```

5 //input data
6 Pt = 500*10^3; //peal pulse power in watts
7 Pmin = 1*10^-12; //minimum receivable power
8 Ac = 5; //area of capture in m^s
9 RCS = 20; //radar cross sectional area in m^2
10 F = 10*10^9; //radar operating frequency
11 Vo = 3*10^8; //vel of Em wave in m/s;
12 lamda = 3*10^-2; //wavelength in cms
13
14 //calculations
15
16 Rmax = ((Pt*Ac*Ac*RCS)/(4*%pi*lamda*lamda*Pmin))
        ^0.25;
17
18 //output
19 mprintf('Maximum Radar range of the Radar system is
        %g Kms', Rmax/1000);
20
21 //=====end of the program

```

---

### Scilab code Exa 11.54 FINDING BEAMWIDTH OF ANTENNA

```

1 //Chapter-11 example 54
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 f = 10*10^9; // operating freq. of radar
   in Hz
7 Vo = 3*10^8; //vel of Em wave in m/s;
8 D = 5; //Diameter of antenna in m
9

```

```

10 //calculations
11 lamda    = Vo/f;           // wavelength in m
12 BW       = 70*(lamda/D)   // BeamWidth in degrees
13
14 //output
15 mprintf('Beamwidth = %3.3f degrees ',BW);
16 //

```

---

**Scilab code Exa 11.55 FINDING OPERATING FREQ PEAK POWER AND RANGE OF RADAR**

```

1 //Chapter-11 example 55
2 //

```

---

```

3 clc;
4 clear;
5 //input data
6 Pav = 200; //average power in watts
7 PRF = 1000; //pulse repetitive frequency in Hz
8 PW = 1*10^-6; //pulse width in sec
9 Pmin = 1*10^-12; //minimum receivable power
10 Ac = 10; //area of capture in m^s
11 RCS = 2; //radar cross sectional area in m^2
12 Vo = 3*10^8; //vel of Em wave in m/s;
13 lamda = 0.1; //wavelength in cms
14
15 //calculations
16 F = Vo/lamda; //operating frequency in hz
17 Pt = Pav/(PRF*PW);
18
19 Rmax = ((Pt*Ac*Ac*RCS)/(4*%pi*lamda*lamda*Pmin))
    ^0.25;

```

```

20
21 //output
22 mprintf('Operating frequency is %g Ghz\n Radar peak
        power is %g KW\n Maximum Radar range of the Radar
        system is %g Km\n',F/10^9,Pt/1000,Rmax/1000);
23
24 //=====end of the program
        =====

```

---

### Scilab code Exa 11.56 FINDING RADIAL VELOCITY OF TARGET

```

1 //Chapter-11 example 56
2 //
        =====

3 clc;
4 clear;
5 //input data
6 f      = 9*10^9;           // operating freq. of radar
        in Hz
7 Vo     = 3*10^8;          //vel of Em wave in m/s;
8 fd     = 1000;            // doppler shift freq. in Hz
9
10 //Calculations
11 lamda  = Vo/f;           // Wavelength in m
12 Vr     = lamda*fd/2;     // radial velocity of target
13
14 //output
15 mprintf('Radial velocity of target Vr = %3.2f m/s',
        Vr);
16
17 //
        =====

```

---

### Scilab code Exa 11.57 FINDING DOPPLER SHIFT FREQUENCY

```
1 //Chapter-11 example 57
2 //


---


3 clc;
4 clear;
5 //input data
6 f      = 10*109;           // operating freq. of radar
   in Hz
7 Vr     = 800;              // radial ve. of of
   aircraft in kmph
8 Vo     = 3*108;          //vel of Em wave in m/s;
9
10 //calculations
11
12 lamda  = Vo/f;            // Wavelength in m
13 Vr1    = Vr*5/18         // kmph to m/s conversion
14 fd     = 2*Vr1/lamda;    // Doppler shift freq, in Hz
15
16 //Output
17 mprintf('Doppler shift frequency fd = %3.2e Hz',fd);
18
19 //
```

---

### Scilab code Exa 11.58 FINDING DOPPLER SHIFT FREQUENCIES

```
1 //Chapter-11 example 58
```

```

2 //


---


3 clc;
4 clear;
5 //input data
6 f      = 6*10^9;           // operating freq. of radar
   in Hz
7 Vr     = 600;             // radial ve. of of
   aircraft in kmph
8 Vo     = 3*10^8;         //vel of Em wave in m/s;
9
10 //calculations
11
12 lamda  = Vo/f;           // Wavelength in m
13 Vr1    = Vr*5/18        // kmph to m/s conversion
14 fd     = 2*Vr1/lamda;   // Doppler shift freq, in Hz
15
16 V      = Vr1*cos((45*%pi/180)) // vel in direction
   of radar if target direction changes by 45 deg
17 fd1    = 2*V/lamda ;    //doppler shift freq. in Hz
18
19
20 //Output
21 mprintf('Doppler shift frequency fd = %3.2f KHz\n
   Doppler shift frequency if the target changes its
   direction by 45deg = %3.2f KHz',fd/1000,fd1
   /1000);
22
23 //


---



```

Scilab code Exa 11.59 FINDING BLIND SPEED

```

1 //Chapter-11 example 59
2 //


---


3 clc;
4 clear;
5 //Given data
6 lamda      = 3*10^-2;      //Wavelength in m
7 PRF        = 1000;        //Pulse Repetitive frequency
   in Hz
8 n          = 1'          // n value for lowest blind
   speed
9
10 //Calculations
11 Vb         = (n*lamda/2)*PRF; //Blind speed of the
   Radar in m/s
12
13 //Output
14 mprintf('Lowet blind speed = %d m/s ',Vb);
15 //


---



```

### Scilab code Exa 11.61 FINDING PULSE WIDTH AND PULSE ENERGY

```

1 //Chapter-11 example 60
2 //


---


3 clc;
4 clear;
5 //Given data
6 PRF1       = 10*10^3;      //pulse repetitive
   freq.1
7 PRF2       = 20*10^3;      //pulse repetitive

```

```

    freq.2
8  Pav          = 1000;           // average tx. power
9  Pt           = 10*10^3;       // peak power
10
11 // Calculations
12 PRT1         = 1/PRF1;        // pulse repetitive
    interval in sec
13 PRT2         = 1/PRF2;        // pulse repetitive
    interval in sec
14 DC           = Pav/Pt;        // duty cycle
15 PW1          = DC*PRT1        // pulse width for
    freq1
16 PW2          = DC*PRT2        // pulse width for
    freq2
17 E1           = Pt*PW1;        // energy of first
    pulse
18 E2           = Pt*PW2;        // energy of second
    pulse
19
20 //output
21 mprintf('PW1 = %3.2 f ms\n PW2 = %3.3 f ms\n Pulse
    Energy for PRF = 10KHz is %3.1 f Joules\n Pulse
    Energy for PRF = 20KHz is %3.2 f Joules\n',PW1
    *1000 ,PW2*1000 ,E1 ,E2 );
22 //

```

---

**Scilab code Exa 11.62** FINDING PRT PRF RANGE RESOLUTION AND PULSE WIDTH

```

1 //Chapter-11 example 62
2 //

```

---

```

3  clc;
4  clear;
5  //Given data
6  Runamb      = 150*103;      // unambiguous range in
    m
7  BW          = 106;        // bandwidth in Hz
8  Vo          = 3*108;      //vel of Em wave in m
    /s;
9
10 //Calculations
11 PRF         = Vo/(2*Runamb) ; //pulse repetitive
    freq. in Hz
12 PRT        = 1/PRF;        // pulse repetition
    interval
13 RR         = Vo/(2*BW);    // Range Resolution
14 PW         = (2*RR)/Vo;    //Pulse width in sec
15
16 //Output
17 mprintf('PRF = %3.2f Hz\n pulse repetition interval
    = %3.1f ms\n Range Resolution = %d m\n PulseWidth
    = %3.2f us',PRF,PRT*1000,RR,PW*106 );
18
19 //

```

---

### Scilab code Exa 11.63 FINDING DOPPLER FREQUENCY

```

1 //Chapter-11 example 63
2 //

```

---

```

3 clc;
4 clear;
5 //Given data

```



```

6 Vr      = 300;           // Velocity of radar in m/s
7 Vair    = 200;           // velocity of aircraft in m/
  s
8 f       = 10*10^9;       // Radar operating frequency
9 Vo      = 3*10^8;        //vel of Em wave in m/s;
10
11 //Calculations
12
13 lamda   = Vo/f;          // wavelength in m
14 Vrel    = Vr+Vair;        //relative radial vel. b/w
  radar and aircraft when approaching each other
15 fd      = (2*Vrel)/lamda // Doppler frequency
16
17 //Output
18 mprintf('Doppler frequency = %3.2 f KHz',fd/1000);
19 //

```

---

### Scilab code Exa 11.64 FINDING MAX RANGE OF RADAR

```

1 //Chapter-11 example 63
2 //

```

---

```

3 clc;
4 clear;
5 //Given data
6 Pt      = 2*10^6;         //Peak power in Watts
7 G       = 45;            // antenna gain in dB
8 f       = 6*10^9;        // operating frequency
9 Te      = 290;           // effective temp in kelvin
10 SNRmin  = 20;           // min SNR in dB
11 PW      = 0.2*10^-3     // pulse width in sec
12 F       = 3;            // Noise Figure

```

```

13 B      = 10*10^3;      // bandwidth in KHz
14 RCS    = 0.1;        // Radar cross section in m
    ^2
15 K      = 1.38*10^-23; // boltzman constant
16 Vo     = 3*10^8;     // vel of Em wave in m/s;
17
18 //antilog acalculations
19 G1     = 10^(45/10);  // antilog conversion of
    gain
20 SNR    = 10^(20/10); // antilog conversion of
    SNRmin
21 F1     = 10^(3/10);  // antilog conversion of
    Noise Figure
22
23 lamda  = Vo/f;       //wavelength in m
24 Rmax   = ((Pt*G1*G1*lamda*lamda*RCS)/((64*%pi*%pi*
    %pi)*(K*Te*B*F1*SNR)))^0.25;
25 //pt1   = 10*log10(Pt)
26 //lamda1 = 10*log10(lamda^2)
27 //G2    = 2*G
28 //KTB   = 10*log10(K*Te*B)
29 //RCS1  = 10*log10(RCS)
30 //p     = 10*log10((4*%pi)^3)
31 //R4max = [pt1+G1+lamda1+RCS1-p-KTB-F-SNRmin];
32
33 //Output
34 mprintf('Maximum Range of the Radar is %3.2 f Km',
    Rmax/100);
35 mprintf('\n Note: Calculation error i Textbook in
    multiplying K*Te*B');

```

---

**Scilab code Exa 11.65** FINDING APERTURE SIZE AND PEAK POWER OF TXR

1 //Chapter-11 example 63

```

2 //

3 clc;
4 clear;
5 //Given data
6 G      = 50;           // antenna gain in dB
7 f      = 6*10^9;      // operating frequency
8 Te     = 1000;        // Noise temp in kelvin
9 SNR    = 20;          // min SNR in dB
10 L     = 10;           // Losses in dB
11 F     = 3;            // Noise Figure in dB
12 RCS   = -10;         // Radar cross section in dB
13 K     = 1.38*10^-23; // boltzman constant
14 Vo    = 3*10^8;      // vel of Em wave in m/s;
15 DC    = 0.3;         // Duty cycle
16 R     = 300*10^3;    // Range in kms
17 Pav   = 1000;        // Average power in watts
18 SV    = 20;          //search volume
19 Ts    = 3;           //Scan time
20
21 //calculations
22
23 Pav1   = 10*log10(Pav)           //conversion to dB
24 KT     = 10*log10(Te*K)         //conversion
    to dB
25 R4     = 10*log10(R^4)           //conversion to dB
26 Ts1   = 10*log10(Ts)           //conversion to
    dB
27 //SNR   = (Pav*A*RCS*Ts)/(16*R^4*K*Te*L*F*SV)
28 A      = (SNR-Pav1-Ts-RCS+16+R4+KT+L+F+SV); //
    aperture
29 Pt     = Pav/DC;                 // peak ower in
    watts
30 //A1    =10^(A/10);             // antilog
    calculation
31
32 //output

```

```
33 mprintf('A = %3.2f dB\n Peak power Pt = %3.2f KW\n',  
    A,Pt/1000);  
34 //mprintf('A = %3.2f m^2\n',A1)  
35 mprintf(' Note: calculation error in textbook at KT'  
    )  
36 //
```

---

---