

Scilab Textbook Companion for
Fundamentals of Electronic Devices
by P. Raja and P. Sharma¹

Created by
Preeti Rani
B.Tech
Mechanical Engineering
Uttrakhand Technical University
College Teacher
None
Cross-Checked by
Chaya Ravindra

June 2, 2016

¹Funded by a grant from the National Mission on Education through ICT,
<http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab
codes written in it can be downloaded from the "Textbook Companion Project"
section at the website <http://scilab.in>

Book Description

Title: Fundamentals of Electronic Devices

Author: P. Raja and P. Sharma

Publisher: Umesh Publications, New Delhi

Edition: 2

Year: 2010

ISBN: 978-93-80176-08-6

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes	4
1 Semiconductor Materials and Crystal Properties	5
2 Energy Bands And Charge Carriers in Semiconductor	16
3 Excess Carriers In Semiconductor	34
4 Junction Properties	49
5 Bipolar Junction Transistors	64
6 Field Effect Transistor	78
7 Optoelectronic Devices	81
8 Negative Conductance Micro Devices	84

List of Scilab Codes

Exa 1.18.3 Volume density of Si	5
Exa 1.18.4 Density of copper crystal	6
Exa 1.21.1 Wavelength of X ray	6
Exa 1.21.2 Spacing of atomic layer	7
Exa 1.21.3 Interplaner spacing	7
Exa 1.21.4 Interplaner spacing	8
Exa 1.21.5 Glacing angle	8
Exa 1.21.6 Wavelength of X ray	9
Exa 1.21.7 Glacing angle	10
Exa 1.21.8 Glacing angle	10
Exa 1.21.9 Lattice constant	11
Exa 1.22.1 Distance between d211 planes	12
Exa 1.22.2 Density	12
Exa 1.22.3 Number of atom per unit cell	13
Exa 1.22.4 Radius of element atom	13
Exa 1.22.5 Packing factor	14
Exa 1.22.6 Number of unit cell	14
Exa 1.22.7 Distance between K and F	15
Exa 2.6.1 Energy Gap	16
Exa 2.6.2 Wavelength	17
Exa 2.15.1 Position of fermi level	17
Exa 2.15.2 Thermal equilibrium electron concentration	18
Exa 2.15.3 Thermal equilibrium hole concentration	18
Exa 2.16.1 Mobility of electrons in copper	19
Exa 2.16.2 Charge density of free electrons	19
Exa 2.16.3 Drift velocity	20
Exa 2.16.4 Mobily of charge carriers	21
Exa 2.16.5 Resistivity of Copper	21

Exa 2.17.1 Conductivity of pure Si	22
Exa 2.17.2 Number of donor atoms	22
Exa 2.17.3 Conductivity of specimen	23
Exa 2.17.4 Mobility of electrons in Ge	23
Exa 2.17.5 Density and mobility of holes	24
Exa 2.17.6 Current produced	24
Exa 2.17.7 Resistivity of dopped Ge	25
Exa 2.17.8 Current produced in Ge sample	26
Exa 2.17.9 Conductivity of pure Si	26
Exa 2.19.1 Hall voltage produced	27
Exa 2.19.2 Hall coefficient and mobility of electrons	27
Exa 2.20.1 Ratio of electron to hole concentration	28
Exa 2.20.2 Hall angle	28
Exa 2.20.3 Mobility and density of charge carriers	29
Exa 2.24.1 Current density in specimen	29
Exa 2.24.2 Relaxation time and resistivity of conductor	30
Exa 2.24.3 Temperature	31
Exa 2.24.4 Thermal equilibrium hole concentration	31
Exa 2.24.5 Minimum donor concentration	32
Exa 2.24.6 Quasi fermi energy levels	32
Exa 3.21.1 Hole concentration at equilibrium	34
Exa 3.21.3 Fermi level	34
Exa 3.21.4 Diffusion coefficients of electrons and holes	35
Exa 3.21.5 Diffusion length	36
Exa 3.21.6 Concentration of holes and electrons	36
Exa 3.21.7 Electron transit time	37
Exa 3.21.8 Resistivity of intrinsic Ge	38
Exa 3.21.9 Concentration of holes and electrons	38
Exa 3.21.10Ratio of donor atoms to Si atom	39
Exa 3.21.11Equilibrium electron and hole densities	39
Exa 3.21.12Carrier concentration	40
Exa 3.21.13Generation rate due to irradiation	40
Exa 3.21.14Mobility of minority charge carriers	41
Exa 3.21.15Hole and electron diffusion current	41
Exa 3.21.16Energy band gap of semiconductor material used	42
Exa 3.21.17Current density in Si	43
Exa 3.21.18Resistance of the bar	43
Exa 3.21.19Depletion width	44

Exa 3.21.20 Minority carrier density	44
Exa 3.21.21 Collector current density	45
Exa 3.21.22 Band gap	45
Exa 3.21.23 Total energy absorbed by sample	46
Exa 3.21.24 Hole current	47
Exa 4.16.1 Contact difference of potential	49
Exa 4.16.2 Height of potential energy barrier	50
Exa 4.16.3 Forward current	51
Exa 4.16.4 Anticipated Factor	52
Exa 4.16.5 Leakage resistance	52
Exa 4.16.6 Dynamic resistance	53
Exa 4.16.7 Barrier capacitance	54
Exa 4.16.8 Width of depletion layer	54
Exa 4.16.9 Current in the junction	55
Exa 4.16.10 Forward biasing current	56
Exa 4.16.11 Theoretical diode current	56
Exa 4.16.12 Diode dynamic resistance	57
Exa 4.16.13 Q point	57
Exa 4.16.14 AC resistance of the Ge diode	58
Exa 4.16.15 Junction potential	58
Exa 4.16.16 Dynamic resistance	59
Exa 4.16.17 Space charge capacitance	60
Exa 4.16.18 Barrier capacitance	60
Exa 4.16.19 Diameter	61
Exa 4.16.20 Temperature of junction	62
Exa 4.16.21 Voltage	62
Exa 4.16.22 Reverse saturation current	63
Exa 5.9.1 IC and VCB	64
Exa 5.9.2 Value of base current	64
Exa 5.11.1 Value of emitter current	65
Exa 5.11.1.a Value of base and emitter current	65
Exa 5.11.3 Change in base current	66
Exa 5.11.4 Transistor current	66
Exa 5.11.5 Collector current	67
Exa 5.11.6 Current gain	68
Exa 5.11.7 AlphaDC and betaDC	68
Exa 5.14.1 AlphaDc and emitter current	69
Exa 5.14.2 Collector and base current	69

Exa 5.14.3 Base current	70
Exa 5.14.5 Emitter current	70
Exa 5.14.6 Region of operation of Si transistor	71
Exa 5.14.7 IB IC and VCE	72
Exa 5.14.8 Region of operation of Value of IB and IC	73
Exa 5.14.9 Value of VBB	73
Exa 5.14.10Minimum value of RC required	74
Exa 5.14.11Value of RE	75
Exa 5.14.12Collector voltage	76
Exa 6.9.1 Pinch off voltage	78
Exa 6.9.2 Value of VGS	79
Exa 6.9.3 Drain current	79
Exa 6.9.4 Transconductance	80
Exa 6.9.5 Value of transconductance and drain current	80
Exa 7.6.1 Component value	81
Exa 7.23.1 Open circuit voltage	81
Exa 7.23.2 Value of photocurrent density	82
Exa 8.13.1 Value of the anode current	84
Exa 8.14.1 Value of the peak reverse recovery current	85

Chapter 1

Semiconductor Materials and Crystal Properties

Scilab code Exa 1.18.3 Volume density of Si

```
1 // Exa 1.18.3
2 clc;
3 clear;
4 close;
5 // Given data
6 At = 28; // Atomic weight
7 n = 4;
8 N_A = 6.023*10^23;
9 a = 5.3; // in
10 a = a * 10^-10; // in m
11 m = At/N_A; // in gm
12 m = m*10^-3; // in kg
13 V = (a)^3; // in m^3
14 Rho = (m*n)/V; // in gm/m^3
15 Rho = Rho * 10^-3; // in kg/m^3
16 disp(Rho, "The volume density in kg/m^3 is");
```

Scilab code Exa 1.18.4 Density of copper crystal

```
1 // Exa 1.18.4
2 clc;
3 clear;
4 close;
5 // Given data
6 r = 1.278; // in
7 a = (4*r)/(sqrt(2)); // in
8 a = a * 10^-10; // in m
9 V = (a)^3; // in m^3
10 At = 63.5; // atomic weight
11 N_A = 6.023*10^23;
12 m = At/N_A; // in gm
13 m = m * 10^-3; // in kg
14 n = 4;
15 Rho = (m*n)/V; // in gm/m^3
16 Rho = Rho * 10^-3; // in kg/m^3
17 disp(Rho,"The density of copper crystal in kg/m^3 is
");
```

Scilab code Exa 1.21.1 Wavelength of X ray

```
1 // Exa 1.21.1
2 clc;
3 clear;
4 close;
5 // Given data
6 d = 2.82; // in
7 d = d * 10^-10; // in m
8 n = 1;
9 theta = 10; // in degree
10 //Formula 2*d*sin(theta) = n*lembda;
11 lembda = 2*d*sind(theta); // in m
12 lembda = lembda * 10^10; // in
```

```
13 disp(lembeda , "The wavelength of X-ray in      is ");
```

Scilab code Exa 1.21.2 Spacing of atomic layer

```
1 // Exa 1.21.2
2 clc;
3 clear;
4 close;
5 // Given data
6 lembda = 1.6; // in
7 lembda = lembda * 10^-10; // in m
8 theta = 14.2; // in degree
9 n = 1;
10 //Formula 2*d*sin(theta) = n*lembda;
11 d = (n*lembda)/(2*sind(theta)); // in m
12 d = d * 10^10; // in
13 disp(d,"The spacing of atomic layer in the crystal
      in      is");
```

Scilab code Exa 1.21.3 Interplaner spacing

```
1 // Exa 1.21.3
2 clc;
3 clear;
4 close;
5 // Given data
6 n = 1;
7 theta = 30; // in degree
8 lembda = 1.78; // in
9 lembda = lembda * 10^-10; // in m
10 //Formula 2*d*sin(theta) = n*lembda;
11 d = (n*lembda)/(2*sind(theta)); // in m
12 d = d * 10^10; // in
```

```
13 disp(d,"The interplaner spacing in      is");
```

Scilab code Exa 1.21.4 Interplaner spacing

```
1 // Exa 1.21.4
2 clc;
3 clear;
4 close;
5 // Given data
6 lembda = 0.58; // in
7 n = 1;
8 theta1 = 6.45; // in degree
9 d = (n*lembda)/(2*sind(theta1)); // in
10 disp(d,"Part (i) : At angle of 6.45 , Interplaner
    spacing of the crystal in      is ");
11 theta2 = 9.15; // in degree
12 d1 = (n*lembda)/(2*sind(theta2)); // in
13 disp(d1,"Part(ii) : At angle of 9.15 , Interplaner
    spacing of the crystal in      is ");
14 theta3 = 13; // in degree
15 n2 = 1;
16 d2 = (n2*lembda)/(2*sind(theta3)); // in
17 disp(d2,"Part(iii) : At angle of 13 , Interplaner
    spacing of the crystal in      is ");
18 // For
19 n=2;
20 d2 = (n*lembda)/(2*sind(theta3)); // in
21 disp(d2,"Part (iv) : The interplaner spacing in
    is : ")
22 disp(d1,"The interplaner spacing for some other set
    of reflecting in      is : ")
```

Scilab code Exa 1.21.5 Glacing angle

```

1 // Exa 1.21.5
2 clc;
3 clear;
4 close;
5 // Given data
6 a = 2.814; // in
7 h = 1;
8 k = 0;
9 l = 0;
10 d = a/(sqrt( ((h)^2) + ((k)^2) + ((l)^2) )); // in
11 n = 2;
12 lembda = 0.710; // in
13 //Formula 2*d*sin(theta) = n*lembda;
14 theta = asind(n*lembda/(2*d) ); // in degree
15 disp(theta , "The glacing angle in degree is");

```

Scilab code Exa 1.21.6 Wavelength of X ray

```

1 // Exa 1.21.6
2 clc;
3 clear;
4 close;
5 // Given data
6 a = 3.65; // in
7 h = 1;
8 k = 0;
9 l = 0;
10 d = a/(sqrt( ((h)^2) + ((k)^2) + ((l)^2) )); // in
11 n = 1;
12 theta = 60; // in degree
13 //Formula 2*d*sin(theta) = n*lembda;
14 lambda = 2*d*sind(theta); // in
15 disp(lambda , "Wavelength of X ray in is");

```

Scilab code Exa 1.21.7 Glacing angle

```
1 // Exa 1.21.7
2 clc;
3 clear;
4 close;
5 // Given data
6 lembda = 1.54; // in
7 lembda= lembda*10^-8; // in cm
8 At = 63.54; // atomic weight
9 density = 9.024; // in gm/cc
10 n = 1;
11 N_A = 6.023*10^23;
12 m = At/N_A; // mass
13 a =(density*m)^(1/3); // in cm
14 h = 1;
15 k = 0;
16 l = 0;
17 d = a/(sqrt( ((h)^2) + ((k)^2) + ((l)^2) )); // in cm
18 n = 1;
19 //Formula 2*d*sin(theta) = n*lembda;
20 theta = asind( (lembda)/(2*d) );// in degree
21 disp(theta,"The glancing angle in degree is");
```

Scilab code Exa 1.21.8 Glacing angle

```
1 // Exa 1.21.8
2 clc;
3 clear;
4 close;
5 // Given data
6 a = 3.615; // in
```

```

7 theta = 22; // in degree
8 n = 1;
9 h = 1;
10 k = 1;
11 l = 1;
12 d = a/(sqrt( ((h)^2) + ((k)^2) + ((l)^2) )); // in
13 // 2*d*sin(theta) = n*lmbda;
14 lembda = 2*d*sind(theta); // in
15 disp(lembda,"The wavelength in is");
16 n = 2;
17 //Formula 2*d*sin(theta) = n*lembda;
18 theta = asind(n*lembda/(2*d)); // in degree
19 disp(theta,"The glacing angle for second order in
degree is");
20 disp("To get the 2nd order spectrum the position of
the detector should be "+string(2*theta)+"")

```

Scilab code Exa 1.21.9 Lattice constant

```

1 // Exa 1.21.9
2 clc;
3 clear;
4 close;
5 // Given data
6 n = 1;
7 lembda = 1.54; // in
8 theta = 21.7; // in degree
9 //Formula 2*d*sin(theta) = n*lembda;
10 d = (lembda*n)/(2*sind(theta)); // in
11 h = 1;
12 k = 1;
13 l = 1;
14 // Formula d = a/(sqrt( ((h)^2) + ((k)^2) + ((l)^2)
));
15 a = d*(sqrt( ((h)^2) + ((k)^2) + ((l)^2) )); // in

```

```
16 disp(a," Lattice constant in      is");
```

Scilab code Exa 1.22.1 Distance between d211 planes

```
1 // Exa 1.22.1
2 clc;
3 clear;
4 close;
5 // Given data
6 a = 4.8; // in
7 h = 2;
8 k = 1;
9 l = 1;
10 d = a/(sqrt( ((h)^2) + ((k)^2) + ((l)^2) )); // in
11 disp(d,"The distance between d_211 plains in      is")
;
```

Scilab code Exa 1.22.2 Density

```
1 // Exa 1.22.2
2 clc;
3 clear;
4 close;
5 // Given data
6 r = 1.28; // in
7 //Formula r = (a*sqrt(2))/4;
8 a = (4*r)/(sqrt(2)); // in
9 a = a * 10^-8; // in cm
10 n = 4;
11 M = 63.5;
12 N_A = 6.023*10^23;
13 Rho = (n*M)/(N_A*((a)^3)); // in gm/cc
```

```
14 disp(Rho ,”The density in gm/cc is”);
```

Scilab code Exa 1.22.3 Number of atom per unit cell

```
1 // Exa 1.22.3
2 clc;
3 clear;
4 close;
5 // Given data
6 a = 2.9; // in
7 a = a * 10^-8; // in cm
8 Rho = 7.87; // in gm/cc
9 N_A = 6.023*10^23;
10 M = 55.85
11 // Rho = (n*M)/(N_A*((a)^3))
12 n = (Rho*N_A*((a)^3))/M; // in atoms per unit cell
13 disp(round(n),”The number of atoms per unit cell is
”);
```

Scilab code Exa 1.22.4 Radius of element atom

```
1 // Exa 1.22.4
2 clc;
3 clear;
4 close;
5 // Given data
6 M = 60; // in gm/mole
7 Rho = 6.23; // in gm/cc
8 n = 4;
9 N_A = 6.023*10^23;
10 // Rho = (n*M)/(N_A*((a)^3));
11 a = ( (n*M)/(N_A*Rho) )^(1/3); // in cm
12 r = (a*sqrt(2))/4; // in cm
```

```
13 r = r * 10^8; // in
14 disp(r,"The radius in is");
```

Scilab code Exa 1.22.5 Packing factor

```
1 // Exa 1.22.5
2 clc;
3 clear;
4 close;
5 // Given data
6 Rho = 5.96; // in gm/cc
7 M = 50;
8 n = 2;
9 N_A = 6.023*10^23;
10 //Formula Rho = (n*M)/(N_A*((a)^3));
11 a = ((n*M)/(N_A*Rho))^(1/3); // in cm
12 r = (a*sqrt(3))/4; // in cm
13 P_F = (2*(4/3)*%pi*((r)^3))/((a)^3); // Packing
    factor
14 disp(P_F,"The Packing factor is");
```

Scilab code Exa 1.22.6 Number of unit cell

```
1 // Exa 1.22.6
2 clc;
3 clear;
4 close;
5 // Given data
6 d = 5.2; // in gm/cc
7 n = 2;
8 M = 120;
9 N_A = 6.023*10^23;
10 m = M/N_A; //mass of 1 atom in gm
```

```
11 m = n*m; //mass of unit cell in gm
12 g = 20; // in gm
13 m = g/m; // in unit cells
14 disp(m,"The number of unit cell in its 20 gm is : ")
;
```

Scilab code Exa 1.22.7 Distance between K and F

```
1 // Exa 1.22.7
2 clc;
3 clear;
4 close;
5 // Given data
6 Rho = 2.48; // in gm/cc
7 K = 39; // molecular weight of K
8 F = 19; // molecular weight of F
9 M = K+F; // molecular weight of KF
10 n = 4;
11 N_A = 6.023*10^23;
12 //Formula Rho = (n*M)/(N_A*((a)^3));
13 a = ((n*M)/(N_A*Rho))^(1/3); // in cm
14 a = a * 10^8; // in
15 r = (a*sqrt(2))/4; // in
16 r = 2*r; // in
17 disp(r,"The distance between ions in is");
```

Chapter 2

Energy Bands And Charge Carriers in Semiconductor

Scilab code Exa 2.6.1 Energy Gap

```
1 // Exa 2.6.1
2 clc;
3 clear;
4 close;
5 // Given data
6 lembda = 11000; // in
7 lembda = lembda * 10^-10; // in m
8 h = 6.625*10^-34;
9 c = 3*10^8; // in m/s
10 e = 1.6*10^-19; // in C
11 E_g = (h*c)/(lembda*e); // in eV
12 disp(E_g,"The energy gap in eV is");
13
14 // Note: In the book, there is calculation error to
    evaluate the value of Eg, so the answer in the
    book is wrong and the answer of coding is correct
.
```

Scilab code Exa 2.6.2 Wavelength

```
1 // Exa 2.6.2
2 clc;
3 clear;
4 close;
5 // Given data
6 E_g = 0.75; // in eV
7 e = 1.6*10^-19; // in C
8 h = 6.63*10^-34; // in J
9 c = 3*10^8; // in m/s
10 //Formula E_g = (h*c)/(lambda*e);
11 lambda = (h*c)/(E_g*e); // in m
12 lambda = lambda * 10^10; // in
13 disp(lambda,"The wavelength in      is");
```

Scilab code Exa 2.15.1 Position of fermi level

```
1 //Exa 2.15.1
2 clc;
3 clear;
4 close;
5 // Given data
6 del_E = 0.3; // in eV
7 T1 = 300; // in K
8 T2 = 330; // in K
9 // del_E = K * T1 * log(N/N_c) where del_E= E_C-E_F
10 // del_E1 = K * T2 * log(N/N_c) where del_E1= E_C-
    E_F at T= 330 K
11 del_E1 = del_E*(T2/T1); // in eV
12 disp("The Fermi level will be "+string(del_E1)+" eV
below the conduction band")
```

Scilab code Exa 2.15.2 Thermal equilibrium electron concentration

```
1 //Exa 2.15.2
2 clc;
3 clear;
4 close;
5 // Given data
6 N_c = 2.8 * 10^19; // in cm^-3
7 del_E = 0.25; // fermi energy in eV
8 KT = 0.0259;
9 f_F = exp(-(del_E)/KT);
10 disp(f_F,"The probability in the condition band is
    occupied by an electron is ");
11 n_o = N_c * exp(-(del_E)/KT); // in cm^-3
12 disp(n_o,"The thermal equilibrium electron
    concentration in cm^-3 is ");
```

Scilab code Exa 2.15.3 Thermal equilibrium hole concentration

```
1 //Exa2.15.3
2 clc;
3 clear;
4 close;
5 // Given data
6 T1 = 300; // in K
7 T2 = 400; // in K
8 del_E = 0.27; // Fermi level in eV
9 KT = (0.0259) * (T2/T1); // in eV
10 N_v = 1.04 * 10^19; // in cm^-3
11 N_v = N_v * (T2/T1)^(3/2); // in cm^-3
12 p_o = N_v * exp(-(del_E)/KT); // in per cm^3
```

```
13 disp(p_o,"The thermal equilibrium hole concentration  
in per cm^3 is");
```

Scilab code Exa 2.16.1 Mobility of electrons in copper

```
1 // Exa 2.16.1  
2 clc;  
3 clear;  
4 close;  
5 // Given data  
6 At = 63.5; // atomic weight  
7 Rho = 1.7*10^-6; // in ohm cm  
8 d = 8.96; // in gm/cc  
9 N_A = 6.02*10^23; // in /gm.mole  
10 e = 1.6*10^-19; // in C  
11 n = (N_A/At)*d;  
12 Miu_e = 1/(Rho*n*e); // in cm^2/volt.sec  
13 disp(Miu_e,"The electron mobility in cm^2/volt-sec  
is");
```

Scilab code Exa 2.16.2 Charge density of free electrons

```
1 // Exa 2.16.2  
2 clc;  
3 clear;  
4 close;  
5 format('e',9)  
6 // Given data  
7 l = 0.1; // in m  
8 A = 1.7; // in mm^2  
9 A = A * 10^-6; // in m^2  
10 R = 0.1; // in ohm  
11 At = 63.5; // atomic weight
```

```

12 N_A = 6.02*10^23;
13 d = 8.96; // in gm/cc
14 n = (N_A/At)*d; // in /cc
15 n = n * 10^6; // in /m^3
16 //Formula R = Rho*(l/A);
17 Rho = (R*A)/l; // in ohm m
18 Sigma = 1/Rho; // in mho/m
19 e = 1.6*10^-19;
20 // Formula Sigma = n*e*Miu_e
21 Miu_e = Sigma/(n*e); // in m^2/V.sec
22 disp(Miu_e , "The mobility in m^2/V-sec is");

```

Scilab code Exa 2.16.3 Drift velocity

```

1 // Exa 2.16.3
2 clc;
3 clear;
4 close;
5 // Given data
6 format('v',7)
7 d = 10.5; // in gm/cc
8 At = 108; // atomic weight
9 N_A = 6.025*10^23; // in /gm mole
10 r = 10^-3; // in m
11 q = 1.6*10^-19; // in C
12 n = (N_A/At)*d; // in /cm^3
13 n = n * 10^6; // in /m^3
14 A = %pi*((r)^2); // in m^2
15 I = 2; // in A
16 // I = q*n*A*v;
17 v = I/(n*q*A); // in m/s
18 disp(v, "The drift velocity in m/s is");
19
20 // Note: There is calculation error to find the
      value of drift velocity (i.e v), so the answer in

```

the book is wrong.

Scilab code Exa 2.16.4 Mobily of charge carriers

```
1 // Exa 2.16.4
2 clc;
3 clear;
4 close;
5 format('e',10)
6 // Given data
7 d = 1.03; // in mm
8 d = d *10^-3; // in m
9 r = d/2; // in m
10 R = 6.51; // in ohm
11 l = 300; // in mm
12 e = 1.6*10^-19;
13 n = 8.4*10^28; // in /m^&#283
14 A = %pi*r^2;
15 // R = Rho*(l/A);
16 Rho = (R*A)/l; // in ohm m
17 Sigma = 1/Rho; // in mho/m
18 disp(Sigma,"The conductivity of copper in mho/m is")
;
19 //Formula sigma = n*e*Miu_e
20 Miu_e = Sigma/(n*e); // in m^2/V.sec
21 disp(Miu_e,"The mobility in m^2/V-sec is");
```

Scilab code Exa 2.16.5 Resistivity of Copper

```
1 // Exa 2.16.5
2 clc;
3 clear;
4 close;
```

```

5 format('e',8)
6 // Given data
7 At = 63.5; // atomic weight
8 d = 8.96; // in gm/cc
9 Miu_e = 43.28; // in cm^2/V.sec
10 N_A = 6.02*10^23; // in /gm mole
11 e = 1.6*10^-19; // in C
12 n = (N_A/At)*d; // in /cc
13 Rho = 1/(n*e*Miu_e); // in ohm-cm
14 disp(Rho,"The resistivity in ohm-cm is");

```

Scilab code Exa 2.17.1 Conductivity of pure Si

```

1 // Exa 2.17.1
2 clc;
3 clear;
4 close;
5 format('e',9)
6 // Given data
7 Mu_e = 1500; // in cm^2/volt sec
8 Mu_h = 500; // in cm^2/volt sec
9 n_i = 1.6 * 10^10; // in per cm^3
10 e = 1.6 * 10^-19; // in C
11 Sigma = n_i * (Mu_e + Mu_h) * e; // in mho/cm
12 disp(Sigma,"The conductivity of pure semiconductor
    in mho/cm is");

```

Scilab code Exa 2.17.2 Number of donor atoms

```

1 // Exa 2.17.2
2 clc;
3 clear;
4 close;

```

```

5 // Given data
6 Rho = 10; // in -cm
7 Mu_d = 500; // in cm^2/v.s.
8 e = 1.6*10^-19;
9 n_d = 1/(Rho * e * Mu_d); // in per cm^3
10 disp(n_d,"The number of donor atom must be added to
    achieve in per cm^3 is ");

```

Scilab code Exa 2.17.3 Conductivity of specimen

```

1 //Exa 2.17.3
2 clc;
3 clear;
4 close;
5 //Given data
6 AvagadroNumber = 6.02 * 10^23; // in atoms/gm.mole
7 at_Ge = 72.6; // atom weight of Ge
8 e = 1.6 * 10^-19; // in C
9 D_Ge = 5.32; // density of Ge in gm/c.c
10 Mu = 3800; // in cm^2/v.s.
11 C_Ge = (AvagadroNumber/at_Ge) * D_Ge; //
    concentration of Ge atoms in per cm^3
12 n_d = C_Ge/10^8; // in per cc
13 Sigma = n_d * Mu * e; // in mho/cm
14 disp(Sigma,"The conductivity in mho/cm is");

```

Scilab code Exa 2.17.4 Mobility of electrons in Ge

```

1 // Exa2.17.4
2 clc;
3 clear;
4 close;
5 // Given data

```

```

6 Rho = 0.3623 * 10^-3; // in Ohm m
7 Sigma = 1/Rho; // in mho/m
8 D = 4.42 * 10^28; // Ge density in atom/m^3
9 n_d = D / 10^6; // in atom/m^3
10 e = 1.6 * 10^-19; // in C
11 Mu = Sigma/(n_d * e); // in m^2/V.sec
12 disp(Mu,"The mobility of electron in germanium in m
^2/V.sec is");

```

Scilab code Exa 2.17.5 Density and mobility of holes

```

1 //Exa 2.17.5
2 clc;
3 clear;
4 close;
5 // Given data
6 AvagadroNumber = 6.025 * 10^26; // in kg.Mole
7 W = 72.59; // atomic weight of Ge
8 D = 5.36 * 10^3; //density of Ge in kg/m^3
9 Rho = 0.42; // resistivity in Ohm m
10 e = 1.6 * 10^-19; // in C
11 Sigma = 1/Rho; // in mho/m
12 n = (AvagadroNumber/W) * D; // number of Ge atoms
    present per unit volume
13 // Holes per unit volume , H = n*10^-6%
14 H= n*10^-8;
15 a=H;
16 // Formula sigma= a*e*Mu_h
17 Mu_h = Sigma/(a * e); // in m^2/V.sec
18 disp(Mu_h,"Mobility of holes in m^2/V.sec is");

```

Scilab code Exa 2.17.6 Current produced

```

1 //Exa 2.17.6
2 clc;
3 clear;
4 close;
5 // Given data
6 e = 1.6 * 10^-19; // in C
7 n_i = 2 * 10^19; // in /m^3
8 Mu_e = 0.36; // in m^2/v.s
9 Mu_h = 0.17; // in m^2/v.s
10 A = 1 * 10^-4; // in m^2
11 V = 2; //in volts
12 l = 0.3; // in mm
13 l = l * 10^-3; // in m
14 E=V/l; // in volt/m
15 Sigma = n_i * e * (Mu_e + Mu_h); // in mho/m
16 // J = I/A = Sigma * E
17 I= Sigma*E*A;
18 disp(I,"The current produced in a small germanium
plate in amp is");

```

Scilab code Exa 2.17.7 Resistivity of dopped Ge

```

1 // Exa 2.17.7
2 clc;
3 clear;
4 close;
5 format('e',10)
6 // Given data
7 D = 4.2 * 10^28; //density of Ge atoms in atoms/m^3
8 N_d = D / 10^6; // in atoms/m^3
9 e = 1.6 * 10^-19; // in C
10 Mu_e = 0.36; // in m^2/vs
11 Sigma_n = N_d * e * Mu_e; // in mho/m
12 Rho_n = 1/Sigma_n; // in ohm m
13 disp(Rho_n,"The resistivity of drop Ge in ohm m is ")

```

) ;

Scilab code Exa 2.17.8 Current produced in Ge sample

```
1 // Exa 2.17.8
2 clc;
3 clear;
4 close;
5 // given data
6 e = 1.6 * 10^-19; // in C
7 n_i = 1 * 10^19; // in per m^3
8 Mu_e = 0.36; // in m^2/volt.sec
9 Mu_h = 0.17; // in m^2/volt.sec
10 A = 2; // in cm^2
11 A = A * 10^-4; // in m^2
12 t = 0.1; // in mm
13 t = t * 10^-3; // in m
14 V = 4; // in volts
15 Sigma_i = n_i * e * (Mu_e + Mu_h); // in mho/m
16 J = Sigma_i * (V/t); // in Amp/m^2
17 I = J * A; // in Amp
18 disp(I,"The current produced in a Ge sample in Amp
is");
```

Scilab code Exa 2.17.9 Conductivity of pure Si

```
1 //Exa 2.17.9
2 clc;
3 clear;
4 close;
5 format('e',9)
6 // Given data
7 e = 1.6 * 10^-19; // in C
```

```

8 Mu_h = 500; // in cm^2/V.s.
9 Mu_e = 1500; // in cm^2/V.s.
10 n_i = 1.6 * 10^10; // in per cm^3
11 Sigma_i = n_i * e * ( Mu_h + Mu_e); // in mho/cm
12 disp(Sigma_i,"Conductivity of pure silicon at room
temperature in mho/cm is");

```

Scilab code Exa 2.19.1 Hall voltage produced

```

1 //Exa 2.19.1
2 clc;
3 clear;
4 close;
5 //Given data
6 l= 0.50*10^-2; // width of ribbon in m
7 d= 0.10*10^-3; // thickness of ribbon in m
8 A= l*d; // area of ribbon in m^2
9 B = 0.8; // in Tesla
10 D = 10.5; // density in gm/cc
11 I = 2; // in amp
12 q = 1.6 * 10^-19; // in C
13 n=6*10^28; // number of elec. per m^3
14 V_H = ( I * B * d)/(n * q * A); // in volts
15 disp(V_H,"The hall Voltage produced in volts is");

```

Scilab code Exa 2.19.2 Hall coefficient and mobility of electrons

```

1 //Exa 2.19.2
2 clc;
3 clear;
4 close;
5 format('e',8)
6 // Given data

```

```

7 l = 1; // in m
8 d = 1; // in cm
9 d = d * 10^-2; // in m
10 W = 1; // in mm
11 W = W * 10^-3; // in m
12 A = d * W; // in m^2
13 I= 1; // in Amp
14 B = 1; // Tesla
15 V_H = 0.074 * 10^-6; // in Volts
16 Sigma = 5.8 * 10^7; // in mho/m
17 R_H = (V_H * A)/(B*I*d); // in m^3/c
18 disp(R_H,"The hall coefficient in m^3/c is");
19 Mu = Sigma * R_H; // in m^2/volt.sec
20 disp(Mu,"The mobility of electrons in copper in m
^2/volt-sec is ");

```

Scilab code Exa 2.20.1 Ratio of electron to hole concentration

```

1 //Exa2.20.1
2 clc;
3 clear;
4 close;
5 // Given data
6 n_i = 1.4 * 10^18; // in /m^3
7 n_D = 1.4 * 10^24; // in /m^3
8 n=n_D; // in /m^3
9 p = n_i^2/n; // in /m^3
10 R = n/p;
11 disp(R,"The ratio of electrons to hole concentration
is");

```

Scilab code Exa 2.20.2 Hall angle

```

1 //Exa 2.20.2
2 clc;
3 clear;
4 close;
5 // Given data
6 B = 0.48; // in wb/m^2
7 R_H = 3.55 * 10^-4; // in m^3/c
8 Rho = 0.00912; // in ohm-m
9 Sigma = 1/Rho; // in (ohm-m)^-1
10 theta_H = atand( Sigma * B * R_H); // in degree
11 disp(theta_H,"The hall angle for a hall coefficient
in degree is");

```

Scilab code Exa 2.20.3 Mobility and density of charge carriers

```

1 //Exa 2.20.3
2 clc;
3 clear;
4 close;
5 //Given data
6 R = 9 * 10^-3; // in ohm-m
7 R_H = 3.6 * 10^-4; // in m^3
8 e = 1.6 * 10^-19; // in C
9 Sigma = 1/R; // in (ohm-m)^-1
10 Rho = 1/R_H; // in coulomb/m^3
11 n = Rho/e; // in /m^3
12 disp(n,"Density of charge carriers in per m^3 is");
13 Mu = Sigma * R_H; // in m^2/v-s
14 disp(Mu,"Mobility of charge carriers in m^2/V-s is")
;
```

Scilab code Exa 2.24.1 Current density in specimen

```

1 //Exa 2.24.1
2 clc;
3 clear;
4 close;
5 // Given data
6 e = 1.6 * 10^-19; // in C
7 R_H = 0.0145; // in m^3/coulomb
8 Mu_e = 0.36; // in m^2/v-s
9 E = 100; // in V/m
10 n = 1/(e * R_H); // in /m^3
11 J = n * e * Mu_e * E; // in A/m^2
12 disp(J,"The current density of specimen in A/m^2 is"
);

```

Scilab code Exa 2.24.2 Relaxation time and resistivity of conductor

```

1 //Exa 2.24.2
2 clc;
3 clear;
4 close;
5 //Given data
6 Mu_e = 7.04 * 10^-3; // in m^2/v-s
7 m = 9.1 * 10^-31;
8 E_F = 5.5; // in eV
9 n = 5.8 * 10^28;
10 e = 1.6 * 10^-19; // in C
11 Torque = (Mu_e/e) * m; // in sec
12 disp(Torque,"Relaxation Time in sec is ");
13 Rho = 1 /(n * e * Mu_e); // in ohm-m
14 disp(Rho," Resistivity of conductor in ohm-m is ");
15 V_F = sqrt((2 * E_F * e)/m); // in m/s
16 disp(V_F," Velocity of electrons with fermi-energy in
m/s is ");

```

Scilab code Exa 2.24.3 Temperature

```
1 //Exa 2.24.3
2 clc;
3 clear;
4 close;
5 format('v',5)
6 // Given data
7 E= 5.95; // in eV
8 EF= 6.25; // in eV
9 delE= 0.01;
10 // delE= 1-1/(1+exp((E-EF)/KT))
11 K=1.381*10^-23; // Boltzman Constant in J/K
12 T = ((E-EF)/log(1/(1-delE)-1)*1.6*10^-19)/K; // in K
13 T= round(T)
14 disp(T,"The temperature in K is : ")
```

Scilab code Exa 2.24.4 Thermal equilibrium hole concentration

```
1 //Exa 2.24.4
2 clc;
3 clear;
4 close;
5 // Given data
6 N_V = 1.04 * 10^19; // in cm^-3
7 T1 = 300; // in K
8 T2 = 400; // in K
9 del_E = 0.27; // in eV
10 N_V = N_V * (T2/T1)^1.5; // in cm^-3
11 KT = (0.0259) * (T2/T1); // in eV
12 P_o = N_V * exp(-(del_E)/KT); // in cm^-3
```

```
13 disp(P_o,"The thermal equilibrium hole concentration  
in silicon in cm^-3 is ");
```

Scilab code Exa 2.24.5 Minimum donor concentration

```
1 //Exa 2.24.5  
2 clc;  
3 clear;  
4 close;  
5 //Given data  
6 N_c = 2.8 * 10^19;  
7 N_V = 1.04 *10^19;  
8 T1 = 550; // in K  
9 T2 = 300; // in K  
10 E_g = 1.12;  
11 KT = (0.0259) ;  
12 n_i = sqrt(N_c *N_V *(T1/T2)^3* exp(-(E_g)/KT*T2/T1)  
); // in cm^-3  
13 // n_o = N_d/2 + sqrt((N_d/2)^2 + (n_i)^2)  
14 // 1.05*N_d -N_d/2= sqrt((N_d/2)^2 + (n_i)^2)  
15 N_d=sqrt((n_i)^2/((0.55)^2-1/4));  
16 disp(N_d,"Minimum donor concentration required in cm  
^-3 is");
```

Scilab code Exa 2.24.6 Quasi fermi energy levels

```
1 //Exa 2.24.6  
2 clc;  
3 clear;  
4 close;  
5 //Given data  
6 T = 300; // in K  
7 n_o = 10^15; // in cm^-3
```

```

8 n_i = 10^10; // in cm^-3
9 p_o = 10^5; // in cm^-3
10 del_n = 10^13; // in cm^-3
11 del_p = del_n; // in cm^-3
12 KT = 0.0259; // in eV
13 delta_E1= KT*log(n_o/n_i); // value of E_F-E_Fi in eV
14 delta_E2= KT*log((n_o+del_n)/n_i); // value of E_Fn-
    E_Fi in eV
15 delta_E3= KT*log((p_o+del_p)/n_i); // value of E_Fi-
    E_Fp in eV
16 disp(delta_E1,"The Fermi level for thermal
    equilibrium in eV is : ")
17 disp(delta_E2,"The quase-Fermi level for electrons
    in non equilibrium in eV is : ")
18 disp(delta_E3,"The quasi-Fermi level for holes in
    non equilibrium in eV is : ")
19 disp("The quasi-Fermi level for electrons is above
    E_Fi ")
20 disp("While the quasi-Fermi level for holes is below
    E_Fi")

```

Chapter 3

Excess Carriers In Semiconductor

Scilab code Exa 3.21.1 Hole concentration at equilibrium

```
1 // Exa 3.21.1
2 clc;
3 clear;
4 close;
5 format('e',9)
6 // Given data
7 N_d = 10^17; // atoms/cm^3
8 n_i = 1.5 * 10^10; // in /cm^3
9 n_o = 10^17; // in cm^3
10 // p_o * n_o = (n_i)^2
11 p_o = (n_i)^2 / n_o; //in holes/cm^3
12 disp(p_o,"The holes concentration at equilibrium in
holes/cm^3 is");
```

Scilab code Exa 3.21.3 Fermi level

```

1 // Exa 3.21.3
2 clc;
3 clear;
4 close;
5 // Given data
6 n_i = 1.5 * 10 ^10; // in /cm^3 for silicon
7 N_d = 10^17; // in atoms/cm^3
8 n_o = 10^17; // electrons/cm^3
9 KT = 0.0259;
10 // E_r - E_i = KT * log(n_o/n_i)
11 del_E = KT * log(n_o/n_i); // in eV
12 disp("The energy band for this type material is Ei +
    "+string(del_E)+" eV");

```

Scilab code Exa 3.21.4 Diffusion coefficients of electrons and holes

```

1 // Exa 3.21.4
2 clc;
3 clear;
4 close;
5 format('e',9)
6 // Given data
7 K = 1.38 * 10^-23; // in J/K
8 T = 27; // in degree
9 T = T + 273; // in K
10 e = 1.6 * 10^-19; // in C
11 Mu_e = 0.17; // in m^2/v-s
12 Mu_e1 = 0.025; // in m^2/v-s
13 D_n = ((K * T)/e) * Mu_e; // in m^2/s
14 disp(D_n,"The diffusion coefficient of electrons in
    m^2/s is ");
15 D_p = ((K * T)/e) * Mu_e1; // in m^2/s
16 disp(D_p,"The diffusion coefficient of holes in m
    ^2/s is ");

```

Scilab code Exa 3.21.5 Diffusion length

```
1 // Exa 3.21.5
2 clc;
3 clear;
4 close;
5 format('e',9)
6 // Given data
7 Mu_n = 0.15; // in m^2/v-s
8 K = 1.38 * 10^-23; // in J/K
9 T = 300; // in K
10 del_n = 10^20; // in per m^3
11 Toh_n = 10^-7; // in s
12 e = 1.6 * 10^-19; // in C
13 D_n = Mu_n * ((K * T)/e); // in m^2/s
14 disp(D_n,"The diffusion coefficient in m^2/s is");
15 L_n = sqrt(D_n * Toh_n); // in m
16 disp(L_n,"The Diffusion length in m is");
17 J_n = (e * D_n * del_n)/L_n; // in A/m^2
18 disp(J_n,"The diffusion current density in A/m^2 is");
19 // Note : The value of diffusion coefficient in the
book is wrong.
```

Scilab code Exa 3.21.6 Concentration of holes and electrons

```
1 // Exa 3.21.6
2 clc;
3 clear;
4 close;
5 // Given data
6 Sigma = 0.1; // in (ohm-m)^-1
```

```
7 Mu_n = 1300;
8 n_i = 1.5 * 10^10;
9 q = 1.6 * 10^-19; // in C
10 n_n = Sigma/(Mu_n * q); // in electrons/cm^3
11 disp(n_n*10^6,"The concentration of electrons per m
    ^3 is");
12 p_n = (n_i)^2/n_n; // in per cm^3
13 p_n = p_n * 10^6; // in perm^3
14 disp(p_n,"The concentration of holes per m^3 is");
```

Scilab code Exa 3.21.7 Electron transit time

```
1 // Exa 3.21.7
2 clc;
3 clear;
4 close;
5 // Given data
6 Mu_e = 0.13; // in m^2/v-s
7 Mu_h = 0.05; // in m^2/v-s
8 Toh_h = 10^-6; // in s
9 L = 100; // in m
10 L = L * 10^-6; // in m
11 V = 2; // in V
12 t_n = L^2/(Mu_e * V); // in s
13 disp(t_n,"Electron transit time in seconds is");
14 p_g = (Toh_h/t_n) * (1 + Mu_h/Mu_e); //photo
    conductor gain
15 disp(p_g,"Photo conductor gain is");
16
17 // Note: There is a calculation error to evaluate
    the value of t_n. So the answer in the book is
    wrong
```

Scilab code Exa 3.21.8 Resistivity of intrinsic Ge

```
1 // Exa 3.21.8
2 clc;
3 clear;
4 close;
5 //Given data
6 n_i = 2.5 * 10^13;
7 Mu_n = 3800;
8 Mu_p = 1800;
9 q = 1.6 * 10^-19; // in C
10 Sigma = n_i * (Mu_n + Mu_p) * q; // in (ohm-cm)^-1
11 Rho = 1/Sigma; // in ohm-cm
12 Rho= round(Rho);
13 disp(Rho,"The resistivity of intrinsic germanium in
ohm-cm is");
14 N_D = 4.4 * 10^22/(1*10^8); // in atoms/cm^3
15 Sigma_n = N_D * Mu_n * q; // in (ohm-cm)^-1
16 Rho_n = 1/Sigma_n; // in ohm-cm
17 disp(Rho_n,"If a donor type impurity is added to the
extent of 1 atom per 10^8 Ge atoms, then the
resistivity drops in ohm-cm is");
```

Scilab code Exa 3.21.9 Concentration of holes and electrons

```
1 // Exa 3.21.9
2 clc;
3 clear;
4 close;
5 // Given data
6 n_i = 10^16; // in /m3
7 N_D = 10^22; // in /m^3
8 n = N_D; // in /m^3
9 disp(n,"Electron concentration per m^3 is");
10 p = (n_i)^2/n; // in /m^3
```

```
11 disp(p,"Hole concentration per m^3 is");
```

Scilab code Exa 3.21.10 Ratio of donor atoms to Si atom

```
1 // Exa 3.21.10
2 clc;
3 clear;
4 close;
5 format('e',8)
6 // Given data
7 Rho = 9.6 * 10^-2; // in ohm-m
8 Sigma_n = 1/Rho; // in (ohm-m)^-1
9 q = 1.6 * 10^-19; // in C
10 Mu_n = 1300 * 10^-4; // in m^2/v-s
11 N_D = Sigma_n / (Mu_n * q); // in atoms/m^3
12 A_D = N_D; // Atom density in atoms/cm^3
13 A_D = A_D * 10^6; // atoms/m^3
14 R_si = N_D/A_D; // ratio
15 disp(R_si,"The ratio of donor atom to silicon atom
    is");
16
17 // Note: In the book the wrong value of N_D
    (5*10^22) is putted to evaluate the value of Atom
    Density (A_D) whereas the value of N_D is
    calculated as 5*10^20.
18 // So the answer in the book is wrong
```

Scilab code Exa 3.21.11 Equilibrium electron and hole densities

```
1 // Exa 3.21.11
2 clc;
3 clear;
4 close;
```

```

5 // Given data
6 n_i = 1.5 * 10^10; // in per cm^3
7 n_n = 2.25 * 10^15; // in per cm^3
8 p_n = (n_i)^2/n_n; // in per cm^3
9 disp(p_n,"The equilibrium electron density per cm^3
    is");
10 h_n = n_n; // in cm^3
11 disp(h_n,"Hole density in per cm^3 is");

```

Scilab code Exa 3.21.12 Carrier concentration

```

1 // Exa 3.21.12
2 clc;
3 clear;
4 close;
5 // Given data
6 N_A = 2 * 10^16; // in atoms/cm^3
7 N_D = 10^16; // in atoms/cm^3
8 C_c = N_A-N_D; // C_c stands for Carrier
    concentration /cm^3
9 disp(C_c,"Carrier concentration per cm^3 is");

```

Scilab code Exa 3.21.13 Generation rate due to irradiation

```

1 // Exa 3.21.13
2 clc;
3 clear;
4 close;
5 // Given data
6 del_n = 10^15; // in cm^3
7 Torque_p = 10 * 10^-6; // in sec
8 R_g = del_n/Torque_p; // in hole pairs/sec/cm^3

```

```
9 disp(R_g,"The rate of generation of minority carrier  
in electron hole pairs/sec/cm^3 is ");
```

Scilab code Exa 3.21.14 Mobility of minority charge carriers

```
1 // Exa 3.21.14  
2 clc;  
3 clear;  
4 close;  
5 // Given data  
6 v = 1/(20 * 10^-6); // in cm/sec  
7 E = 10; // in V/cm  
8 Mu= v/E; // in cm^2/V-sec  
9 disp(Mu,"The mobility of minority charge carrier in  
cm^2/V-sec is ");
```

Scilab code Exa 3.21.15 Hole and electron diffusion current

```
1 // Exa 3.21.15  
2 clc;  
3 clear;  
4 close;  
5 // Given data  
6 q = 1.6 * 10^-19; // in C  
7 N_D = 4.5 * 10^15; // in /cm^3  
8 del_p = 10^21;  
9 e=10; // in cm  
10 A = 1; // in mm^2  
11 A = A * 10^-14; // cm^2  
12 l = 10; // in cm  
13 Torque_p = 1; // in microsec  
14 Torque_p = Torque_p * 10^-6; // in sec  
15 Torque_n = 1; // in microsec
```

```

16 Torque_n = Torque_n * 10^-6; // in sec
17 n_i = 1.5 * 10^10; // in /cm^3
18 D_n = 30; // in cm^2/sec
19 D_p = 12; // in cm^2/sec
20 n_o = N_D; // in /cm^3
21 p_o = (n_i)^2/n_o; // in /cm^3
22 disp(p_o,"Hole concentration at thermal equilibrium
per cm^3 is");
23 l_n = sqrt(D_n * Torque_n); // in cm
24 disp(l_n,"Diffusion length of electron in cm is");
25 l_p = sqrt(D_p * Torque_p); // in cm
26 disp(l_p,"Diffusion length of holes in cm is");
27 x=34.6*10^-4; // in cm
28 dpBYdx = del_p * e; // in cm^4
29 disp(dpBYdx,"Concentration gradient of holes at
distance in cm^4 is");
30 e1 = 1.88 * 10^1; // in cm
31 dnBYdx = del_p * e1; // in cm^4
32 disp(dnBYdx,"Concentration gradient of electrons in
per cm is");
33 J_P = -(q) * D_p * dpBYdx; // in A/cm^2
34 disp(J_P,"Current density of holes due to diffusion
in A/cm^2 is");
35 J_n = q * D_n * dnBYdx; // in A/cm^2
36 disp(J_n,"Current density of electrons due to
diffusion in A/cm^2 is");

```

Scilab code Exa 3.21.16 Energy band gap of semiconductor material used

```

1 // Exa 3.21.16
2 clc;
3 clear;
4 close;
5 // Given data
6 e= 1.6*10^-19; // electron charge in C

```

```

7 h = 6.626 * 10^-34; // in J-s
8 h= h/e; // in eV
9 c = 3 * 10^8; // in m/s
10 lembda = 5490 * 10^-10; // in m
11 f = c/lembda;
12 E = h * f; // in eV
13 disp(E,"The energy band gap of the semiconductor
material in eV is");

```

Scilab code Exa 3.21.17 Current density in Si

```

1 // Exa 3.21.17
2 clc;
3 clear;
4 close;
5 // Given data
6 y2 = 6 * 10^16; // in /cm^3
7 y1 = 10^17; // in /cm^3
8 x2 = 2; // in m
9 x1 = 0; // in m
10 D_n = 35; // in cm^2/sec
11 q = 1.6 *10^-19; // in C
12 dnBYdx = (y2 - y1)/((x2-x1) * 10^-4);
13 J_n = q * D_n * dnBYdx; // in A/cm^2
14 disp(J_n,"The current density in silicon in A/cm^2
is");

```

Scilab code Exa 3.21.18 Resistance of the bar

```

1 // Exa 3.21.18
2 clc;
3 clear;
4 close;

```

```

5 // Given data
6 q = 1.6 * 10^-19; // in C
7 n_n = 5 * 10^20; // in /m^3
8 n_n = n_n * 10^-6; // in cm^3
9 Mu_n = 0.13; // in m^2/V-sec
10 Mu_n = Mu_n * 10^4; // in cm^2/V-sec
11 Sigma_n = q * n_n * Mu_n; // in (ohm-cm)^-1
12 Rho = 1/Sigma_n; // in -cm
13 l = 0.1; // in cm
14 A = 100; // m^2
15 A = A * 10^-8; // in cm^2
16 R = Rho * (l/A); // in Ohm
17 R=round(R*10^-6); // in M
18 disp(R,"The resistance of the bar in M is");

```

Scilab code Exa 3.21.19 Depletion width

```

1 // Exa 3.21.19
2 clc;
3 clear;
4 close;
5 // Given data
6 t_d = 3; // total depletion in m
7 D = t_d/9; // in m
8 disp(D,"Depletion width in m is");

```

Scilab code Exa 3.21.20 Minority carrier density

```

1 // Exa 3.21.20
2 clc;
3 clear;
4 close;
5 // Given data

```

```

6 n_i = 1.5 * 10^16; // in /m^3
7 n_n = 5 * 10^20; // in /m^3
8 p_n = (n_i)^2/n_n; // in /m^3
9 disp(p_n,"The majority carrier density per m^3 is");

```

Scilab code Exa 3.21.21 Collector current density

```

1 // Exa 3.21.21
2 clc;
3 clear;
4 close;
5 // Given data
6 D_n = 25; // in cm^2/sec
7 q = 1.6 * 10^-19; // in C
8 y2 = 10^14; // in /cm^3
9 y1 = 0; // in /cm^3
10 x2 = 0; // in m
11 x1 = 0.5; // in m
12 x1 = x1 * 10^-4; // in cm
13 dnBYdx = abs((y2-y1)/(x2-x1)); // in /cm^4
14 J_n = q * D_n * (dnBYdx); // in /cm^4
15 J_n = J_n * 10^-1; // in A/cm^2
16 disp(J_n,"The collector current density in A/cm^2 is
");
17
18 // Note: In the book, the calculated value of dn by
// dx (2*10^19) is wrong. Correct value is 2*10^18
// so the answer in the book is wrong.

```

Scilab code Exa 3.21.22 Band gap

```

1 //Exa 3.21.22
2 clc;

```

```

3 clear;
4 close;
5 // Given data
6 h = 6.64 * 10^-34; // in J-s
7 e= 1.6*10^-19; // electron charge in C
8 c= 3 * 10^8; // in m/s
9 lembda = 0.87; // in m
10 lembda = lembda * 10^-6; // in m
11 E_g = (h * c)/lembda; // in J-s
12 E_g= E_g/e; // in eV
13 disp(E_g,"The band gap of the material in eV is");

```

Scilab code Exa 3.21.23 Total energy absorbed by sample

```

1 // Exa 3.21.23
2 clc;
3 clear;
4 close;
5 // Given data
6 I_o = 10; // in mW
7 e = 1.6 * 10^-19; // in J/eV
8 hv = 2; // in eV
9 hv1=1.43; // in eV
10 alpha = 5 * 10^4; // in cm^-1
11 l = 46; // in m
12 l = l * 10^-6; // in m
13 I_t = round(I_o * exp(-(alpha) * l)); // in mW
14 AbsorbedPower= I_o-I_t; // in mW
15 AbsorbedPower=AbsorbedPower*10^-3; // in W or J/s
16 disp(AbsorbedPower,"The absorbed power in watt or J/
    s is");
17 F= (hv-hv1)/hv; // fraction of each photon energy
    unit
18 EnergyConToHeat= AbsorbedPower*F; // in J/s
19 disp(EnergyConToHeat , "The amount of energy converted

```

```

        to heat per second in J/s is : ")
20 A= (AbsorbedPower-EnergyConToHeat)/(e*hv1);
21 disp(A,"The number of photon per sec given off from
      recombination events in photons/s is");

```

Scilab code Exa 3.21.24 Hole current

```

1 // Exa 3.21.24
2 clc;
3 clear;
4 close;
5 // Given data
6 format('e',9)
7 Mu_p = 500; // in cm^2/v-s
8 kT = 0.0259;
9 Toh_p = 10^-10; // in sec
10 p_o = 10^17; // in cm^-3
11 q= 1.6*10^-19; // in C
12 A=0.5; // in square meter
13 del_p = 5 * 10^16; // in cm^-3
14 n_i= 1.5*10^10; // in cm^-3
15 D_p = kT * Mu_p; // in cm/s
16 L_p = sqrt(D_p * Toh_p); // in cm
17 x = 10^-5; // in cm
18 p = p_o+del_p* %e^(x/L_p); // in cm^-3
19 // p= n_i*%e^(Eip)/kT where Eip=E_i-F_p
20 Eip= log(p/n_i)*kT; // in eV
21 Ecp= 1.1/2-Eip; // value of E_c-E_p in eV
22 Ip= q*A*D_p/L_p*del_p*%e^(x/L_p); // in A
23 disp(Ip,"The hole current in A is : ")
24 Qp= q*A*del_p*L_p; // in C
25 disp(Qp,"The value of Qp in C is : ")
26
27 // Note: There is a calculation error to evalaute
      the value of hole current but they putted correct

```

value of it to evaluate the value of Q_p .
28 // Hence the value of hole current in the
book is wrong

Chapter 4

Junction Properties

Scilab code Exa 4.16.1 Contact difference of potential

```
1 // EXa 4.16.1
2 clc;
3 clear;
4 close;
5 // Given data
6 t = 4.4 * 10^22; // total number of Ge atoms/cm^3
7 n = 1 * 10^8; // number of impurity atoms
8 N_A = t/n; // in atoms/cm^3
9 N_A = N_A * 10^6; // in atoms/m^3
10 N_D = N_A * 10^3; // in atoms/m^3
11 n_i = 2.5 * 10^13; // in atoms/cm^3
12 n_i = n_i * 10^6; // in atoms/m^3
13 V_T = 26; //in mV
14 V_T= V_T*10^-3; // in V
15 V_J = V_T * log((N_A * N_D)/(n_i)^2); // in V
16 disp(V_J,"The contact potential in V is");
17 // Part (b)
18 t = 5* 10^22; // total number of Si atoms/cm^3
19 N_A = t/n; // in atoms/cm^3
20 N_A = N_A * 10^6; // in atoms/m^3
21 N_D = N_A * 10^3; // in atoms/m^3
```

```

22 n_i = 1.5 * 10^10; // in atoms/cm^3
23 n_i = n_i * 10^6; // in atoms/m^3
24 V_T = 26; //in mV
25 V_T= V_T*10^-3; // in V
26 V_J = V_T * log((N_A * N_D)/(n_i)^2); // in V
27 disp(V_J,"The contact potential in V is");

```

Scilab code Exa 4.16.2 Height of potential energy barrier

```

1 // Exa 4.16.2
2 clc;
3 clear;
4 close;
5 // Given data
6 V_T = 26; // in mV
7 V_T=V_T*10^-3; // in V
8 n_i = 2.5 * 10^13;
9 Sigma_p = 1;
10 Sigma_n = 1;
11 Mu_n = 3800;
12 q = 1.6 * 10^-19; // in C
13 Mu_p = 1800;
14 N_A = Sigma_p/(2* q * Mu_p); // in /cm^3
15 N_D = Sigma_n /(q * Mu_n); // in /cm^3
16 V_J = V_T * log((N_A * N_D)/(n_i)^2); // in V
17 disp(V_J,"For Ge the height of the energy barrier in
   V is");
18 // For Si p-n junction
19 n_i = 1.5 * 10^10;
20 Mu_n = 1300;
21 Mu_p = 500;
22 N_A = Sigma_p/(2* q * Mu_p); // in /cm^3
23 N_D = Sigma_n /(q * Mu_n); // in /cm^3
24 V_J = V_T * log((N_A * N_D)/(n_i)^2); // in V
25 disp(V_J,"For Si p-n junction the height of the

```

energy barrier in V is");

Scilab code Exa 4.16.3 Forward current

```
1 //Exa 4.16.3
2 clc;
3 clear;
4 close;
5 // Given data
6 Eta = 1;
7 V_T = 26; // in mV
8 V_T= V_T*10^-3; // in V
9 // I = I_o * (%e^(V/(Eta*V_T)) - 1) and I = -(0.9) * I_o;
10 V= log(1-0.9)*V_T; // in V
11 disp(V,"The voltage in volts is : ")
12 // Part (ii)
13 V1=0.05; // in V
14 V2= -0.05; // in V
15 ratio= (%e^(V1/(Eta*V_T))-1)/(%e^(V2/(Eta*V_T))-1)
16 disp(ratio,"The ratio of the current for a forward
bias to reverse bias is : ")
17 // Part (iii)
18 Io= 10; // in A
19 Io=Io*10^-3; // in mA
20 //For
21 V=0.1; // in V
22 I = Io * (%e^(V/(Eta*V_T)) - 1); // in mA
23 disp(I,"For V=0.1 V , the value of I in mA is : ")
24 //For
25 V=0.2; // in V
26 I = Io * (%e^(V/(Eta*V_T)) - 1); // in mA
27 disp(I,"For V=0.2 V , the value of I in mA is : ")
28 //For
29 V=0.3; // in V
```

```
30 I = Io * (%e^(V/(Eta*V_T)) - 1); // in mA
31 disp(I*10^-3, "For V=0.3 V , the value of I in A is :
")
32 disp("From three value of I, for small rise in
      forward voltage , the diode current increase
      rapidly")
```

Scilab code Exa 4.16.4 Anticipated Factor

```
1 //Exa 4.16.4
2 clc;
3 clear;
4 close;
5 // Given data
6 // Part (i)
7 T1= 25; // in C
8 T2= 80; // in C
9 // Formula Io2= Io1*2^((T2-T1)/10)
10 AntiFactor= 2^((T2-T1)/10);
11 disp(round(AntiFactor), "Anticipated factor for Ge is
      : ")
12 // Part (ii)
13 T1= 25; // in C
14 T2= 150; // in C
15 AntiFactor= 2^((T2-T1)/10);
16 disp(round(AntiFactor), "Anticipated factor for Si is
      : ")
```

Scilab code Exa 4.16.5 Leakage resistance

```
1 //Exa 4.16.5
2 clc;
3 clear;
```

```

4 close;
5 // Given data
6 I=5; // in A
7 V=10; // in V
8 T1= 0.11; // in C^-1
9 T2= 0.07; // in C^-1
10 // Io+I_R=I (i)
11 // dI_by_dT= dIo_by_dT (ii)
12 // 1/Io*dIo_by_dT = T1 and 1/I*dI_by_dT = T2, So
13 Io= T2*I/T1; // in A
14 I_R= I-Io; // in A
15 R= V/I_R; // in M
16 disp(R,"The leakage resistance in M is : ")

```

Scilab code Exa 4.16.6 Dynamic resistance

```

1 //Exa 4.16.6
2 clc;
3 clear;
4 close;
5 // Given data
6 Eta = 1;
7 T = 125; // in C
8 T = T + 273; // in K
9 V_T = 8.62 * 10^-5 * 398; // in V
10 I_o = 30; // in A
11 I_o= I_o*10^-6; // in A
12 v = 0.2; // in V
13 r_f = (Eta * V_T)/(I_o * %e^(v/(Eta* V_T))); // in ohm
14 disp(r_f,"The dynamic resistance in the forward direction in ohm is ");
15 r_r = (Eta * V_T)/(I_o * %e^(-v/(Eta* V_T))); // in ohm
16 disp(r_r*10^-3,"The dynamic resistance in the

```

```
    reverse direction in kohm is");
```

Scilab code Exa 4.16.7 Barrier capacitance

```
1 // Exa 4.16.7
2 clc;
3 clear;
4 close;
5 // Given data
6 epsilon = 16/(36 * %pi * 10^11); // in F/cm
7 A = 1 * 10^-2;
8 W = 2 * 10^-4;
9 C_T = (epsilon * A)/W; // in F
10 disp(C_T*10^12, "The barrier capacitance in pF is");
```

Scilab code Exa 4.16.8 Width of depletion layer

```
1 //Exa 4.16.8
2 clc;
3 clear;
4 close;
5 //Given data
6 A = 1; // in mm^2
7 A = A * 10^-6; // in m^2
8 N_A = 3 * 10^20; // in atoms/m^3
9 q = 1.6 *10^-19; // in C
10 V_o = 0.2; // in V
11 epsilon_r=16;
12 epsilon_o= 8.854*10^-12; // in F/m
13 epsilon=epsilon_r*epsilon_o;
14 // Part (a)
15 V=-10; // in V
16 // V_o - V = 1/2*((q * N_A )/epsilon) * W^2
```

```

17 W = sqrt(((V_o - V) * 2 * epsilon)/(q * N_A)); // m
18 C_T1 = (epsilon * A)/W; // in F
19 disp(W*10^6,"The width of the depletion layer for
      an applied reverse voltage of 10V in m is ");
20 // Part (b)
21 V=-0.1; // in V
22 W = sqrt(((V_o - V) * 2 * epsilon)/(q * N_A)); // m
23 C_T2 = (epsilon * A)/W; // in F
24 disp(W*10^6,"The width of the depletion layer for
      an applied reverse voltage of 0.1V in m is ");
25 // Part (c)
26 V=0.1; // in V
27 W = sqrt(((V_o - V) * 2 * epsilon)/(q * N_A)); // m
28 disp(W*10^6,"The width of the depletion layer for
      an applied for a forward bias of 0.1V in m is "
      );
29 // Part (d)
30 disp(C_T1*10^12,"The space charge capacitance for an
      applied reverse voltage of 10V in pF is");
31 disp(C_T2*10^12,"The space charge capacitance for an
      applied reverse voltage of 0.1V in pF is");

```

Scilab code Exa 4.16.9 Current in the junction

```

1 // Exa 4.16.9
2 clc;
3 clear;
4 close;
5 // Given data
6 I_o = 1.8 * 10^-9; // A
7 v = 0.6; // in V
8 Eta = 2;
9 V_T = 26; // in mV
10 V_T=V_T*10^-3; // in V
11 I = I_o * (%e^(v/(Eta * V_T))); // in A

```

```
12 disp(I*10^3,"The current in the junction in mA is");
```

Scilab code Exa 4.16.10 Forward biasing current

```
1 // Exa 4.16.10
2 clc;
3 clear;
4 close;
5 // Given data
6 I_o = 2.4 * 10^-14;
7 I = 1.5; // in mA
8 I=I*10^-3; // in A
9 Eta = 1;
10 V_T = 26; // in mV
11 V_T= V_T*10^-3; // in V
12 v =log((I + I_o)/I_o) * V_T; // in V
13 disp(v,"The forward biasing voltage across the
junction in V is");
```

Scilab code Exa 4.16.11 Theoretical diode current

```
1 // Exa 4.16.11
2 clc;
3 clear;
4 close;
5 // Given data
6 I_o = 10; // in nA
7 // I = I_o * ((e^(v/(Eta * V_T))) - 1)
8 // e^(v/(Eta * V_T))<< 1, so neglecting it
9 I = I_o * (-1); // in nA
10 disp(I,"The Diode current in nA is ");
```

Scilab code Exa 4.16.12 Diode dynamic resistance

```
1 // Exa 4.16.12
2 clc;
3 clear;
4 close;
5 // Given data
6 R = 4.5; // in ohm
7 I = 44.4; // in mA
8 I=I*10^-3; // in A
9 V = R * I; // in V
10 Eta = 1;
11 V_T = 26; // in mV
12 V_T=V_T*10^-3; // in V
13 I_o = I/((%e^(V/(Eta * V_T))) -1); // in A
14 // At
15 V = 0.1; // in V
16 r_f = (Eta * V_T)/(I_o * ((%e^(V/(Eta * V_T)))-1));
    // in ohm
17 disp(r_f,"The diode dynamic resistance is");
```

Scilab code Exa 4.16.13 Q point

```
1 // Exa 4.16.13
2 clc;
3 clear;
4 close;
5 // Given data
6 V_D = 10; // in V
7 // V_S = i*R_L + V_D
8 V_S = V_D; // in V (i * R_L = 0)
```

```

9 disp(V_S,"when diode is OFF, the voltage in volts is
       : ");
10 R_L = 250; // in ohm
11 I = V_S/R_L; // in A
12 disp(I*10^3,"when diode is ON, the current in mA is"
       );
13 V_D= 0:0.1:10; // in V
14 I= (V_S-V_D)/R_L*1000; // in mA
15 plot(V_D,I)
16 xlabel("V_D in volts");
17 ylabel("Current in mA")
18 title("DC load line");
19 disp("DC load line shown in figure")

```

Scilab code Exa 4.16.14 AC resistance of the Ge diode

```

1 // Exa 4.16.14
2 clc;
3 clear;
4 close;
5 // Given data
6 V = 0.25; // in V
7 I_o = 1.2; // in A
8 I_o = I_o * 10^-6; // in A
9 V_T = 26; // in mV
10 V_T = V_T * 10^-3; // in V
11 Eta = 1;
12 r = (Eta * V_T)/(I_o * (%e^(V/(Eta * V_T)))); // in
       ohm
13 disp(r,"The ac resistance of the diode in ohm is");

```

Scilab code Exa 4.16.15 Junction potential

```

1 // Exa 4.16.15
2 clc;
3 clear;
4 close;
5 // Given data
6 t = 4.4 * 10^22; // in total number of atoms/cm^3
7 n = 1 * 10^8; // number of impurity
8 N_A = t/n; // in atoms/cm^3
9 N_A = N_A * 10^6; // in atoms/m^3
10 N_D = N_A * 10^3; // in atoms/m^3
11 V_T = 26; // in mV
12 V_T = V_T * 10^-3; // in V
13 n_i = 2.5 * 10^19; // in /cm^3
14 V_J = V_T * log((N_A * N_D)/(n_i)^2); // in V
15 disp(V_J,"The junction potential in V is")

```

Scilab code Exa 4.16.16 Dynamic resistance

```

1 // Exa 4.16.16
2 clc;
3 clear;
4 close;
5 // Given data
6 Eta = 1;
7 I_o = 30; // in MuA
8 I_o = I_o * 10^-6; // in A
9 v = 0.2; // in V
10 K = 1.381 * 10^-23; // in J/degree K
11 T = 125; // in C
12 T = T + 273; // in K
13 q = 1.6 * 10^-19; // in C
14 V_T = (K*T)/q; // in V
15 r_f = (Eta * V_T)/(I_o * (%e^(v/(Eta * V_T)))); // in ohm
16 disp(r_f,"The forward dynamic resistance in ohm is")

```

```

    ;
17 r_f1 = (Eta * V_T)/(I_o * (%e^(-(v)/(Eta * V_T))));  

    // in ohm  

18 disp(r_f1*10^-3,"The Reverse dynamic resistance in  

    k   is");

```

Scilab code Exa 4.16.17 Space charge capacitance

```

1 // Exa 4.16.17
2 clc;
3 clear;
4 close;
5 // Given data
6 q = 1.6 * 10^-19; // in C
7 N_A = 3 * 10^20; // in /m^3
8 A = 1; // in m^2
9 A = A * 10^-6; // in m^2
10 V = -10; // in V
11 V_J = 0.25; // in V
12 V_B = V_J - V; // in V
13 epsilon_o = 8.854; // in pF/m
14 epsilon_o = epsilon_o * 10^-12; // in F/m
15 epsilon_r = 16;
16 epsilon = epsilon_o * epsilon_r;
17 W = sqrt((V_B * 2 * epsilon)/(q * N_A)); // in m
18 disp(W*10^6,"The width of depletion layer in m is"  

    );
19 C_T = (epsilon * A)/W; // in pF
20 disp(C_T*10^12,"the space charge capacitance in pF  

    is");

```

Scilab code Exa 4.16.18 Barrier capacitance

```

1 // Exa 4.16.18
2 clc;
3 clear;
4 close;
5 // Given data
6 W = 2 * 10^-4; // in cm
7 W = W * 10^-2; // in m
8 A = 1; // in mm^2
9 A = A * 10^-6; // in m^2
10 epsilon_r = 16;
11 epsilon_o = 8.854 * 10^-12; // in F/m
12 epsilon = epsilon_r * epsilon_o;
13 C_T = (epsilon * A)/W; // in F
14 disp(C_T*10^12,"The barrier capacitance in pF is");

```

Scilab code Exa 4.16.19 Diameter

```

1 // Exa 4.16.19
2 clc;
3 clear;
4 close;
5 // Given data
6 C_T = 100; // in pF
7 C_T=C_T*10^-12; // in F
8 epsilon_r = 12;
9 epsilon_o = 8.854 * 10^-12; // in F/m
10 epsilon = epsilon_r * epsilon_o;
11 Rho_p = 5; // in ohm-cm
12 Rho_p = Rho_p * 10^-2; // in ohm-m
13 V_j = 0.5; // in V
14 V = -4.5; // in V
15 Mu_p = 500; // in cm^2
16 Mu_p = Mu_p * 10^-4; // in m^2
17 Sigma_p = 1/Rho_p; // in per ohm-m
18 qN_A = Sigma_p/ Mu_p;

```

```

19 V_B = V_j - V;
20 W = sqrt((V_B * 2 * epsilon)/qN_A); // in m
21 //C_T = (epsilon * A)/W;
22 A = (C_T * W)/ epsilon; // in m
23 D = sqrt(A * (4/%pi)); // in m
24 D = D * 10^3; // in mm
25 disp(D,"The diameter in mm is");

```

Scilab code Exa 4.16.20 Temperature of junction

```

1 // Exa 4.16.20
2 clc;
3 clear;
4 close;
5 // Given data
6 q = 1.6 * 10^-19; // in C
7 Mu_p = 500; // in cm^2/V-sec
8 Rho_p = 3.5; // in ohm-cm
9 Mu_n = 1500; // in cm^2/V-sec
10 Rho_n = 10; // in ohm-cm
11 N_A = 1/(Rho_p * Mu_p * q); // in /cm^3
12 N_D = 1/(Rho_n * Mu_n * q); // in /cm^3
13 V_J = 0.56; // in V
14 n_i = 1.5 * 10^10; // in /cm^3
15 V_T = V_J/log((N_A * N_D)/(n_i)^2); // in V
16 // V_T = T/11600
17 T = V_T * 11600; // in K
18 T = T - 273; // in C
19 disp(T,"The Temperature of junction in C is");

```

Scilab code Exa 4.16.21 Voltage

```
1 // Exa 4.16.21
```

```

2 clc;
3 clear;
4 close;
5 // Given data
6 V_T = 26; // in mV
7 V_T = V_T * 10^-3; // in V
8 Eta = 1;
9 // I = -90% for Io , so
10 IbyIo= 0.1;
11 // I = I_o * ((e^(v/(Eta * V_T)))-1)
12 V = log(IbyIo) * V_T; // in V
13 disp(V,"The reverse bias voltage in volts is");

```

Scilab code Exa 4.16.22 Reverse saturation current

```

1 // Exa 4.16.22
2 clc;
3 clear;
4 close;
5 // Given data
6 R = 5; // in ohm
7 I = 50; // in mA
8 I=I*10^-3; // in A
9 V = R * I; // in V
10 Eta = 1;
11 V_T = 26; // in mV
12 V_T=V_T*10^-3; // in V
13 I_o = I/((%e^(V/(Eta * V_T))) - 1); // in A
14 disp(I_o*10^6,"Reverse saturation current in A is"
);
15 v1 = 0.2; // in V
16 r = (Eta * V_T)/(I_o * (%e^(v1/(Eta * V_T)))); // in
ohm
17 disp(r,"Dynamic resistance of the diode in ohm is");

```

Chapter 5

Bipolar Junction Transistors

Scilab code Exa 5.9.1 IC and VCB

```
1 // Exa 5.9.1
2 clc;
3 clear;
4 close;
5 // Given data
6 V_EE = 8; // in V
7 V_BE = 0.7; // in V
8 R_E = 1.5; // in k ohm
9 I_E = (V_EE - V_BE)/R_E; // in mA
10 I_C = I_E; // in mA
11 disp(I_C,"The value of I_C in mA is");
12 V_CC = 18; // in V
13 R_C = 1.2; // in k
14 V_CB = V_CC - (I_C * R_C); // in V
15 disp(V_CB,"The value of V_CB in V is");
```

Scilab code Exa 5.9.2 Value of base current

```
1 // Exa 5.9.2
2 clc;
3 clear;
4 close;
5 // Given data
6 alpha = 0.9;
7 I_E = 1; // mA
8 I_C = alpha * I_E; // in mA
9 I_B = I_E - I_C; // in mA
10 disp(I_B,"The value of base current in mA is");
```

Scilab code Exa 5.11.1 Value of emitter current

```
1 // Exa 5.11.1
2 clc;
3 clear;
4 close;
5 // Given data
6 bita = 50;
7 I_B= 20; // in A
8 I_B=I_B*10^-6; // in A
9 I_C= bita*I_B; // in A
10 I_E= I_C+I_B; // in A
11 I_E = I_E * 10^3; // in mA
12 disp(I_E,"The Emitter current in mA is");
```

Scilab code Exa 5.11.1.a Value of base and emitter current

```
1 // Exa 5.11.1( a )
2 clc;
3 clear;
4 close;
5 // Given data
```

```
6 beta_dc = 90;
7 I_C = 15; // in mA
8 I_C = I_C * 10^-3; // in A
9 I_B = I_C/beta_dc; // in A
10 disp(I_B*10^6,"The base current in A is");
11 I_E = I_C + I_B; // in A
12 I_E = I_E * 10^3; // in mA
13 disp(I_E,"The Emitter current in mA is");
14 alpha_dc = beta_dc/(1+beta_dc);
15 disp(alpha_dc,"The value of alpha_dc is");
```

Scilab code Exa 5.11.3 Change in base current

```
1 // Exa 5.11.3
2 clc;
3 clear;
4 close;
5 // Given data
6 del_ic = 1.8; // in mA
7 del_ie = 1.89; // in mA
8 alpha = del_ic / del_ie;
9 bita = alpha/(1 - alpha);
10 del_ib = del_ic/bita; // in mA
11 del_ib = del_ib * 10^3; // in A
12 disp(del_ib,"The change in I_B in A is");
```

Scilab code Exa 5.11.4 Transistor current

```
1 //Exa 5.11.4
2 clc;
3 clear;
4 close;
5 // Given data
```

```

6 V_CC = 10; // in V
7 R_C = 3; // in k
8 R_C= R_C*10^3; // in
9 bita = 100;
10 I_CO = 20; // in nA
11 I_CO = I_CO * 10^-9; // in A
12 V_BB = 5; // in V
13 R_B = 200; // in k
14 R_B= R_B*10^3; // in
15 V_BE = 0.7; // in V
16 // Applying KVL to the base circuit , V_BB= I_B*R_B+
V_BE
17 I_B = (V_BB - V_BE)/R_B; // in A
18 disp(I_B*10^6,"The base current in A is");
19 I_C = (bita * I_B) + I_CO; // in A
20 disp(I_C*10^3,"The collector current in mA is");
21 I_E = I_C + I_B; // in A
22 disp(I_E*10^3,"Emitter current in mA is");
23 V_CE = V_CC - (I_C * R_C); // in V
24 disp(V_CE,"Collector emitter voltage in V is");

```

Scilab code Exa 5.11.5 Collector current

```

1 //Exa 5.11.5
2 clc;
3 clear;
4 close;
5 // Given data
6 bita = 100;
7 I_CBO = 4; // in A
8 I_B = 40; // in A
9 I_C = (bita * I_B) + ((1+bita) * I_CBO); // in A
10 I_C = I_C * 10^-3; // in msA
11 disp(I_C,"The collector current in mA is");

```

Scilab code Exa 5.11.6 Current gain

```
1 // Exa 5.11.6
2 clc;
3 clear;
4 close;
5 // Given data
6 del_IC = 1 * 10^-3; // in A
7 del_IB = 10 * 10^-6; // in A
8 CurrentGain= del_IC/del_IB;
9 disp(CurrentGain,"The current gain is");
10 del_IC= del_IC*10^3; // in mA
11 del_IB= del_IB*10^6; // in A
12 I_B=0:0.1:50; // in A
13 I_C= I_B/del_IB+del_IC; // in mA
14 plot(I_B,I_C)
15 xlabel("Base current in A");
16 ylabel("Collector current in mA")
17 title("Transfer Characteristics")
18 disp("Transfer Characteristics is shown in figure")
```

Scilab code Exa 5.11.7 AlphaDC and betaDC

```
1 //Exa 5.11.7
2 clc;
3 clear;
4 close;
5 //Given data
6 I_CEO = 21; // in A
7 I_CBO = 1.1; // in A
8 beta_dc = (I_CEO/I_CBO) - 1;
9 disp(beta_dc,"Value of beta_dc is");
```

```
10 alpha_dc = beta_dc/(1 + beta_dc);  
11 disp(alpha_dc , "The value of alpha_dc is");
```

Scilab code Exa 5.14.1 AlphaDc and emitter current

```
1 // Exa 5.14.1  
2 clc;  
3 clear;  
4 close;  
5 // Given data  
6 I_CBO = 3; //in A  
7 I_CBO= I_CBO*10^-3; // in mA  
8 I_C= 15; // in mA  
9 // But it is given that I_C= 99.5% of I_E , SO  
10 I_E= I_C/99.5*100; // in mA  
11 alpha_dc= I_C/I_E;  
12 disp(alpha_dc , "The value of alpha_dc is : ")  
13 disp(I_E , "The value of I_E in mA is : ")
```

Scilab code Exa 5.14.2 Collector and base current

```
1 //Exa 5.14.2  
2 clc;  
3 clear;  
4 close;  
5 //Given data  
6 alpha_dc = 0.99;  
7 I_CBO = 10; // in A  
8 I_CBO= I_CBO*10^-6; // in A  
9 I_E = 10; // in mA  
10 I_E= I_E*10^-3; // in A  
11 I_C = (alpha_dc * I_E) + I_CBO; // in A  
12 disp(I_C*10^3 , "The value of I_C in mA is");
```

```
13 I_B = I_E - I_C; // in A
14 I_B = I_B * 10^6; // in A
15 disp(I_B,"The value of I_B in A is");
```

Scilab code Exa 5.14.3 Base current

```
1 // Exa 5.14.3
2 clc;
3 clear;
4 close;
5 format('v',9)
6 // Given data
7 alpha_dc = 0.99;
8 I_C = 6; // in mA
9 I_C= I_C*10^-3; // in A
10 I_CBO = 15; // in A
11 I_CBO= I_CBO*10^-6; // in A
12 I_E = (I_C - I_CBO)/alpha_dc; // in A
13 I_B = I_E - I_C; // in A
14 I_B= I_B*10^6; // in A
15 I_B= round(I_B)
16 disp(I_B,"The value of I_B in A is");
```

Scilab code Exa 5.14.5 Emitter current

```
1 //Exa 5.14.5
2 clc;
3 clear;
4 close;
5 // Given data
6 alpha_dc = 0.98;
7 I_CBO = 12; // in A
8 I_CBO = I_CBO * 10^-6; // in A
```

```

9 I_B = 120; // in A
10 I_B = I_B * 10^-6; // in A
11 beta_dc = alpha_dc/(1-alpha_dc);
12 I_E = ((1 + beta_dc) * I_B) + ((1 + beta_dc) * I_CBO
    ); // in A
13 I_E = I_E * 10^3; // in mA
14 disp(I_E,"The value of I_E in mA is");

```

Scilab code Exa 5.14.6 Region of operation of Si transistor

```

1 //Exa 5.14.6
2 clc;
3 clear;
4 close;
5 // Given data
6 bita= 100;
7 V_BEsat= 0.8; // in V
8 V_CEsat= 0.2; // in V
9 V_BEact= 0.7; // in V
10 V_CC = 10; // in V
11 V_BB=5; // in V
12 R_E = 2; // in k
13 R_C = 3; // in k
14 R_B= 50; // in k
15 // Applying KVL to collector loop
16 // V_CC= I_Csat*R_C +V_CEsat +I_E*R_E and I_E=
    I_Csat+I_B , So
17 //I_B= ((V_CC-V_CEsat)-(R_C+R_E)*I_Csat)/R_E;
    (i)
18 // Applying KVL to base loop
19 // V_BB-I_B*R_B -V_BEsat-I_E*R_E =0 and I_E= I_Csat+
    I_B , So
20 //V_BB-V_BEsat= R_E*I_Csat + (R_B+R_E)*I_B
    (ii)
21 // From eq (i) and (ii)

```

```

22 I_B = ((V_BB-V_BEsat)*5- (V_CC-V_CEsat)*2) / ((R_B+
    R_E)*5 - R_E*2) ;// in mA
23 I_Csat= ((V_CC-V_CEsat)-R_E*I_B)/(R_C+R_E); // in mA
24 I_Bmin= I_Csat/bita; // in mA
25 if I_B<I_Bmin then
26     disp("Since the value of I_B ("+string(I_B*10^3)
        +" A ) is less than the value of I_Bmin ("+
        string(I_Bmin*10^3)+" A )");
27     disp("So the transistor is not in the saturation
        region. But it is conducting hence it can
        not be in cutoff.");
28     disp("Therefore the transistor is in the active
        region")
29 end

```

Scilab code Exa 5.14.7 IB IC and VCE

```

1 //Exa 5.14.7
2 clc;
3 clear;
4 close;
5 // Given data
6 bita= 100;
7 V_BEsat= 0.8; // in V
8 V_CEsat= 0.2; // in V
9 V_BEact= 0.7; // in V
10 V_CC = 10; // in V
11 V_BB=5; // in V
12 R_E = 2; // in k
13 R_C = 3; // in k
14 R_B= 50; // in k
15 // Applying KVL to input loop
16 // V_BB= I_B*R_B+(1+bita)*I_B*R_E+V_BEact or
17 I_B= (V_BB-V_BEact)/(R_B+(1+bita)*R_E); // in mA
18 I_C= bita*I_B; // in mA

```

```

19 // Applying KVL to collector circuit
20 // V_CC= I_Csat*R_C +V_CEsat +(I_C+I_B)*R_E
21 V_CEact= V_CC-I_B*R_E-I_C*(R_C+R_E); // in V
22 disp(I_B*10^3,"The value of I_B in A is : ")
23 disp(I_C,"The value of I_C in mA is : ")
24 disp(V_CEact,"The value of V_CE in volts is : ")

```

Scilab code Exa 5.14.8 Region of operation of Value of IB and IC

```

1 //Exa 5.14.8
2 clc;
3 clear;
4 close;
5 //Given data
6 bita = 100;
7 V_CEsat = 0.2; // in V
8 R_B = 150; // in kohm
9 R_C = 2; // in kohm
10 V_CC = 10; // in V
11 V_BEsat = 0.8; // in V
12 I_B = (V_CC - V_BEsat)/R_B; // in mA
13 I_C = (V_CC - V_CEsat)/R_C; // in mA
14 I_Bmin = I_C/bita; // in mA
15 if I_B>I_Bmin then
16     disp("Since the value of I_B ("+string(I_B*10^3)
17         +" A ) is greater than the value of I_Bmin ("+
18         +string(I_Bmin*10^3)+" A )");
17     disp("So the transistor is in the saturation
region .")
18 end

```

Scilab code Exa 5.14.9 Value of VBB

```

1 //Exa 5.14.9
2 clc;
3 clear;
4 close;
5 //Given data
6 bita = 100;
7 V_CE = 0.2; //in V
8 V_BE = 0.8; // in V
9 R_C= 500; // in
10 R_B= 44*10^3; // in
11 R_E= 1*10^3; // in
12 V_CC= 15; // in V
13 V_GE= -15; // in V
14 // Applying KVL to collector circuit
15 // V_CC-V_GE - I_Csat*R_C-V_CE-I_E*R_E=0, but I_Csat
   = bita*I_Bmin and I_E= 1+bita
16 I_Bmin= (V_CC-V_GE-V_CE)/(R_C*bita+(1+bita)*R_E); //
   in A
17 // Applying KVL to the base emitter circuit
18 // V_BB-I_Bmin*R_B-V_BE-I_E*R_E + V_CC=0
19 V_BB= I_Bmin*R_B + V_BE + (1+bita)*I_Bmin*R_E-V_CC;
   // in V
20 disp(I_Bmin*10^3,"The value of I_B(min) in mA is : ")
21 disp(V_BB,"The value of V_BB in volts is : ")

```

Scilab code Exa 5.14.10 Minimum value of RC required

```

1 // Exa 5.14.10
2 clc;
3 clear;
4 close;
5 // Given data
6 V_ECsat= 0.2; // in V
7 V_CC= 10; // in V

```

```

8 V_EBsat= 0.8; // in V
9
10 // Part (i)
11 bita= 100;
12 R_B= 220; // in k
13 // Applying KVL to collector circuit , V_CC= V_EC+
    ICRC
14 ICRC= V_CC-V_ECsat; // in V
15 // Applying KVL to input loop , V_CC= V_EBsat+I_B*R_B
    (i)
16 I_B= (V_CC-V_EBsat)/R_B; // in mA
17 I_C= bita*I_B; // in mA
18 R_Cmin= ICRC/I_C; // in k
19 disp(R_Cmin,"The minimum value of R_C in k is : "
    )
20 // Part (ii)
21 R_C= 1.2; // in k
22 I_Csat= ICRC/R_C; // in mA
23 I_B= I_Csat/bita; // in mA
24 // From eq (i)
25 R_B= (V_CC-V_EBsat)/I_B; // in k
26 disp(R_B,"The maximum value of R_B in k is : ")

```

Scilab code Exa 5.14.11 Value of RE

```

1 //Exa 5.14.11
2 clc;
3 clear;
4 close;
5 // Given data
6 bita= 100;
7 V_BEsat= 0.8; // in V
8 V_CEsat= 0.2; // in V
9 V_BEact= 0.7; // in V
10 V_CC = 10; // in V

```

```

11 R_E = 1; // in k
12 R_C = 2; // in k
13 R_B= 100; // in k
14 bita=100;
15 alpha= bita/(1+bita);
16 // Applying KVL to collector circuit
17 // V_CC= I_Csat*R_C +V_CE +R_E*I_E
18 // but I_E= alpha*I_Csat
19 I_Csat= (V_CC-V_CEsat)/(R_C+R_E*alpha); // in mA
20 I_Bmin= I_Csat/bita; // in mA
21 // Applying KVL to base loop
22 // V_CC= I_B*R_B +V_BEsat +I_E*R_E
23 // but I_E= I_Csat+I_B
24 I_B= (V_CC-V_BEsat-I_Csat*R_E)/(R_B+R_E); // in mA
25 disp(I_B*10^3,"The value of I_B in A is : ")
26 disp(I_Bmin*10^3,"The minimum value of I_B in A is
: ")
27 if I_B>I_Bmin then
28     disp("Since the value of I_B is greater than the
value of I_Bmin , ")
29     disp("Hence the transistor is in saturation .")
30 end
31 I_E= (1+bita)*I_Bmin; // in mA
32 R_E= (V_CC-V_BEact-I_Bmin*R_B)/I_E; // in k
33 disp(R_E,"The value of R_E in k is : ")
34 disp("So R_E should be greater than this value in
order to bring the transistor just out of
saturation ")

```

Scilab code Exa 5.14.12 Collector voltage

```

1 // Exa 5.14.12
2 clc;
3 clear;
4 close;

```

```

5 // Given data
6 V_CC = 9; // in V
7 V_BE = 0.8; // in V
8 V_CE = 0.2; // in V
9 R_B = 50; // in k
10 R_C=2; // in k
11 R_E = 1; // in k
12 bita=70;
13 // Applying KVL to input loop , V_CC= I_B*R_B +V_BE +
   I_E*R_E
14 // V_CC- V_BE= (R_B+R_E)*I_B + R_E*I_C ( i )
15 // Applying KVL to output loop , V_CC= R_C*I_C +V_CE
   +I_C*R_E +I_B*R_E
16 //I_B = ((V_CC- V_CE)-(R_C+R_E)*I_C)/R_E ( ii
   )
17 // From eq ( i ) and ( ii )
18 I_C= ((V_CC- V_BE)-(R_B+R_E)*(V_CC- V_CE)/R_E
   /(1-(R_B+R_E)*(R_C+R_E)); // in mA
19 I_B = ((V_CC- V_CE)-(R_C+R_E)*I_C)/R_E // in mA
20 I_Bmin= I_C/bita; // in mA
21 if I_B>I_Bmin then
22     disp("Since the value of I_B ("+string(I_B)+" mA
           ) is greater than the value of I_Bmin ("+
           string(I_Bmin)+" mA")
23     disp("So the transistor is in saturation ")
24 end
25 V_C= V_CC-I_C*R_C; // in V
26 disp(V_C,"The value of collector voltage in volts is
   : ")
27 bita= I_C/I_B;
28 disp(bita,"The minimum value of bita that will
   change the state of the transistor is : ")

```

Chapter 6

Field Effect Transistor

Scilab code Exa 6.9.1 Pinch off voltage

```
1 //Exa 6.9.1
2 clc;
3 clear;
4 close;
5 // Given data
6 q = 1.6 * 10^-19; // in C
7 N_D = 10^15; // in electrons/cm^3
8 N_D = N_D * 10^6; // in electrons/m^3
9 epsilon_r = 12;
10 epsilon_o = (36 * %pi * 10^9)^-1;
11 epsilon = epsilon_o * epsilon_r;
12 a = 3 * 10^-4; // in cm
13 a = a * 10^-2; // in m
14 V_P = (q * N_D * a^2)/( 2 * epsilon); // in V
15 disp(V_P,"The Pinch off voltage in V is");
16 // V_GS = V_P * (1-(b/a))^2
17 b = (1-0.707) *a; // in m
18 disp(b*10^6,"The value of b in m is : ")
19 disp("Hence the channel width has been reduced to
      about one third of its value for V_GS = 0"); //
20 // Note : The unit of b in the book is wrong since
```

the value of b is calculated in m .

Scilab code Exa 6.9.2 Value of VGS

```
1 // Exa 6.9.2
2 clc;
3 clear;
4 close;
5 // Given data
6 I_DSS = 8; // in mA
7 V_P = -4; // in V
8 I_D = 3; // in mA
9 V_GS = V_P * (1 - sqrt(I_D/I_DSS)); // in V
10 disp(V_GS,"The value of V_GS in V is");
11 V_DS = V_GS - V_P; // in V
12 disp(V_DS,"The value of V_DS in V is");
```

Scilab code Exa 6.9.3 Drain current

```
1 // Exa 6.9.3
2 clc;
3 clear;
4 close;
5 // Given data
6 V_P = -4; // in V
7 I_DSS = 9; // in mA
8 I_DSS = I_DSS * 10^-3; // in A
9 V_GS = -2; // in V
10 I_D = I_DSS * ((1 - (V_GS/V_P))^2); // in A
11 disp(I_D*10^3,"The drain current in mA is ");
```

Scilab code Exa 6.9.4 Transconductance

```
1 // Exa 6.9.4
2 clc;
3 clear;
4 close;
5 // Given data
6 I_DSS = 12; // in mA
7 I_DSS = I_DSS * 10^-3; // in A
8 V_P = -(6); // in V
9 V_GS = -(1); // in V
10 g_mo = (-2 * I_DSS)/V_P; // in A/V
11 g_m = g_mo * (1 - (V_GS/V_P)); // in S
12 disp(g_m*10^3,"The value of transconductance in mS
is");
```

Scilab code Exa 6.9.5 Value of transconductance and drain current

```
1 //Exa 6.9.5
2 clc;
3 clear;
4 close;
5 // Given data
6 I_DSS = 10; // in mA
7 I_DSS = I_DSS * 10^-3; // in A
8 V_P = -(5); // in V
9 V_GS = -(2.5); // in V
10 g_m = ((-2 * I_DSS)/V_P) * (1 - (V_GS/V_P)); // in S
11 g_m = g_m * 10^3; // in mS
12 disp(g_m,"The Transconductance in mS is");
13 I_D = I_DSS * ((1 - (V_GS/V_P))^2); // in A
14 disp(I_D*10^3,"The drain current in mA is");
```

Chapter 7

Optoelectronic Devices

Scilab code Exa 7.6.1 Component value

```
1 // Exa 7.6.1
2 clc;
3 clear;
4 close;
5 // Given data
6 O_V = 5; // output voltage in V
7 V_D = 1.5; // voltage drop in V
8 R = (O_V - V_D)/O_V;
9 R = R * 10^3; // in ohm
10 disp(R,"The resistance value in ohm is");
11 disp("As this is not standard value, use R=680
      which is a standard value")
```

Scilab code Exa 7.23.1 Open circuit voltage

```
1 // Exa 7.23.1
2 clc;
3 clear;
```

```

4 close;
5 // Given data
6 N_A = 7.5*10^24; // in atoms/m^3
7 N_D = 1.5*10^22; // in atoms/m^3
8 I_lembda = 12.5*10^-3; // in A/cm^2
9 D_e = 25*10^-4; // in m^2/s
10 D_h = 1*10^-3; // in m^2/s
11 Torque_eo = 500; // in ns
12 Torque_ho = 100; // in ns
13 n_i = 1.5*10^16; // in /m^3
14 e = 1.6*10^-19;
15 P_C = 12.5; // in mA/cm^2
16 L_e = sqrt(D_e*Torque_ho*10^-9); // in m
17 L_e = L_e * 10^6; // in m
18 L_h = sqrt(D_h*Torque_ho*10^-9); // in m
19 L_h = L_h * 10^6; // in m
20 J_s = e*((n_i)^2)*( (D_e/(L_e*10^-6*N_A)) + (D_h/(L_h*10^-6*N_D)) ); // in A/m^2
21 J_s = J_s * 10^-4; // in A/cm^2
22 V_T = 26; // in mV
23 V_OC = V_T*log( 1+(I_lembda/J_s) ); // in mV
24 V_OC = V_OC * 10^-3; // in V
25 disp(V_OC,"Open circuit voltage in V is");

```

Scilab code Exa 7.23.2 Value of photocurrent density

```

1 // Exa 7.23.2
2 clc;
3 clear;
4 close;
5 // Given data
6 Phi_o = 1*10^21; // in m^-2s^-1
7 Alpha = 1*10^5; // in m^-1
8 W = 25; // in m
9 W = W * 10^-6; // in m

```

```
10 e = 1.6*10^-19; // in C
11 G_L1 = Alpha*Phi_o; // in m^-3s^-1
12 G_L2 = Alpha*Phi_o*%e^(-Alpha*W); // in m^-3s^-1
13 J_L = e*Phi_o*(1-%e^(-Alpha*W)); // in A/m^2
14 J_L = J_L * 10^-1; // in mA/cm^2
15 disp(J_L,"Photo current density in mA/cm^2 is");
```

Chapter 8

Negative Conductance Micro Devices

Scilab code Exa 8.13.1 Value of the anode current

```
1 // Exa 8.13.1
2 clc;
3 clear;
4 close;
5 // Given data
6 R= 10; // in k
7 R= R*10^3; // in
8 // Part (i)
9 V=300; // in V
10 I_A= V/R; // in A
11 disp("Part (i) : For 300 V voltage : ")
12 disp(I_A*10^3,"The anode current in mA is : ");
13 // Part (ii)
14 V=100; // in V
15 I_A= V/R; // in A
16 disp("Part (ii) : For 100 V voltage : ")
17 disp(I_A*10^3,"The anode current in mA is : ");
```

Scilab code Exa 8.14.1 Value of the peak reverse recovery current

```
1 // Exa 8.14.1
2 clc;
3 clear;
4 close;
5 // Given data
6 t_rr = 10; // in s
7 Q_rr = 150; // in c
8 I_rr = (2*Q_rr)/t_rr; // in A
9 disp(I_rr,"The peak reverse recovery current in A is
");
```
