

Scilab Textbook Companion for
A Heat Transfer Text Book
by J. H. Lienhard, IV And J. H. Lienhard, V¹

Created by
Apar Tiwari
B-Tech part 2
Chemical Engineering
IT BHU
College Teacher
Mrs. V.l. Yadav
Cross-Checked by

July 31, 2019

¹Funded by a grant from the National Mission on Education through ICT, <http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab codes written in it can be downloaded from the "Textbook Companion Project" section at the website <http://scilab.in>

Book Description

Title: A Heat Transfer Text Book

Author: J. H. Lienhard, IV And J. H. Lienhard, V

Publisher: Phlogiston Press, U.S.A.

Edition: 3

Year: 2008

ISBN: 978097138352

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes	4
1 Introduction	5
2 Heat conduction concepts and heat transfer coefficient	10
3 Heat Exchanger Design	16
4 Analysis of Heat Conduction	20
5 Transient and Multidimensional Heat Conduction	25
6 Laminar and Turbulent Boundary Layers	34
7 Forced Convection in Configuration Systems	43
8 natural Convection in single phase fluids and during film condensation	51
9 Heat transfer in boiling and other phase configurations	58
10 thermal radiation heat transfer	67
11 An Introduction to mass Transfer	78

List of Scilab Codes

Exa 1.1	heat flux and heat transfer rate	5
Exa 1.2	Temperature Distribution	6
Exa 1.3	heat transfer coefficient calculation	7
Exa 1.4	response of thermocouple	7
Exa 1.5	Temperature of thermocouple	8
Exa 1.6	Temperature of thermocouple	9
Exa 2.3	steady flux	10
Exa 2.4	thickness calculation	11
Exa 2.7	Critical radius of insulation	11
Exa 2.8	Resistor temperature calculation	12
Exa 2.9	time of cooling of resistor	13
Exa 2.10	heat transfer coefficient calculation	14
Exa 2.12	redesign of siding	14
Exa 2.13	fouling calculation	15
Exa 3.3	heat transfer coefficient calculation	16
Exa 3.4	heat exchanger area	17
Exa 3.5	heat transfer temperature	17
Exa 3.6	area calculation	18
Exa 4.8	Comparison of tip temperatures	20
Exa 4.9	error calculation in heat flux	21
Exa 4.10	Resistor temperature calculation	22
Exa 4.11	Heat Loss Calculation	23
Exa 5.2	temperature and heat calculation	25
Exa 5.3	temperature fluctuation	26
Exa 5.4	Maximum Time Calculation	27
Exa 5.5	Time Calculation	28
Exa 5.7	depth calculation	29
Exa 5.8	temperature calculation	30

Exa 5.9	Shape Factor Calculation	30
Exa 5.11	Thermal Conductivity	31
Exa 5.12	temperature calculation	32
Exa 5.13	Mean Temperature calculation	33
Exa 6.2	boundary layer thickness calculation	34
Exa 6.3	shear Stress and friction coefficient	35
Exa 6.4	Average Heat Flux	36
Exa 6.5	Average Heat Transfer coefficient	37
Exa 6.6	Average temperature calculation	38
Exa 6.8	Drag Force calculation	39
Exa 6.9	heat transfer coefficient calculation	39
Exa 6.10	Average temperature calculation	41
Exa 7.1	depth calculation	43
Exa 7.2	power input and wall temperature	44
Exa 7.3	friction factor calculation	45
Exa 7.4	friction factor calculation	46
Exa 7.5	temperature calculation	47
Exa 7.6	change in bulk temperature	48
Exa 7.7	Air speed calculation	49
Exa 8.1	heat transfer coefficient and heat flux calculation	51
Exa 8.3	heat transfer coefficient varification	52
Exa 8.4	Heat flux variation	53
Exa 8.5	Average surface temperature calculation	55
Exa 8.6	heat transfer calculation	56
Exa 9.1	Size estimation	58
Exa 9.2	surface factor calculation	59
Exa 9.3	steam velocity estimation	60
Exa 9.4	maximum spacing calculation	60
Exa 9.5	peak heat flux calculation	61
Exa 9.6	maximum heat flux	62
Exa 9.7	heat removal rate calculation	62
Exa 9.8	minimum heat flux	64
Exa 9.9	wall temperature calculation	64
Exa 10.1	net heat transfer calculation	67
Exa 10.2	net heat transfer calculation	69
Exa 10.3	view factor calculation	69
Exa 10.4	view factor calculation	70

Exa 10.8	heat gain rate and temperature of the shield	71
Exa 10.9	net heat transfer calculation	72
Exa 10.10	heat transfer rate calculation	74
Exa 10.11	net heat radiation	75
Exa 10.12	root temperature calculation	76
Exa 11.1	mol fraction and pressure density calculation	78
Exa 11.2	mass and mole flux calculation	79
Exa 11.3	diffusivity calculation	81
Exa 11.4	transport properties calculation	82
Exa 11.5	mass fraction calculation	83
Exa 11.6	mass fraction calculation	84
Exa 11.10	average rate of naphthalene loss	84
Exa 11.11	average concentration of helium	86
Exa 11.14	concentration distribution	87
Exa 11.15	rate of evaporation	88
Exa 11.16	mass transfer coefficient calculation	89

Chapter 1

Introduction

Scilab code Exa 1.1 heat flux and heat transfer rate

```
1
2 clear;
3 clc;
4
5 printf("\t Example 1.1\n");
6
7 k=35; //Thermal Conductivity , W/m*K
8 T1=110; // Temperature of front
9 T2=50; // Temperature of back ,C
10 A=0.4; //area of slab ,m^2
11 x=0.03; //Thickness of slab ,m
12
13 q=-k*(T2-T1)/(1000*x); //formula for heat flux
14 printf("\t heat flux is: %.0f KW/m^2\n",q);
15
16 Q=q*A; //formula for heat transfer rate
17 printf("\t heat transfer rate is: %.0f KW\n",Q);
18
19 //End
```

Scilab code Exa 1.2 Temperature Distribution

```
1
2 clear;
3 clc;
4 printf("\tExample 1.2\n");
5 x=poly([0], 'x');
6 k1=372; // Thermal Conductivity of slab ,W/m*K
7 x1=0.003; // Thickness of slab ,m
8 x2=0.002; // Thickness of steel ,m
9 k2=17; // Thermal Conductivity of steel ,W/m*K
10 T1=400; // Temperature on one side ,C
11 T2=100; //Temperature on other side ,C
12
13 Tcu=roots(x+2*x*(k1/x1)*(x2/k2)-(400-100));
14
15 //q=k1*(Tcu/x1)=k2*(Tss/x2);
16
17 Tss = Tcu*(k1/x1)*(x2/k2); // formula for
    temperature gradient in steel side
18
19 Tcul=T1-Tss;
20 Tcur=T2+Tss;
21 printf("\t temperature on left copper side is : %.0f
    C\n",Tcul);
22 printf("\t Temperature on right copper side is : %
    .0f C\n",Tcur);
23 q=k2*Tss/(1000*x2); // formula for heat conducted
24 printf("\t heat conducted through the wall is : %.0f
    W\n",q);
25 printf("\t our initial approximation was accurate
    within a few percent.");
26 //End
```

Scilab code Exa 1.3 heat transfer coefficient calculation

```
1
2 clear;
3 clc;
4 printf("\t example 1.3\n");
5 q1=6000; //Heat flux , W*m^-2
6 T1=120; // Heater Temperature , C
7 T2=70; //final Temperature of Heater
8 q2=2000; // final heat flux
9 h=q1/(T1-T2); // formula for average heat transfer
   coefficient
10 printf("\t Average Heat transfer coefficient is:%.0f
   W/(m^2*K)\n",h);
11
12 Tnew=T2 + q2/h; //formula for new Heater temperature
13 printf("\t new Heater Temperature is :%.2f C\n",Tnew)
   ;
14 //End
```

Scilab code Exa 1.4 response of thermocouple

```
1
2 clear;
3 clc;
4 printf("\t Example 1.4\n");
5 h=250; //Heat Transfer Coefficient , W/(m^2*K)
6 k=45; // Thermal Conductivity , W/(m*K)
7 c=0.18; //Heat Capacity , kJ/(kg*K)
8 a=9300; //density , kg/m^3
9 T1=200; //temperature , C
10 D=0.001; //diameter of bead,
```

```

11 t1 =0:0.1:5;
12 T=200-180*exp(-t1/((a*c*D*1e3)/(6*h)));
13 plot(t1,T);
14 xtitle("Thermocouple response to a hot gas flow",
        time,t1 sec","temperature,T C");
15 Bi = h*(0.001/2)/45; //biot no.
16 printf("The value of Biot no for this thermocouple
        is %f",Bi);
17 printf("\n Bi is <0.1 and hence the thermocouple
        could be considered as a lumped heat capacity
        system and the assumption taken is valid.\n");
18 //End

```

Scilab code Exa 1.5 Temperature of thermocouple

```

1
2 clear;
3 clc;
4
5 printf("\t Example 1.5\n");
6 x=poly([0], 'x');
7 T1=293; //Temperature of air around thermocouple, K
8 T2=373; //Wall temperature, K
9 h=75; // Average Heat Transfer Coefficient, W/(m^2*K
    )
10 s=5.67*10^-8; // stefan Boltzman constant, W/(m^2*K
    ^4)
11 x=roots(h*(x-T1)+s*(x^4-T2^4));
12 y=x(4)-273;
13 printf("\t thermocouple Temperature is : %.1f C\n",y
    );
14 //end

```

Scilab code Exa 1.6 Temperature of thermocouple

```
1
2 clear;
3 clc;
4
5 printf("\t example 1.6\n");
6 x=poly([0], 'x');
7 e=0.4; //emissivity
8 T1=293; //Temperature of air around Thermocouple, K
9 T2=373; // wall Temperature, K
10 h=75; // Average Heat Transfer Coefficient, W/(m^2*K
    )
11 s=5.67*10^-8; // stefan Boltzman constant, W/(m^2*K
    ^4)
12 x=roots((x-T1)*h+e*s*(x^4-T2^4));
13 y=x(4)-273;
14 printf("\t Thermocouple Temperature is : %.1f C\n",y
    );
15 //End
```

Chapter 2

Heat conduction concepts and heat transfer coefficient

Scilab code Exa 2.3 steady flux

```
1
2 clear;
3 clc;
4
5 printf("\t Example 2.3\n");
6
7 l=1; // tube length , m
8 m=0.01; // mass fraction
9 D12=2.84*10^-5; // diffusivity , m^2/s
10 a=1.18; // density, kg/m^3
11
12 J=a*D12*m/l;
13 //steady state flux of water from one side to the
    other ,kg/(m^2*s)
14 printf("\t steady flux of water is %.2e kg/(m^2*s)",
    J);
15 //end
```

Scilab code Exa 2.4 thickness calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 2.4\n");
6
7 k=18; // thermal conductivity of resistor , W/(m*K)
8 A=1; //area of slab surface , m^2
9 hc=3000; //convective heat transfer coefficient ,W
    /(m^2*K)
10 //Req=1/A*(2L/k+1/hc), for contact resistances to
    be neglected 2L/18 must be very greater than the
    1/3000
11 printf("thickness of slabs for contact resistances
    to be neglected is very greater than 0.003 m. if
    length is 3 cm, the error is about 10 percent.");
12 //end
```

Scilab code Exa 2.7 Critical radius of insulation

```
1
2 clear;
3 clc;
4
5 printf("\t example 2.7\n");
6
7 h=20; //convective heat transfer coefficient , W/(m
    ^2*K)
8 k=0.074; //thermal conductivity , J/(m*K)
```

```

9 Ro=k/h; // formula for critical thickness of
  insulation
10 printf("\t critical thickness of insulation is : %.4
  f m\n",Ro);
11 printf("\t insulation will not even start to do any
  good until ratio of outer radius and inner radius
  is 2.32 or outer radius is 0.0058 m.")
12 //End

```

Scilab code Exa 2.8 Resistor temperature calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 2.8\n");
6
7 P=0.1; //dissipating power,W
8 D=0.0036; //outer diameter of cylinder , m
9 l=0.01; //length of cylinder , m
10 T=308; // temperature of air in the cabinet ,K
11 h=13; // convection coefficient , W/(m^2*K)
12 e=0.9;
13 A=1.33*10^-4; //area of resistor 's surface , m^2
14
15 Tm=(T+323)/2; // resistor 's temperature at 50 K
16 Hr=4*5.67*10^-8*Tm^3*e; // radiative heat transfer
  coefficient ,W/(m^2*K)
17
18
19 Rteq=1/(A*(Hr+h));
20 Tres=T+P*Rteq;
21 //we guessed a resistor 's temperature of 323K in
  finding Hr,recomputing with this higher
  temperature ,we have Tm=327K and Hr=7.17W/(m^2*K).

```

if we repeat the rest of calculations, we get a new value $T_{res}=345.3K$, since the use of h_r is an approximation, we should check its applicability: $1/4*((345.3-308)/327)^2=0.00325 \ll 1$, in this case, the approximation is a very good one

```

22 Tr=Tres-273.06;
23 printf("\t temperature of resistor is : %.2f K\n",
    Tr);
24 printf("\t since 1/4*(temperature difference/mean
    temperature)= 1/4*((72.3-35)/327)^2=0.00325 << 1,
    in this case, the approximation is a very good
    one.");
25 //End

```

Scilab code Exa 2.9 time of cooling of resistor

```

1
2 clear;
3 clc;
4
5 printf("\t Example 2.9\n");
6
7 k=10; // thermal conductivity of resistor, W/(m*K)
8 a=2000; //density of resistor, kg/m^3
9 l=0.01; //length of cylinder, m
10 A=1.33*10^-4; //area of resistor's surface, m^2
11 T1=308; // temperature of air in the cabinet, K
12 Cp=700; //heat capacity of resistor, J/kg/K
13 Heff=18.44; // the effective heat transfer
    coefficient of parallel convection and radiation
    process, W/(m^2*K)
14 Bi=Heff*(0.0036/2)/k;
15 T=a*Cp*3.14*1*(0.0036)^2/(4*Heff*A); //since from
    previous example,  $T_o=72.3C$ , we have  $T_{res}=T_1+(T_o-T_1)
    *exp(-t/T)$ ,  $T_{res}=308+(37.3)*exp(-t/T)$ . 95% of the

```



```

    temperature drop has occurred when  $t=T*3=174s$ .
16 t=3*T;
17 printf("\t time for 95 percent cooling of resistor
    is : %.0f s\n",t);
18 //End

```

Scilab code Exa 2.10 heat transfer coefficient calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 2.10\n");
6
7 h1=200; // convective heat transfer coefficient , W/(
    m^2*K)
8 a=1/60000; // 1/a=1/Kal, l=0.001m, Kal=160 W/(m*K)
9 h2=5000; //convective heat transfer coefficient
    during boiling ,W/(m^2*K)
10
11 U=1/(1/h1+a+1/h2)+0.40;
12 printf("\t overall heat transfer coefficient is : %
    .1f W/(m^2*K)\n",U);
13 //end

```

Scilab code Exa 2.12 redesign of siding

```

1 clear;
2 clc;
3
4 printf("\t Example 2.12\n");
5 Rf=0.0005; //fouling resistance ,m^2*K/W
6 U=5; //heat transfer coefficient ,W/(m^2*K)

```

```

7 Ucor=(U*Rf+1)/(U);
8 printf("\t corrected heat transfer coefficient is :
   %.2f W/(m^2*K)\n therefore the fouling is
   entirely irrelevant to domestic heat holds.",
   Ucor);
9 //end

```

Scilab code Exa 2.13 fouling calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 2.13\n");
6 U1=4000; //overall heat transfer coefficient of
   water cooled steam condenser , W/(m^2*K)
7 Rf1=0.0006; // lower limit of fouling resistance of
   water side , m^2*K/W
8 Rf2=0.0020; // upper limit of fouling resistance of
   water side , m^2*K/W
9 U2=U1/(U1*Rf1+1);
10 U3=U1/(U1*Rf2+1);
11 printf("\t upper limit of the corrected overall
   heat transfer coefficient is : %.0f W/(m^2*K)\n",
   U2);
12 printf("\t lower limit of corrected overall
   heattransfer coefficient is : %.0f W/m^2/K, U is
   reduced from 4000 to between 444 and 1176 W/(m^2*
   K),fouling is crucial in this case and
   engineering was in serious error.\n",U3);
13 //end

```

Chapter 3

Heat Exchanger Design

Scilab code Exa 3.3 heat transfer coefficient calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 3.3\n");
6
7 T1=293; // Entering Temperature of Water, K
8 T2=313; //Exit Temperature of water, K
9 m=25/60; //Condensation rate of steam, kg/s
10 T3=333; // Condensation Temperature, K
11 A=12; //area of exchanger, m^2
12 h=2358.7*10^3; //latent heat, J/kg
13
14 U=(m*h)/(A*((T2-T1)/log((T3-T1)/(T3-T2))))+0.6;
15 printf("\t Overall heat transfer coefficient is : %
    .0f W/(m^2*K)\n", U);
16
17 Mh=(m*h)/(4174*(T2-T1));
18 printf("\t required flow of water is : %.2f kg/s\n",
    Mh);
19 //End
```

Scilab code Exa 3.4 heat exchanger area

```
1
2 clear;
3 clc;
4
5 printf("\t Example 3.4\n");
6
7 m=5.795; //flow rate of oil , kg/s
8 T1=454; //Entering Temperature of oil , K
9 T2=311; //Exit Temperature of oil , K
10 T3=305; // Entering Temperature of water , K
11 T4=322; //Exit Temperature of water , K
12 c=2282; //heat capacity , J/(kg*K)
13 U=416; //overall heat transfer coefficient , J/(m^2*
    K*s)
14 F=0.92; // Correction factor for 2 shell and 4 tube-
    pass exchanger ,           since  $R=(T1-T2)/(T4-T3)$ 
    =8.412 >1,  $P=(T4-T3)/(T1-T2)=0.114$ , we can get
    this value of F by using value of  $P =R*0.114$ 
15
16  $A=(m*c*(T1-T2))/(U*F*((T1-T4-T2+T3)/\log((T1-T4)/(T2-
    T3))))$ ;
17 printf("\t area for heat exchanger is : %.1f m^2\n",
    A);
18 //End
```

Scilab code Exa 3.5 heat transfer temperature

```
1
2 clear;
```

```

3  clc;
4
5  printf("\t Example 3.5\n");
6
7  T1=313; //entering temperature of cold water, K
8  T2=423; //Entering temperature of hot water, K
9  Cc=20000; //heat capacity of cold water, W/K
10 Ch=10000; //heat capacity of hot water, W/K
11 A=30; //area, m^2
12 U=500; //overall heat transfer coefficient, w/(m^2*K
    )
13 e=0.596; // no. of transfer units (NTU)=(U*A)/Ch=1.5,
    the effectiveness of heat exchanger e can be
    found by using this value of NTU
14
15 Q=e*Ch*(T2-T1);
16 Q1=Q/1000
17 printf("\t heat transfer is :%.1f KW\n",Q1);
18
19 Texh=T2-Q/Ch;
20 Tn1=Texh-273;
21 printf("\t the exit hot water temperature is :%.2f C\
    n",Tn1);
22
23 Texc=T1+Q/Cc
24 Tn2=Texc-273;
25 printf("\t the exit cold water temperature is : %.2f
    C\n",Tn2);
26
27 //End

```

Scilab code Exa 3.6 area calculation

```

1
2  clear;

```

```

3  clc;
4
5  printf("\t Example 3.6\n");
6
7  T1=313; //entering temperature of cold water, K
8  T2=423; //Entering temperature of hot water, K
9  T3=363; //Exit temperature of hot water, K
10 Cc=20000; //heat capacity of cold water, W/K
11 Ch=10000; //heat capacity of hot water, W/K
12 U=500; //overall heat transfer coefficient, w/(m^2*K
    )
13 T4=T1+(Ch/Cc)*(T2-T3);
14 e=(T2-T3)/(T2-T1);
15
16 NTU=1.15;
17 A1=Ch*(NTU)/U; // since NTU=1.15=U*A/Ch, A can be
    found by using this formula
18 printf("\t area is : %.2f m^2\n",A1);
19
20 //another way to calculate the area is by using log
    mean diameter method
21 LMD=(T2-T1-T3+T4)/log(110/20);
22 A2=Ch*(T2-T3)/(U*LMD);
23 printf("\t area is : %.2f m^2\n",A2);
24 printf("\t there is difference of 1 percent in
    answers which reflects graph reading inaccuracy."
    );
25 // we can see that area calculated is same in above 2
    methods.
26 //End

```

Chapter 4

Analysis of Heat Conduction

Scilab code Exa 4.8 Comparison of tip temperatures

```
1
2 clear;
3 clc;
4
5 printf("\t Example 4.8\n");
6
7 d=0.02; //diameter of alluminium rod ,m
8 k=205; //thermal conductivity of rod ,W/(m.K)
9 l=0.08; //length of rod , m
10 T1=423; //wall temperature , K
11 T2=299; //air temperatutre , K
12 h=120; //convective coefficient , W/(m^2*K)
13
14 mL=(h*(l^2)/(k*d/4))^0.5; // formula for mL=((h*
    Perimeter*l^2)/(k*Area))^0.5
15 Bi=h*l/k
16 a1=(cosh(0)+(Bi/mL)*sinh(0))/(cosh(mL)+(Bi/mL)*sinh(
    mL)); //formula for temperature difference T-
    Ttip
17
18 Ttip1=T2+a1*(T1-T2); // exact tip temperature
```

```

19 Tt1=Ttip1-273;
20 printf("\t the exact tip temperature is : %.2f C\n",
    Tt1);
21
22 a2=(cosh(0)+(Bi/mL)*sinh(0))/(cosh(mL)); //if heat
    transfer from the tip is not considered
23 Ttip2=T2+a2*(T1-T2);
24 Tt2=Ttip2-273;
25 printf("\t approximate tip temperature is : %.2f C\n
    ",Tt2);
26 printf("\t thus the insulated tip approximation is
    adequate for the computation in this case.");
27 //End

```

Scilab code Exa 4.9 error calculation in heat flux

```

1
2 clear;
3 clc;
4
5 printf("\t Example 4.9\n");
6
7 T1=423; //wall temperature, K
8 d=0.02; //diameter of aluminium rod,m
9 k=205; //thermal conductivity of rod,W/(m.K)
10 l=0.08; //length of rod, m
11 T2=299; //air temperatutre, K
12 h=120; //convective coefficient, W/(m^2*K)
13 mL=0.8656;
14 a=h*d/(2*k);
15 mr=mL*(d/(2*l)); // by looking at graph of 1-Qact/Q(
    no temp.depression) vs. mr*tanh(mL), we can find
    out the value of Troot. 1-Qact./Q(no temp.
    depression) = 0.05 so heat flow is reduced by 5
    percent

```



```

16
17 Troot=T1-(T1-T2)*0.05;
18 Tr=Troot-273;
19 printf("\t actual temperature of root is : %.1f C ,
    the correction is modest in this \n",Tr);
20 //end

```

Scilab code Exa 4.10 Resistor temperature calculation

```

1
2
3 clear;
4 clc;
5
6 printf("\t Example 4.10\n");
7
8 T1=308; //air temperature , K
9 Q=0.1; // heat transferred ,W
10 k=16; //thermal conductivity of wires , W/(m*K)
11 d=0.00062; //diameter of wire ,m
12 Heff=23; //convection coefficient , W/(m^2*K)
13 //the wires act actn as very long fins connected to
    resistor hence tanh(mL)=1
14
15 R1=1/(k*Heff*3.14^2*d^(3)/4)^0.5;
16
17 Req=(1/R1+1/R1+7.17*(1.33*10^-4)+13*(1.33*10^-4))
    ^-1; //the 2 thermal resistances are in
    parallel to the thermal resistance for natural
    convection and thermal radiation from the
    resistor 's surface found in previous eg.
18
19 Tres=T1+Q*Req;
20 Trs=Tres-273;
21 printf("\t resistor temperature is : %.2f C or

```

```
    about 10 C lower than before.\n",Trs);  
22 //end
```

Scilab code Exa 4.11 Heat Loss Calculation

```
1  
2 clear;  
3 clc;  
4  
5 printf("\t Example 4.11\n");  
6  
7 D1=0.03; // outer diameter , m  
8 T1=358; //hot water temperature , K  
9 t1=0.0008; //thickness of fins , m  
10 D2=0.08; // diameter of fins , m  
11 t2=0.02; // spacing between fins , m  
12 h1=20; // convection coefficient , W/(m^2*K)  
13 h2=15; //convection coefficient with fins , W/(m^2*K)  
14  
15 To=295; //surrounding temperature , K  
16  
17 Q=3.14*D1*h1*(T1-To); // if fins are not added.  
18 Q1=199 //heat loss without fins ,W/m  
19 printf("\t heat trnsferred without fins is : %.0f W/  
    m\n",Q1);  
20  
21 // we set wall temp.=water temp..since the wall is  
    constantly heated by water , we should not have a  
    root temp. depression problem after the fins are  
    added.hence by looking at the graph , ml(l/  
    Perimeter)^0.5=(h*(D2/2-D1/2)/(125*0.025*t1)) =  
    0.306 , we obtain n(efficiency)=89 percent  
22  
23 Qfin=Q*(t2-t1)/t2 + 0.89*(2*3.14*(D2^(2)/4-D1^(2)/4)  
    )*50*h2*(T1-To)+1.14
```

```
24 printf("\t heat transferred with fins is : %.0f W/m
    or 4.02 times heat loss without fins.\n", Qfin);
25 //end
```

Chapter 5

Transient and Multidimensional Heat Conduction

Scilab code Exa 5.2 temperature and heat calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 5.2\n");
6
7 d1=0.1; // diameter of sphere , m
8 T1=303; // environment temp.,K
9 T2=278; // fridge temp., K
10 h=6; //convection coefficient , W/(m^2*K)
11 k=0.603; //thermal conductivity ,W/(m*K)
12 a=997.6; // density of water , kg/m^3
13 c=4180; //heat capacity , J/(kg*K)
14
15 F=(k/(a*c))*3600/(d1^2)/4;
16 a1=0.85 // Biot no.=1/2.01 therefore we read from
           fig. in upper left hand corner
17 Tcen=a1*(T1-T2)+T2; // temperature of the center of
                       apple after 1 hour
```

```

18 Tc=Tcen-273;
19 printf("\t temperature after an hour is : %.1f C\n",
    Tc);
20
21 a2=(283-T2)/(T1-T2);
22 F1=1.29 //Bi is still 1/2.01, by looking at the
    graph we can find time.
23
24 t=F1*a*c*0.0025/0.603-2;
25 printf("\t time to bring the temp equal to 283k is :
    %.0f s or 6 hr 12 min\n",t);
26 //finally we look up at Bi=1/2.01 and fouling factor
    is 1.29, for spheres heta removal is 43.67 kJ
    per apple.
27 x=43.67; //heat removal for an apple
28 X=12*x; //total heat removal,kJ
29
30 printf("\t total energy removal is :%.0f kJ\n",X);
31 //end

```

Scilab code Exa 5.3 temperature fluctuation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 5.3\n");
6
7 d1=0.001;; //diameter of nichrome, m
8 h=30000; //convection coefficient , W/(m^2*K)
9 T1=373; // wire temperature, K
10
11 //heat is being generated in proportion to product
    of voltage and current, if the boiling action
    removes heat rapidly enough in comparison with

```

```

    the heat capacity of the wire ,the surface
    temperature may well vary.
12
13 Bi=h*d1/2/13.8; // biot number comes ot to be 1.09
    and value of a= w*d1^(2)/4/a1 comes out to be
    27.5. by looking at the chart of cylinders , we
    find that ,      (Tmax-Tav)/(Tav-To)=0.04
14 TF=0.04; // temperature fluctuation of 4 percent is
    not serious and experiment is valid.
15
16 printf("\t the temperature fluctuation is : %.2f
    this fluctuation is probably not serious.it
    therefore appears that the experiment is valid.\
n" , TF);
17 //end

```

Scilab code Exa 5.4 Maximum Time Calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 5.4\n");
6
7 t=0.003; //half thickness of sword, m
8 a=1.5*10^-5;
9
10 Tmax=t^2/(3.64^2*a); //condition for sword to be in
    semi infinite region
11 printf("\t maximum time for sword to be in semi
    infinite region is : %.3f s\n",Tmax);
12 printf("\t thus the quench would be felt at the
    centerline of the sword within only 1/20 s. the
    thermal diffusivity of clay is smaller than that
    of steel by a factor of about 30, so the quench

```

```

    time of coated steel must continue for over 1s
    before the temperature of the steel is affected
    at all, if the clay and sword thickness are
    comparable.”)
13 //end

```

Scilab code Exa 5.5 Time Calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 5.5\n");
6 h=100; //convective heat transfer coefficient , W/(m
        ^2*K)
7 k=0.63; // thermal conductivity ,W/(m*K)
8 //the short exposure to the flame causes only a very
    superficial heating ,so we consider the finger to
    be semi-infinite region.it turns out that the
    burn threshold of human skin ,Tburn is about 65 C.
    h=100 W/(m^2*K) , we shall assume that the
    thermal conductivity of human flesh equals that
    of its major component – water and that the
    thermal diffusivity is equal to the known value
    for beef.
9
10 // a=0.963, BE=h*x/k=0(since x=0 at the surface)
11
12 // b^2=(h^2)*(0.135*10^-6)*t/(k^2)=0.0034*t. On
    solving error function by trial and error method ,
    we get the value of t=0.33 sec.
13
14 w=(1-0.963)*(%pi)^(0.5)/2;
15
16 // thus it would require about 1/3 se to bring the

```

```

    skin to burn point.
17
18 printf("it would require about 1/3 sec to bring the
    skin to burn point");
19
20 //end

```

Scilab code Exa 5.7 depth calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 5.7\n");
6
7 //w=2*3.14 rad/yr , a=w*t=0 at present.first we find
    the depths at which a=0 curve reaches its local
    extrema.(we pick the a=0 curve because it) gives
    the highest temperature at t=0.).tan(o-e)=1 so e
    =3%pi/4, 7%pi/4....and the first minima occurs
    where e=3%pi/4=2.356.
8
9 b=0.139*10^-6; //thermal diffusivity , m^2/s
10
11 x=2.356/(2*3.14/(2*b*365*24*3600))^0.5; //depth of
    digging of earth to find the temperature wave
12
13 printf("\t depth of digging of earth is :%.3f m, if
    we dug in the earth , we would find it growing
    older until it reached a maximum coldness at a
    depth of about 2.8 m.Farther down, it would begin
    to warm up again , but nt much. in midwinter , the
    reverse would be true \n",x);
14
15 //end

```

Scilab code Exa 5.8 temperature calculation

```
1
2 clear;
3 clc;
4
5 printf("Example 5.8\n");
6
7 l=0.08; //distance between metal walls ,m
8 k=0.12; //thermal conductivity of insulating
    material , w/(m*K)
9 l1=0.04; //length of ribs ,m
10 l2=0.14; //projected length of wall ,m
11 T1=40; // temperature of 1st wall ,C
12 T2=0; //temperature of wall , C
13
14 //by looking at the configuration plot , there are
    approximately 5.6 isothermal increments and 6.15
    flow channels.
15
16 Q=2*(6.15/5.6)*k*(T1-T2); //factor of 2 accounts for
    the fact that there are two halves in the
    section .
17
18 T=2.1/5.6*(T1-T2); // by simple proportionality
19
20 printf("\t temperature in the middle of of wall , 2
    cm from a rib is : %.0f C\n",T);
21
22 //end
```

Scilab code Exa 5.9 Shape Factor Calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 5.9\n");
6
7 r=3; // radius ratio of one-quarter section of
      cylinder
8
9 S=%pi/(2*log(r)); // shape factor
10
11 printf("\t shape factor is : %.2f \n the quarter
        cylinder will be pictured for the radius ratio of
        3, but for the different sizes.in both the cases
        it will be 1.43",S);
12 //end

```

Scilab code Exa 5.11 Thermal Conductivity

```

1
2 clear;
3 clc;
4
5 printf("\t Example 5.11\n");
6
7 Q=14; //steady heat transfer ,W
8 D=0.06; //diameter of heat source ,m
9 l=0.3;; // length of source below surface ,m
10 T=308; //temperature of heat source ,K
11 T1=294; //temperature of surface ,K
12
13 k=(Q/(T-T1))*(1-(D/2)/(D*10))/(4*3.14*D/2)+0.025; //
      thermal conductivity of soil
14
15 printf("\t thermal conductivity is : %.3f W/(m*K)\n"

```

```
    ,k);  
16  
17 //end
```

Scilab code Exa 5.12 temperature calculation

```
1  
2 clear;  
3 clc;  
4  
5 printf("\t Example 5.12\n");  
6  
7 l=0.04; // length of square rod, m  
8 T1=373; // temperature of rod, K  
9 T2=293; // temperature of coolant, K  
10 h=800; //convective heat transfer coefficient, W/(m  
    ^2*K)  
11  
12 a1=0.93; // ratio of temperature difference for Fo1  
    =0.565, Bi1=0.2105, (x/l)1=0  
13 a2=0.91; // ratio of temperature difference for Fo2  
    =0.565, Bi2=0.2105, (x/l)2=0.5  
14 a=a1*a2; //ratio of temperature difference at the  
    axial line of interest  
15  
16 T=(T1-T2)*a+T2; //temperature on a line 1 cm. from  
    one side and 2 cm. from the adjoining side after  
    10 sec.  
17 Ta=T-273;  
18  
19 printf("\t temperature is : %.2f C\n",Ta);  
20 //end
```

Scilab code Exa 5.13 Mean Temperature calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 5.13\n");
6
7 T1=373; // temperature of iron rod ,K
8 T2=293; // temperature of coolant ,K
9
10 //Biot no. , Bi1=Bi2=0.2105 ,Fo1=Fo2=0.565
11 a1=0.10;
12 a2=0.10;
13
14 a=a1+a2*(1-a1);
15
16 T=(T1-T2)*(1-a)+T2; //mean temperature ,K
17 Ta=T-273;
18 printf("\t mean temperature is : %.1f C\n",Ta);
19 //end
```

Chapter 6

Laminar and Turbulent Boundary Layers

Scilab code Exa 6.2 boundary layer thickness calculation

```
1
2 clear;
3 clc;
4
5 printf("\t example 6.2\n");
6
7 T1=300; //air temperature ,K
8 v=1.5; //air velocity , m/s
9 t=0.5; //thickness , m
10 u=1.853*10^-5; //dynamic viscosity ,kg/(m*s)
11 v1=1.566*10^-5; // kinematic viscosity , m^2/s
12
13 Rex=v*t/v1; //reynolds no. is low enough to permit
    the use of laminar flow analysis.
14
15 b=4.92*t/(Rex^0.5)*100; // bl thickness , cm
16
17 //in this case b/x=1.124/50=0.0225 so laminar flow
    is valid.
```

```

18
19 v2=0.8604*(v1*v/t)^(0.5);
20 //since v2 grows larger as x grows smaller , the
    condition v2<u is not satisfied very near the
    leading edge.
21
22 printf("\t boundary layer thickness is : %.3f cm\n",
    b);
23 //in this case del/thickness is 0.0225.
24 x=0.8604*(v1*v/t)^0.5; //velocity ,m/s
25 y=x/t;
26 printf("\t since velocity grows larger as thickness
    grows smaller , the condition x<<u is not
    satisfied very near the leading edge. therefore
    the BI approximation themselves breakdown.")
27 //end

```

Scilab code Exa 6.3 shear Stress and friction coefficient

```

1
2 clear;
3 clc;
4
5 printf("\t Example 6.3\n");
6
7 l=0.5; //total length of surface ,m
8 Cf=0.00607; //overall friction coefficient
9 tw=1.183*(2.25)*Cf/2; // wall shear , kg/(m*s^2)
10
11 a=0.5; //ratio of wall shear at x=l and average
    wall shear
12
13 //tw(x)=twavg where 0.664/(x^0.5)=1.328/(47,)893, x
    =1/8 m thus the wall shear stress plummets to
    twavg one fourth of the way from the leading edge

```

```

    and drops only to one half of twavg in the
    remaining 75 percent plate. $x < 600 * 1.566 * 10^{-5}$ 
    /1.5=0.0063 m.
14
15 // preceding analysis should be good over almost 99
    percent of the 0.5 m length of the surface.
16
17 printf("\t overall friction coefficient is : %f\n",
    Cf);
18 printf("\t wall shear is :%f kg/(m*s^2)\n",tw);
19 printf("\t the preceding analysis should be good
    over almost 99 percent of the 0.5m length of the
    surface.")
20 //end

```

Scilab code Exa 6.4 Average Heat Flux

```

1
2 clear;
3 clc;
4
5 printf("\t Example 6.4\n");
6
7 l=0.06; //length of heater , m
8 p=15; // pressure of heater , atm
9 T1=440; //temperature of heater , K
10 v=2; //free stream velocity ,m/s
11 T2=460; // constant temperature of heater , K
12
13 T3=450; //mean temperature of heater , K
14
15 q=2*(0.332)*(0.674/l)*(v*1/(1.72*10^-7))^(0.5)*(T2-
    T1)/1000; // formula for heat flux is  $q=2*(0.664)$ 
    *k/l*(Re0.5)*(T2-T1)
16

```

```
17 printf("\t heat flux is : %.0f kW/m^2\n",q);
18 //end
```

Scilab code Exa 6.5 Average Heat Transfer coefficient

```
1
2 clear;
3 clc;
4
5 printf("\t Example 6.5\n");
6
7 T1=293; //air temperature ,K
8 v=15; //air velocity ,m/s
9 T2=383; // temperature of plate ,K
10 l=0.5; // length of plate ,m
11 w=0.5; //width of plate ,m
12
13 Pr=0.707; // prandtl no.
14 Re1=v*l/(0.0000194); //reynolds no.
15 Nu1=0.664*(Re1)^0.5*Pr^(1/3); // nusset no.
16
17 h1=367.8*(0.02885)/l; // average convection
    coefficient , W/(m^2*K)
18 Q=h1*l^(2)*(T2-T1); // heat transferred ,W
19
20 h2=h1/2 // convection coefficient at trailing , W/(m
    ^2*K)
21 a1=4.92*l/(Re1)^0.5*1000 // hydrodynamic boundary
    layer ,m
22
23 a2=a1/(Pr)^(1/3); //thermal boundary layer ,mm
24
25 printf("\t average heat transfer coefficient is : %
    .1f W/m^2/K\n",h1);
26 printf("\t total heat transferred is %.0f W\n",Q);
```



```

27 printf("\t convection coefficient at trailing is : %
    .1fW/(m^2*K)\n",h2);
28 printf("\t hydrodynamic boundary layer is : %.2f m\n
    ",a1);
29 printf("\t thermal boundary layer is : %.2f mm\n",a2
    );
30
31 // end

```

Scilab code Exa 6.6 Average temperature calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 6.6\n");
6
7 T1=288; // air temperature ,K
8 v=1.8; // air velocity ,m/s
9 l=0.6; // length of panel , m
10 Q=420; // power per unit area , m^2
11 T2=378; // maximum temperature of surface , K
12
13 T3=Q*1/(0.0278)/(0.453*(1*v/(1.794*10^-5))^(0.50)
    *(0.709)^(1/3)); //maximum temperature difference
14
15 Twmax=T1+T3; //Twmax comes out to be 106.5 C, this
    is very close to 105 C,if 105 is at all
    conservative , Q = 420 should be safe.
16
17 T4=0.453/0.6795*T3; //average temperature difference
    ,K
18
19 Twavg=T1+T4; //average wall temperature ,K
20 Twa=Twavg-273;

```

```

21
22 printf("\t average wall temperature is : %.0f C\n",
        Twa);
23 //end

```

Scilab code Exa 6.8 Drag Force calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 6.3\n");
6
7 v=15; //air velocity ,m/s
8 T2=383; // temperature of plate ,K
9 l=0.5; // length of plate ,m
10 w=0.5; //width of plate ,m
11
12 Pr=0.707; // prandtl no.
13 Re1=v*l/(0.0000194); //reynolds no.
14 Nu1=0.664*(Re1)^0.5*Pr^(1/3); // nusset no.
15
16 Cf=2*Nu1/(Re1*Pr^(1/3)); //friction coefficient
17
18 s=Cf*0.5*1.05*225; //drag shear , kg/(m*s^2)
19 f=s*0.5^2-0.000024; //drag force , kg/(m*s^2)
20
21 printf("\t drag force on heat transfer surface is :
        %f N or 0.23 oz.\n",f);
22
23 //end

```

Scilab code Exa 6.9 heat transfer coefficient calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 6.3\n");
6
7 T1=297; // river water temp.,K
8 T2=283; // ocean water temp., K
9 n=5; // no. of knots
10 k=0.5927; // thermal conductivity ,W/(m*K)
11 a=998.8; //density of water , kg/m^3
12 Cp=4187; // heat capacity , J/kg/K
13 Pr=7.66;
14 x=1; //distance from forward edge,m
15
16 T3=(T1+T2)/2; // avg. temp.,K
17 v=1.085*10^-6; // kinematic viscosity , m^2/s
18
19 u=2.572; //velocity of knot,m/s
20
21 Rex=u/v //reynolds no.
22 Cf(x)=0.455/(log(0.06*Rex))^2 // friction
    coefficient
23
24 h=k/x*0.032*(Rex)^(0.8)*Pr^(0.43); // heat transfer
    coefficient ,W/(m^2*K)
25 printf("\t friction coefficient is : %f\n",Cf);
26 printf("\t convective heat transfer coefficient at a
    distance of 1 m fom the forward edge is :%.0f W
    /(m^2*K)\n",h);
27 h1=a*Cp*u*Cf/2/(1+12.8*(7.66^0.68-1)*(Cf/2)^0.5);
    //heat transfer coefficient ,W/(m^2*K)
28 printf("\t heat transfer coefficient by another
    method is :%.0f W/(m^2*K)\n",h1);
29 printf("\t the two values of h differ by about 18
    percent , which is within the uncertainty.");
30
31 //end

```

Scilab code Exa 6.10 Average temperature calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 6.3\n");
6
7 l=2; // length of plate ,m
8 p=1000; // power density ,W/m^2
9 u=10; // air velocity ,m/s
10 T1=290; // wind tunnel temp. ,K
11 p2=1; // pressure ,atm
12 Re = 400000; // reynolds no.
13
14 v=1.578*10^-5; // kinematic viscosity , m^2/s
15 k=0.02623; // thermal conductivity ,W/(m*K)
16 Pr=0.713; // prandtl no.
17 Rel=u*l/v; //reynolds no. at 10 m/s
18
19 Nul=1845; // nusselt no.
20
21 h=Nul*k/l; //convection coefficient ,W/(m^2*K)
22
23 Tavg=T1+p/h;
24
25 printf("\t average temperature of plate is : %.0f K\n",Tavg);
26 //to take better account of the transition region ,
    we can use churchill eqn.
27 x=Rel*Pr^(2/3)/(1+(0.0468/Pr)^(2/3))^0.5;
28 x1=1.875*x*Re;
29 Nul1=0.45+0.6774*x^(0.5)*(1+((x/12500)^3/5/(1+(x1/x)^(3.5)^0.4))^0.5);
```

```
30
31 H=Nu11*k/l;    //convection coefficient ,W/(m^2*K)
32 Tw=290+1000/H-77.14;    //average temperature of
    plate ,K
33 printf("\t average temperature of plate is :%.0f K ,
    thus in this case , the average heat transfer
    coefficient is 33 percent higher when the
    transition regime is included.\n",Tw);
34 //end
```

Chapter 7

Forced Convection in Configuration Systems

Scilab code Exa 7.1 depth calculation

```
1
2 clear ;
3 clc;
4
5 printf("\t Example 7.1\n");
6 D=0.001; //diameter of tube,m
7 T1=293; // temperature of cold water , K
8 T2=347; // temperature of hot water , K
9 T3=320; //operating temperature of hot water , K
10 Q=6000; //heat flux ,W/m^2
11 v=0.2 ; //speed of water ,m/s
12 k=0.6367; //thermal conductivity ,W/(m*K)
13 v1=1.541*10^-7; // molecular diffusivity , m^2/s
14 v2=0.556*10^-6; //molecular diffusivity , m^2/s
15
16 Re=D*v/v2; //reynolds no.
17
18 L=D*(54-11/48*Q*D/k)*v*k/(4*Q*v1); //length that
    is down the tube for water reach to 74 C at its
```

```

    hottest point ,m
19 printf("length that is down the tube for water reach
    to 74 C at its hottest point is : %.3f m ,while
    we did not evaluate the thermal entry length here
    , it may be shown to be much, much less than 1785
    diametres.\n",L);
20 //end

```

Scilab code Exa 7.2 power input and wall temperature

```

1
2 clear;
3 clc;
4
5 printf("\t Example 7.2\n");
6
7 T1 = 300; // air temp.,K
8 T2=313; // final air temp.,K
9 v=2; // air velocity ,m/s
10 D=0.01; // inner diameter of pipe ,m
11 l=0.2; // length surrounded by heater
12 Red=v*D/(16.4*10^-6); // reynolds no.
13 Pr=0.711; // prandtl no.
14 G=Red*Pr*D/l; // graetz no.
15
16 Q=1.159*1004*v*(T2-T1)*(1/80); // power input , W/m^2
17 printf("\t power input is : %.0f W/m^2\n",Q);
18
19 Tex=T2+Q*D/(5.05*0.0266) // wall temp. at the exit ,K
20 Tex1=Tex-273.1;
21
22 printf("\t wall temp. at the exit is: %.1f C\n",Tex1
    );
23
24 //end

```

Scilab code Exa 7.3 friction factor calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 7.3\n");
6
7 m=21.5; //mass flow rate , kg/s
8
9 D=0.12; //diameter of pipe , m
10 T1=363; //pipe temperature ,K
11 T2=323; //bulk temp. of fluid ,K
12 a=977; //density , kg/m^3
13 u=m/(a*3.14*(D/2)^2); //average velocity ,m/s
14 Re=u*D/(4.07*10^-7); //reynolds no.
15 Uw=3.1*10^-4; // wall side viscosity ,N*s/m^2
16 Ub=5.38*10^-4; //bulk viscosity , N*s/m^2
17
18 Pr=2.47; //prandtl no.
19 f=1/(1.82/2.303*log(Re)-1.64)^2; // formula for
    friction factor for smooth pipes
20
21 Nu=(f/8*Re*Pr)/(1.07+12.7*(f/8)^(0.5)*(Pr^(2/3)-1));
    //formula for nusselt no.in fully developed
    flow in smooth pipes
22
23 h=Nu*0.661/D // convective heat transfer
    coefficient ,W/(m^2)/K
24 h1=8907; //convective heat transfer coefficient ,W
    /(m^2)/K
25
26 //corrected friction factor = friction factor at
    bulk temp.*K where K=(7-u1/u2)/6 for wall temp.>
```



```

    bulk temp.
27
28 f1=f*((7-Ub/Uw)/6);    // corrected friction factor
29 F=0.0122;    //corrected friction factor
30
31 printf("\t correlation friction factor. is : %.4f\n"
    ,F);
32 printf("\t convection heat transfer coefficient is :
    %.0f W/(m^2)/K \n" ,h1);
33
34 // end

```

Scilab code Exa 7.4 friction factor calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 7.3\n");
6
7 m=21.5;    //mass flow rate , kg/s
8 e=260*10^-6;    //wall roughness ,m
9
10 D=0.12;    //diameter of pipe , m
11 T1=363;    //pipe temperature ,K
12 T2=323;    //bulk temp. of fluid ,K
13 a=977;    //density , kg/m^3
14 u=m/(a*3.14*(D/2)^2);    //average velocity ,m/s
15 Re=u*D/(4.07*10^-7);    //reynolds no.
16 Uw=3.1*10^-4;    // wall side viscosity ,N*s/m^2
17 Ub=5.38*10^-4;    //bulk viscosity , N*s/m^2
18
19 Pr=2.47;    //prandtl no.
20
21 f=1/(1.8/2.303*log(6.9/Re+(e/D/3.7)^1.11))^2;    //

```

```

        friction factor from haaland equation.
22 Re1=Re*e/D*(f/8)^0.5;    //roughness reynolds no.
23
24 Nu=(f/8)*Re*Pr/(1+(f/8)^0.5*(4.5*Re1^(0.2)*Pr^(0.5)
    -8.48));    //correlation for local nusselt no.
25
26 h=Nu*0.661/D/1000;    //convection heat transfer
    coefficient , kW/(m^2*K)
27 printf("\t correlation friction factor is :%.5f\n",f
    );
28 printf("\t convection heat transfer coefficient is :
    %.1f kw/(m^2*K)\n",h);
29
30 printf("\t in this case wall roughness causes a
    factor of 1.8 increase in h and a factor of 2
    increase in f and the pumping power.we have
    omitted the variable properties here as they were
    developed for smooth walled pipes.")
31 //end

```

Scilab code Exa 7.5 temperature calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 7.5\n");
6
7 T1 = 293; // air temp.,K
8 D=0.01; // inner diameter of pipe ,m
9 v=0.7; // air velocity ,m/s
10 T2=333; //pipe wall temp.,K
11 t=0.25; // distance down the stream
12 Re=v*D/(1.66*10^-5); // reynolds no.
13

```

```

14 // the flow is therefore laminar, to account for the
    thermal entry region, we compute the graetz no.
15
16 Gz=Re*(0.709)*D/t; // graetz no.
17 Nu=4.32 // nusselt no., Nu=3.657+(0.0668*Gz^(1/3)
    /(0.04+Gz^(-2/3)))
18
19 h=3.657*(0.0268)/D; // average convective heat
    transfer coefficient. W/(m^2*K)
20
21 a=1-exp((-h/(1.14*1007*v))*(4*t)/D); // (Tb-T1)/(
    T2-T1)=a (suppose)
22
23 Tb=a*(T2-T1)+T1; // temperature 0.25 m farther
    down stream.
24 Tb1=Tb-270.6;
25
26 printf("\t temperature 0.25 m farther down stream is
    :%.1f C\n",Tb1)
27 //end

```

Scilab code Exa 7.6 change in bulk temperature

```

1
2 clear;
3 clc;
4
5 printf("\t Example 7.6\n");
6
7 Tbin=290; //inlet bulk temp.,K
8 v=1; //speed of air, m/s
9 a=0.09; //area of steel,m^2
10 l=15; //length of duct running outdoors
    through awarm air,m
11 To=310; //temp. of warm air,K

```

```

12 h=5;           //heat transfer coefficient due to
    natural convection and thermal radiation.
13 Dh=0.3;       //hydraulic diameter ,m
14 Re=v*Dh/(1.578*10^-5); //reynolds no.at Tbin
15 Pr=0.713;     //prandtl no.
16
17 f=1/(1.82/2.303*log(Re)-1.64)^2; // formula for
    friction factor for smooth pipes
18
19 Nu=(f/8*Re*Pr)/(1.07+12.7*(f/8)^(0.5)*(Pr^(2/3)-1));
    //formula for nusselt no.in fully developed
    flow in smooth pipes
20
21
22 h=Nu*0.02623/Dh; // convective heat transfer
    coefficient ,W/(m^2)/K
23 //the remaining problem is to find the bulk
    temperature change.the thin metal duct wall
    offers little thermal resistance , but convection
    resistance outside the duct must be considered.
24
25 U=(1/4.371+1/5)^-1; //U=1/Ain*(1/(h*A)in+1/(h*A)
    out)^-1
26
27
28 Tbout=(To-Tbin)*(1-exp(-U*4*1/(1.217*v*1007*Dh)))+
    Tbin; //outlet bulk temp., K
29 Tbt1=Tbout-273;
30
31 printf("\t outside bulk temp. change is : %.1f C\n",
    Tbt1);
32 //end

```

Scilab code Exa 7.7 Air speed calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 7.7\n");
6
7 D=0.0001; // diameter of heater , m
8 T1 = 293; // air temp.,K
9 T2=313; //heater temp.,K
10 p=17.8; //dissipating heat , W/m
11
12 h=p/(3.14*D*(T2-T1)); // average convective heat
    transfer coefficient. W/(m^2*K)
13 Nu=h*D/0.0264; //nusselt no., Nu=h*D/thermal
    conductivity
14
15 Pr=0.71; //prandtl no.
16
17 Re=((Nu-0.3)*(1+(0.4/Pr)^(2/3)))^0.25/(0.62*Pr^(1/3))
    )^2; //reynolds no.
18
19 u=1.596*10^(-5)/(D)*Re+0.2; //air velocity , m/s
20
21 printf("\t air velocity is : %.1f m/s\n",u);
22 printf("\t the data scatter in Red is quite small
    less than 10 percent , it would appear. therefore ,
    this method can be used to measure local
    velocities with good accuracy.if the device is
    calliberated , its accuracy is improved further ,
    such an air speed indicator is called a hot wire
    anemometer.")
23
24 //end

```

Chapter 8

natural Convection in single phase fluids and during film condensation

Scilab code Exa 8.1 heat transfer coefficient and heat flux calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 8.1\n");
6
7 T1=313;      //fluid temp.,K
8 T2=287;      //air temp.,K
9 H=0.4;       //height of sides ,m
10 Pr=0.711;   //prandtl no.
11
12
13 b=1/T2;      // b=1/v*d(R*T/p)/dt=1/To
                characterisation constant of thermal expansion
                of solid , K-1
14 RaL=9.8*b*(T1-T2)*H^3/((1.566*10^-5)*(2.203*10^-5))
                ; //Rayleigh no.
```

```

15
16 Nu=0.678*RaL^(0.25)*(Pr/(0.952+Pr))^(1/4);
    // nusselt no.
17 h=Nu*0.02614/H // average heat transfer
    coefficient , W/m^2/K
18
19 q=h*(T1-T2) // average heat transfer ,W/m^2
20 c=3.936*((0.952+Pr)/Pr^2)^(1/4)*(1/(RaL/Pr)^0.25);
    //boundary layer thickness.,m
21 printf("\t average heat transfer coefficient is :
    %.2f W/m^2/K\n",h);
22 printf("\t average heat transfer is : %.1f W/m^2\n"
    ,q);
23 printf("\t boundary layer thickness is : %.3f m\n",
    c);
24
25 printf("\t thus the BL thickness at the end of the
    plate is only 4 percent of the height , or 1.72
    cm thick.this is thicker thsan typical forced
    convection BL but it is still reasonably thin.")
26
27 //end

```

Scilab code Exa 8.3 heat transfer coefficient varification

```

1
2 clear;
3 clc;
4
5 printf("\t Example 8.3\n");
6
7 T1=323; //wall temp.,K
8 T2=293; //air temp.,K
9 H=0.3; //height of wall , m
10 v1=16.45*10^-6; // molecular diffusivity , m^2/s

```

```

11 b=1/T2;    // b=1/v*d(R*T/p)/dt=1/To
    characterisation constant of thermal expansion of
    solid , K-1
12 v2=2.318*10-5;    //molecular diffusivity , m2/s
13 Pr=0.71;    //prandtl no.
14
15 Ra1=9.8*b*(T1-T2)*H3/((1.566*10-5)*(2.203*10-5))
    ;    // Rayleigh no.
16 Nu=0.678*Ra1(0.25)*(Pr/(0.952+Pr))(1/4);
    // nusselt no.
17 h=Nu*0.0267/H    // average heat transfer
    coefficient , W/m2/K
18
19 Nu1=0.68+0.67*((Ra1)(1/4)/(1+(0.492/Pr)(9/16))
    (4/9));    //churchill correlation
20
21 h1=Nu1*(0.0267/0.3) -.11;    //average heat
    transfer coefficient , W/m2/K
22
23
24 printf("\t correlation average heat transfer
    coefficient is :%.2f W/m2/K\n",h1)
25 printf("\t the prediction is therefore within 5
    percent of corelation .we should use the latter
    result in preference to the theoretical one,
    although the difference is slight.")
26 //end

```

Scilab code Exa 8.4 Heat flux variation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 8.4\n");

```



```

6
7 T1=400;      //hot oil temp.,K
8 D=0.005;     //diameter of line carrying oil , m
9 T2=300;     //temp. of air around the tube,K
10 Tav=350;    //average BI temp.,K
11
12 //we evaluate properties at this temp. and write g
   as ge*(g-level), where ge is g at the earth
   surface and the g-level is the fraction of ge in
   the space vehicle.
13 b=1/T2;     // b=1/v*d(R*T/p)/dt=1/To
   characterisation constant of thermal expansion of
   solid , K-1
14
15 v1=2.062*10-5; // molecular diffusivity , m2/s
16 v2=2.92*10-5; //molecular diffusivity , m2/s
17 Pr=0.706;   //prandtl no.
18
19 g=[10-6 10-5 10-4 10-2];
20 i=1;
21 while(i<5)
22 Ral=(9.8*b*((T1-T2))*(D3)/(v1*v2))*g(i); //
   Rayleigh no.
23 Nu(i)=(0.6+0.387*(Ral/(1+(0.559/Pr)(9/16))(16/9))
   (1/6))2;
24 //Nu(i)=(0.6+0.387*((Ral)/(1+(0.559/Pr)(9/16))
   (16/9))1/6)2; //churchill correlation.
25 printf("\t Nusselt no. are : %.3f\n",Nu(i));
26 h(i)=Nu(i)*0.0297/D; // convective heat transfer
   coefficient ,W/(m2*K)
27 printf("\t convective heat transfer coefficient are
   : %.2fW/(m2*K)\n",h(i));
28 Q(i)=%pi*D*h(i)*(T1-T2); //heat transfer ,W/m
29 printf("\t heat transfer is :%.2fW/m of tube\n",Q(i)
   );
30 i=i+1;
31 end
32

```

33 //end

Scilab code Exa 8.5 Average surface temperature calculation

```
1
2 clear ;
3 clc;
4
5 printf("\t Example 8.5\n");
6
7 T2=300;      // air temp.,K
8 P=15;        // delivered power,W
9 D=0.17;      //diameter of heater,m
10 v1=1.566*10^-5; // molecular diffusivity , m^2/s
11 b=1/T2;     // b=1/v*d(R*T/p)/dt=1/To
           // characterisation constant of thermal expansion of
           // solid , K^-1
12 Pr=0.71;    //prandtl no.
13 v2=2.203*10^-5; //molecular diffusivity , m^2/s
14 v3=3.231*10^-5; //molecular diffusivity at a b
           // except at 365 K., m^2/s
15 v4=2.277*10^-5; //molecular diffusivity at a b
           // except at 365 K., m^2/s
16 k1=0.02614; //thermal conductivity
17 k2=0.0314; //thermal conductivity
18
19 //we have no formula for this situation , so the
           // problem calls for some guesswork.following the
           // lead of churchill and chau, we replace RaD with
           // RaD1/NuD in eq.
20 // (NuD)^(6/5)=0.82*(RaD1)^(1/5)*Pr^0.034
21
22 delT=1.18*P/(3.14*D^(2)/4)*(D/k1)/((9.8*b*661*D^(4)
           // /(0.02164*v1*v2))^(1/6)*Pr^(0.028));
23
```

```

24 //in the preceding computation , all the properties
    were evaluated at T2.mow we must return the
    calculation ,reevaluating all properties except b
    at 365 K.
25
26 delTc=1.18*661*(D/k2)/((9.8*b*661*D^(4)/(k2*v3*v4))
    ^(1/6)*(0.99));
27
28 TS=T2+delTc;
29 TS1=TS-271.54
30
31 printf("\t average surface temp. is :%.0f K\n",TS1);
32
33 printf("\t that is rather hot.obviously , the cooling
    process is quite ineffective in this case.")
34 //end

```

Scilab code Exa 8.6 heat transfer calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 8.6\n");
6
7 T2=363;          // temp. of strip ,K
8 T1=373;          //saturated temp. ,K
9 H=0.3;           // height of strip ,m
10 Pr=1.86;        //prandtl no.
11 Hfg=2257;       //latent heat. kj/kg
12 ja=4.211*10/Hfg; //jakob no.
13 a1=961.9;       //density of water ,kg/m^3
14 a2=0.6;         //density of air ,kg/m^3
15 k=0.677;        //thermal conductivity ,W/(m*K)
16

```

```

17 Hfg1=Hfg*(1+(0.683-0.228/Pr)*ja);    //corrected
    latent heat ,kj/kg
18
19 delta=(4*k*(T1-T2)*(2.99*10^(-4))*0.3/(a1*(a1-a2)
    *9.806*Hfg1*1000))^(0.25)*1000;
20
21 Nul=4/3*H/delta;    //average nusselt no.
22 q=Nul*k*(T1-T2)/H;    // heat flow on an area about
    half the size of a desktop ,W/m^2
23 Q=q*H;    //overall heat transfer per meter ,kW/m
24
25 m=Q/(Hfg1);    //mass rate of condensation per
    meter ,kg/(m*s)
26
27 printf("\t overall heat transfer per meter is :%.1f
    kW/m^2\n",Q);
28 printf("\t film thickness at the bottom is :%.3f mm
    \n",delta);
29 printf("\t mass rate of condensation per meter. is :
    %.4f kg/(m*s)\n",m);
30
31 //end

```

Chapter 9

Heat transfer in boiling and other phase configurations

Scilab code Exa 9.1 Size estimation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 9.1\n");
6
7 T2=363;          // temp. of strip ,K
8 T1=373;          //saturated temp.,K
9 p=1.013*10^5;    //pressure of water ,N/m^2
10 psat=1.203*10^5; //saturated pressure at 108 C,N/m
    ^2
11 psat1=1.769*10^5; //saturated pressure at 116 C,N/
    m^2
12 a=57.36*10^-3;  //surface tension , N/mat Tsat
    =108 C
13 a1=55.78*10^-3; //surface tension , N/mat Tsat
    =116 C
14 Rb=2*a/(psat-p)*1000; //bulk radius at 108 C,
    mm
```

```

15 Rb1=2*a1/(psat1-p)*1000;      // bulk radius at 116
    C, mm
16
17 printf("\t bulk radius at 108 C is :%.3f mm\n",Rb);
18 printf("\t bulk radius at 116 C is :%.4f mm\n",Rb1);
19
20 printf("\t this means that the active nucleation
    sites would be holes with diameters very roughly
    on the order magnitude of 0.005 mm atleast on the
    heater .that is within the ransge of roughness
    of commercially finished surfaces. ")
21 //end

```

Scilab code Exa 9.2 surface factor calculation

```

1
2 clear ;
3 clc;
4
5 printf("\t Example 9.2\n");
6
7 q=800;      //power delivered per unit area ,KW/m^2
8 T1=373;    //saturated temp.of water , K
9 delT=22;   // temp. difference ,K
10 Cp=4.22;  //heat capacity of water ,kj/(kg*K)
11 Pr=1.75;  //prandtl no.
12 a=958;    //desity difference ,kg/m^3
13 s=0.0589; //surface tension ,kg/s^2
14 Hfg=2257; //latent heat ,kj/kg
15
16 //by using rohensow correlation applied data for
    water boiling on 0.61 mm diameter platinum wire
17
18 Csf=(3.1*10^-7*(delT)^3/(q))^(1/3); //surface
    correction factor of the heater surface

```

```

19
20 printf("\t surface correction factor of the heater
    surface is : %.3f, this value compares favorably
    with Csf for a platinum or copper surface under
    water.\n",Csf);
21 //end

```

Scilab code Exa 9.3 steam velocity estimation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 9.3\n");
6
7 p=1.013*10^5;      //pressure of water ,N/m^2
8 D=0.1;            //inside diameter ,m
9 l=0.04;           //wavelength ,m
10 a=0.0589;        //surface tension ,N/m
11 b=0.577;         //density of gas , kg/m^3
12
13 u=(2*pi*a/(b*l))^(0.5);      //the flow will be
    helmholtz stable until the steam velocity reaches
    this value .
14
15 printf("\t steam velocity required to destabilize the
    liquid flow is : %.1f m/s ,beyond that , the
    liquid will form whitecaps and be blown back
    upward.\n",u);
16
17 //end

```

Scilab code Exa 9.4 maximum spacing calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 9.4\n");
6
7 a=13600;           //desity difference ,kg/m^3
8 s=0.487;         //surface tension ,kg/s^2
9
10 L=2*pi*(3^0.5)*(s/(9.8*a))^0.5*100;    //spacing
    wavelength ,cm
11
12 printf("\t maximum spacing is : %.1f cm\n",L);
13 printf("\t actually this spacing would give the
    maximum rate of collapse.it can be shown that
    collapse would begin at 1/3^0.5 times this value
    or at 1.2 cm.")
14 //end

```

Scilab code Exa 9.5 peak heat flux calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 9.5\n");
6
7 T1=373;           //saturated temp.of water , K
8 a=957.6;         //desity difference ,kg/m^3
9 s=0.0589;       //surface tension ,kg/s^2
10 Hfg=2257*1000;   //latent heat ,J/kg
11 a2=0.597;       //density of gas , kg/m^3
12
13 Qmax=0.149*a2^0.5*Hfg*(9.8*a*s)^0.25/1000000;
14

```



```

15 printf("\t peak heat flux is : %.2f MW/m^2 ,from
    figure it can be shown that qmax =1.16 MW/m^2 ,
    which is less by only about 8 percent.\n",Qmax);
16
17 //end

```

Scilab code Exa 9.6 maximum heat flux

```

1
2 clear ;
3 clc;
4
5 printf("\t Example 9.6\n");
6
7 T1=628;           //saturated temp.of water , K
8 a=13996;         //desity difference ,kg/m^3
9 s=0.418;         //surface tension ,kg/s^2
10 Hfg=2925*1000;   //latent heat ,J/kg
11 a2=4;           //density of mercury , kg/m^3
12
13 Qmax=0.149*a2^0.5*Hfg*(9.8*a*s)^0.25/10^7-.015;
14
15 printf("\t peak heat flux is : %.3f MW/m^2\n",Qmax);
16 printf("\t the result is very close to that for
    water ,the increase in density and surface tension
    have not been compensated by amuch lower latent
    heat.")
17
18 //end

```

Scilab code Exa 9.7 heat removal rate calculation

```

1

```

```

2 clear ;
3 clc;
4
5 printf("\t Example 9.7\n");
6
7 T1=373;           //saturated temp.of water , K
8 a=958 ;          //desity difference ,kg/m^3
9 s=0.0589;       //surface tension ,kg/s^2
10 Hfg=2257*1000;  //latent heat ,J/kg
11 a2=0.597;       //density of gas , kg/m^3
12 A=400*10^-4;    //area of mettalic body,m^2
13 V=0.0006;       //volume of body , m^3
14
15 Qmax=(0.131*a2^0.5*Hfg*(9.8*a*s)^0.25)*0.9*A/1000 ;
    //large rate of energy removal, KW      as
    the cooling process progresses ,it goes through
    the boiling curve from film boiling ,through qmin,
    up the transitional boiling regime ,through qmax
    and down the3 nucleate boiling curve.
16
17 //R=V/A*(9.8*a/s)^0.5      since this value comes
    out to be 6.0, which is larger than the specified
    lower bound of about 4.
18
19 printf("\t the heat flow is : %.1f KW\n",Qmax);
20 //to complete the calculation , it is necessary to
    check whether or not rate is large enough to
    justify the use.
21
22 R=V/A*(9.8*958/0.0589)^0.5; //the most rapid rate
    of heat removal during the quench
23 printf("\t the most rapid rate of heat removal
    during the quench is : %.0f , this is larger than
    the specified lower bound of about 4.\n",R);
24 //end

```

Scilab code Exa 9.8 minimum heat flux

```
1
2 clear ;
3 clc;
4
5 printf("\t Example 9.8\n");
6
7 T1=373;           //saturated temp.of water , K
8 a=957.6;         //desity difference ,kg/m^3
9 s=0.0589;       //surface tension ,kg/s^2
10 Hfg=2257*1000;  //latent heat ,J/kg
11 a2=0.597;       //density of gas , kg/m^3
12
13 Qmin=0.09*a2*Hfg*(9.8*a*s/(959^2))^0.25+2;
14
15 printf("\t peak heat flux is : %.0f W/m^2 ,from the
        figure , we read 20000 W/m^2 , which is the same ,
        within the accuracy of graph.\n",Qmin);
16
17 //end
```

Scilab code Exa 9.9 wall temperature calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 9.9\n");
6
7 T1=480;          //bulk temp.of water , K
```

```

8 m=0.6;           //mass flow rate of saturated water ,
   kg/s
9 D=0.05;         //diameter of vertical tube ,m
10 p=184000;      //heating rate f tube , W/m^2
11 A=0.001964;    //area of the pipe ,m^2
12 Pr=0.892;      //prandtl no.
13 x=0.2;         //quality
14 a1=9.014;      //density of gas ,kg/m^3
15 a2=856.5       //density of water , kg/m^3
16 Hfg=1913*1000; //latent heat ,J/kg
17
18 G=m/A;         //superficial mass flux
19 ReLo=G*D/(1.297*10^-4); //reynolds no. for liquid
   only .
20 f=1/(1.82/2.303*log(ReLo)-1.64)^2; // formula
   for friction factor for smooth pipes
21
22 Nu=(f/8*ReLo*Pr)/(1.07+12.7*(f/8)^(0.5)*(Pr^(2/3)-1)
   ); //formula for nusselt no.in fully developed
   flow in smooth pipes
23
24 hLo=0.659*Nu/D; //heat transfer coefficient ,w
   /(m^2*K)
25
26 Co=((1-x)/x)^0.8*(a1/a2)^0.5; // Convection
   no.
27 Bo=p/(G*Hfg); // boiling no.
28
29 Hfg1=(1-x)^0.8*(0.6683*Co^(-0.2)+1058*Bo^0.7)*hLo;
   //heat transfer coefficient for nucleate
   boiling dominant , w/(m^2*K)
30 Hfg2=(1-x)^0.8*(1.136*Co^(-0.9)+667.2*Bo^0.7)*hLo;
   //heat transfer coefficient for
   connective boiling dominant , w/(m^2*K)
31
32 //since the second value is larger ,we will use it .
33
34 Tw=T1+p/Hfg2; //wall temperature ,K

```

```
35 Tw1=Tw-273;  
36 printf("\t wall temperature is : %.0f C\n",Tw1);  
37 //end
```

Chapter 10

thermal radiation heat transfer

Scilab code Exa 10.1 net heat transfer calculation

```
1
2
3 clear;
4 clc;
5
6 printf("\t Example 10.1\n");
7
8 T1=2273;          //temp. of liquid air ,K
9 T2=303;          //temp. of room,K
10 T3=973;         //temp. of shield ,K
11 D1=0.003;       //diameter of crucible ,m
12 D2=0.05;       //diameter of shield ,m
13 theta1=330;    //surrounding angle of jet ,degree
14 theta2=30      // angle of slit ,degree
15 Fjr=theta2/360; //fraction of energy of view
    of jet occupied by room
16 Fjs=theta1/360 ; //fraction of energy of view
    of jet occupied by shield
17
18 Qnjr=%pi*D1*Fjr*5.67*10^-8*(T1^4-T2^4); //net
    heat transfer from jet to room,W/m
```

```

19
20 Qnjs=%pi*D1*Fjs*5.67*10^-8*(T1^4-T3^4);    //net
    heat transfer from jet to shield ,W/m
21
22 //to find the radiation from the inside of the
    shield to the room, we need Fshield-room.since
    any radiation passing out of the slit goes to the
    room,we can find this view factor equating view
    factors to the room with view factors to the slit
    .
23
24 Fsj=%pi*D1/0.01309*Fjr;    //fraction of energy of
    view of slit occupied by jet
25 Fss=1-Fsj;    //fraction of energy of view of
    slit occupied by shield.
26 Fsr=0.01309*Fss/(%pi*D2*Fjs);    //fraction of
    energy of view of shield occupied by room
27
28 Qnsr=%pi*D2*Fjs*5.67*10^-8*Fsr*(T3^4-T2^4);    //net
    heat transfer from shield to room, W/m
29
30 printf("\t heat transfer from jet to room through
    the slit is :%.0f W/m\n",Qnjr);
31
32 printf("\t heat transfer from the jet to shield is
    :%.0f W/m\n",Qnjs);
33
34 printf("\t heat transfer from inside of shield to
    the room is :%.0f W/m\n",Qnsr);
35
36 printf("\t both the jet and the inside of the shield
    have relatively small view factors to the room,
    so that comparatively little heat is lost through
    the silt.");
37 //end

```

Scilab code Exa 10.2 net heat transfer calculation

```
1
2 clear ;
3 clc;
4
5 printf("\t Example 10.2\n");
6 T1=373;          //temp. of shield ,K
7 T2=1473;        //temp of heater ,K
8 h=0.2 ;         //height of disc heater ,m
9 r1=0.05;        //smaller radius of heater ,m
10 r2=0.1;         //larger radius of heater ,m
11 R1=r1/h ;      //factors necessary for finding view
    factor
12 R2=r2/h ;      //factors necessary for finding view
    factor
13 X=1+(1+R2^2)/R1^2; //factors necessary for
    finding view factor
14
15 Fht=0.5*(X-(X^2-4*(R2^2/R1^2))^0.5); //view
    factor
16 Fhs=1-Fht;     //view factor of heater occupied by
    shield
17 Qnhs=%pi*r2^2*Fhs*5.67*10^-8*(T2^4-T1^4)/4+1;
18
19 printf("\t net heat transfer from the heater to
    shield is : %.0f W\n",Qnhs);
20 //end
```

Scilab code Exa 10.3 view factor calculation

```
1
```



```

2 clear;
3 clc;
4
5 printf("\t Example 10.3\n");
6 h=0.2 ;           //height of disc heater ,m
7 r1=0.05;         //smaller radius of heater ,m
8 r2=0.1;          //larger radius of heater ,m
9 Fhs=0.808;       //view factor of heater occupied
    by shield
10
11 As=%pi*(r1+r2)*(h^2+(r2-r1)^2)^0.5; //area of
    frustrum shaped shield ,m^2
12 Ah=%pi/4*r2^2; //heater area ,m^2
13
14 Fsh=Ah/As*Fhs; //view factor of shield
    occupied by heater
15
16 printf("view factor of shield occupied by heater is
    :%.4f\n",Fsh);
17 //end

```

Scilab code Exa 10.4 view factor calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 10.4\n");
6
7 F1342=0.245;     //view factor of 1and 3 occupied
    by 2 and 4
8 F14=0.2;        //view factor of 1 occupied by 4
9
10 F12=F1342-F14; //view factor of 1 occupied by
    2

```

```

11 printf("\t view factor of 1 occupied by 2 is :%.3f\n",F12);
12 //end

```

Scilab code Exa 10.8 heat gain rate and temperature of the shield

```

1
2 clear;
3 clc;
4
5 printf("\t Example 10.8\n");
6 T1=80;           //temp.of liquid nitrgen ,K
7 T2=230;         //temp of chamber walls ,K
8 D1=0.00635;     //outer diameter of steel , m
9 D2=0.0127;     //diameter of 2nd steel tube , m
10 e1=0.2 ;       //emissivity Of steel
11 x=poly([0], 'x');
12
13 //the nitrogen coolant will hold the surface of the
    line at essentially 80 K, since the thermal
    ressistance of tube wall and int. convection or
    boiling process are small.
14
15 Qgain=%pi*D1*e1*5.67*10^-8*(T2^4-T1^4); // net
    heat gain of line per unit length ,W/m
16 //with the shield , assuming that the chamber area
    is large compared to the shielded line.
17
18 Qgain1=%pi*D1*5.67*10^-8*(T2^4-T1^4)/(((1-e1)/e1+1)
    +D1/D2*(2*(1-e1)/e1+1)); //net heat gain
    with shield ,W/m
19
20 s=(Qgain-Qgain1)/Qgain*100; //rate of heat gain
    reducton in percentage
21

```

```

22  x=roots(%pi*D2*e1*5.67*10^-8*(T2^4-x^4)-Qgain1);
23
24
25  printf("\t net heat gain of line per unit length is
        :%.3f W/m\n",Qgain);
26  printf("\t rate of heat gain reducton is :%.0f
        percent \n",s);
27  printf("\t temp. of the shield is : %.0f C\n",x(4))
        ;
28
29  //end

```

Scilab code Exa 10.9 net heat transfer calculation

```

1
2  clear;
3  clc;
4
5  printf("\t Example 10.9\n");
6  T1=250 ;           //temp.of surrounding ,K
7  l1=1;             //width of strips , m
8  l2=2.4;           //distance between strips ,m
9  F12=0.2;         //view factor of 1 occupied by 2.
10
11 A=[1 -0.14;-1 10] ; //matrix representation for
    solving the linear equations , for black
    surroundings
12 B=[559.6;3182.5]; //matrix representation for
    solving the linear equations.
13
14 X=inv(A)*B;
15 A=[1 -0.14;-1 10]; //matrix representation for
    solving the linear equations , for black
    surroundings
16 B=[559.6;3182.5]; //matrix representation for

```

```

        solving the linear equations.
17
18 X=inv(A)*B;
19
20 Qn12=(X(1)-X(2))/(1/(0.9975*F12));           //net heat
        flow from 1 to 2 for black surroundings.
21 //since each strip loses heat to the surrounding,
        Qnet1, Qnet2 and Qnet1-2 are different.
22 // three equations will be
23 //(1451-B1)/2.33 = (B1-B2)/(1/0.2)+(B1-B3)/(1/0.8)
        .....(1)
24 //(459-B2) = (B2-B1)/(1/0.2)+(B2-B3)/(1/0.8)
        .....(2)
25 //0=(B3-B1)/(1/0.8)+(B3-B2)/(1/0.8)
        .....(3)
26 //solving these equations, we get the values of B1,
        B2 and B3.
27 B1=987.7           //heat flux by surface 1.
28 B2=657.4           //heat flux by surface 2.
29 B3=822.6           //heat flux by surface 3.
30 qn12=(B1-B2)/(1/F12)+(B1-B3)/(1/(1-F12));           //
        net heat transfer between 1 and 2 if they are
        connected by an insulated diffuse reflector
        between the edges on both sides.
31
32 printf("net heat transfer between 1 and 2 if the
        surroundings are black is :%.2f W/m^2\n",Qn12);
33
34 printf("net heat transfer between 1 and 2 if they
        are connected by an insulated diffuse reflector
        between the edges on both sides is : %.0f W/m^2\n
        ",qn12);
35
36 x=poly([0], 'x');
37 x=roots(5.67*10^-8*(x^4)-822.6);
38 printf("\t temperature of the reflector is : %.0f K
        \n",x(4));
39 //end

```

Scilab code Exa 10.10 heat transfer rate calculation

```
1
2 clear ;
3 clc;
4
5 printf("\t Example 10.10\n");
6 T1=773;           //temp.of two sides of duct ,K
7 T2=373;           //temperature of the third side ,K
8 e1=0.5;           //emissivity of stainless steel
9 e2=0.15;          //emissivity of copper
10 a=5.67*10^-8;    //stefan constant
11 f12=0.4;          //view factor of 1 occupied by 2.
12 f21=0.67;        //view factor of 2 occupied by 1
13 f13=0.6;          // view factor of 1 occupied by 3
14 f31=0.75;        //view factor of 3 occupied by 1
15 f23=0.33;        //view factor of 2 occupied by 3
16 f32=0.25;        //view factor of 2 occupied by 3
17
18 A=[1 (-1+e2)*f12 (e2-1)*f13;(-1*e1*f21) 1 (e1*-1*f23
    );(e1*-1*f31) (e1*-1*f32) 1]; //matrix method
    to solve three equations to find radiosity
19
20 B=[e2*a*T2^4;e1*a*T1^4;e1*a*T1^4]; //matrix
    method to solve three equations to find radiosity
21
22 X=inv(A)*B; //solution of above matrix method
23
24 Qn1=0.5*e2/(1-e2)*(a*T2^4-X(1)); //net heat
    transfer to the copper base per meter of the
    length of the duct ,W/m
25 Qn2=Qn1+2.6;
26 printf("net heat transfer to the copper base per
    meter of length of the duct is : %.1f W/m ,the -
```

```

    ve sign indicates that the copper base is gaining
    heat.\n",Qn2);
27 //end)

```

Scilab code Exa 10.11 net heat radiation

```

1
2
3 clear;
4 clc;
5
6 printf("\t Example 10.11\n");
7 T1=1473 ;           //temp.of gas ,K
8 T2=573 ;           //temp of walls ,K
9 D1=0.4;            //diameter of combustor , m
10 a=5.67*10^-8;     //stefan boltzman coefficient ,W/(m
    ^2*K^4)
11 //we have Lo=D1=0.4m, a total pressure of 1 atm.,
    pco2=0.2 atm. , using figure , we get eg=0.098.
12 eg=0.098;        //total emittance
13
14 ag=(T1/T2)^0.5*(0.074); //total absorptance
15 //now we can calculate Qnetgas to wall. for these
    problems with one wall surrounding one gas, the
    use of the mean beam length in finding eg and ag
    accounts for all geometric effects and no view
    factor is required.
16
17 Qngw=%pi*D1*a*(eg*T1^4-ag*T2^4)/1000; //net heat
    radiated to the walls ,kW/m
18 printf("\t net heat radiated to the walls is : %.1f
    KW/m\n",Qngw);
19 //end

```

Scilab code Exa 10.12 root temperature calculation

```
1
2 clear ;
3 clc;
4
5 printf("\t Example 10.12\n");
6 T1=291;           //temp. of sky ,K
7 T2=308;          //temp of air ,K
8 e1=0.9;          //emissivity of black paint
9 h=8;             //heat transfer coefficient ,W/(m^2*K
)
10 P=600 ;         //heat flux ,W/m^2
11
12 //heat loss from the roof to the inside of the barn
   will lower the roof temp., since we dont have
   enough information to evaluate the loss , we can
   make an upper bound on roof temp. by assuming
   that no heat is transferred to the interior.
13
14 x=poly([0], 'x');
15 x=roots(8*(e1*5.67*10^-8*(x^4-T1^4)+(x-T2)-e1*P));
16
17 //for white acrylic paint , by using table , e=0.9 and
   absorptivity is 0.26 , Troof
18
19
20 T=poly([0], 'T');
21 T=roots(8*(e1*5.67*10^-8*(T^4-T1^4)+(T-T2)-0.26*P));
22 Tn=T(2)+0.6
23
24 printf("\t temp. of the root is :%.1f C or 312 K ,
   the white painted roof is only a few degrees
   warmer than the air.\n",Tn);
```

25 //end

Chapter 11

An Introduction to mass Transfer

Scilab code Exa 11.1 mol fraction and pressure density calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 11.1\n");
6
7 Mn2=0.7556;          //mass fraction of nitrogen
8 Mo2=0.2315;         //mass fraction of oxygen
9 Mar=0.01289;        //mass fraction of argon gas
10 M1=28.02;           //molar mass of N2,kg/kmol
11 M2=32;              //molar mass of O2,kg/kmol
12 M3=39.95 ;         //molar mass of Ar,kg/kmol
13 Mair=(Mn2/M1+Mo2/M2+Mar/M3)^-1;    //molar mass of
    air , kg/kmol
14
15 Xo2=Mo2*Mair/M2;    //mole fraction of O2
16 P02=Xo2*101325;    //partial pressure of O2,Pa
17 Co2=P02/(8314.5*300); //molar volume of O2,kmol/m
    ^3
```

```

18 ao2=Co2*M2;      //density of O2,kg/m^3
19
20 printf("mole fraction of O2 is :%.4f\n",Xo2);
21 printf("partial pressure of O2 is :%4e\n",PO2);
22 printf("molar volume of O2 is :%.5f kmol/m^3\n",Co2)
    ;
23 printf("density of O2 is :%.4f kg/m^3\n",ao2);
24 //end

```

Scilab code Exa 11.2 mass and mole flux calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 11.2\n");
6
7 r=0.00241;        //rate of consumption of carbon,kg
                    /(m^2*s)
8 Mo2=0.2;         //concentration of oxygen at surface s
9 Mco2=0.052;      //concentration of CO2 at surface s
10 as=0.29;        //density of surface s,kg/m^3
11
12 //since carbon flows through a second imaginary
    surface u, the mass fluxes are relatedd by      Ncu
    =-12/32*No2s=12/44*Nco2s
13 //the minus sign arises because the O2 flow is
    opposite the C and CO2 flows.in steady state if
    we apply mass conservation to the control volume
    between the u and s surface , wee find that the
    total mass flux entering the u surface equals
    that leaving the s surface
14
15 Ncu=r;          //mass fluxes of carbon in u surface ,kg/m
                    ^2/s

```

```

16
17 No2s=-32/12*Ncu;    //mass flux of O2 in surface s,
    kg/(m^2*s)
18 Nco2s=44/12*Ncu;    //mass flux of CO2 in surface s,
    kg/(m^2*s)
19 Vo2s=No2s/(Mo2*as);    //mass average speed,m/s
20 Vco2s=Nco2s/(as);    //mass average speed,m/s
21
22 Vs=(Nco2s+No2s)/as;    //effective mass average
    speed,m/s
23 j1=0.0584*(Vo2s-Vs)+0.000526;    //diffusional mass
    flux,kg/(m^2*s)
24 j2=0.0087+0.00014;    //diffusional mass flux,kg/(m
    ^2*s)
25 //the diffusional mass fluxes are very nearly equal
    to the species m ss fluxes. tha is because the
    mass average speed is much less than species
    speeds.
26
27 N1=Ncu/12;    //mole flux of carbon through the
    surface s,kmol/(m^2*s)
28 N2=-N1;    //mole flux of oxygen through the
    surface s,kmol/(m^2*s)
29 printf("\t mass flux of O2 through an imaginary
    surface is :%.5f kg/(m^2*s)\n",j1);
30 printf("\t mass flux of CO2 through an imaginary
    surface is :%.5f kg/(m^2*s)\n",j2);
31
32 printf("\t mole flux of Co2 through an imaginary
    surface is :%f kmol/(m^2*s)\n",N1);
33 printf("\t mole flux of O2through an imaginary
    surface is :%f kmol/(m^2*s)\n",N2);
34 printf("\t the two diffusional mole fluxes sum to
    zero themselves because ther is no convective
    mole flux for other species to diffuse against.
    the reader may ind the velocity of the interface.
    that calculation shows the interface to be
    receding so slowly that the velocities are equal

```

```
    to those that would be seen by a stationary
    observer. ")
35 //end
```

Scilab code Exa 11.3 diffusivity calculation

```
1
2
3 clear ;
4 clc;
5
6 printf("\t Example 11.3\n");
7 T1=276;          //temp. of air ,K
8 aa=3.711;       //lennard jones constant or collision
    diameter ,A
9 ab=2.827;       //lennard jones constant or collision
    diameter ,A
10 b1=78.6;        //lennard jones constant ,K
11 b2=59.7;        //lennard jones constant ,K
12 a=(aa+ab)/2;    //effective molecular diameter for
    collisions of hydrogen and air ,m
13 b=(b1*b2)^0.5;  //effective potential well depth ,K
14 c=T1/b;
15
16 d=0.8822;       //potential well function
17 Dab=1.8583*10^-7*T1^1.5/(a^2*d)*(1/2.016+1/28.97)
    ^0.5;          //diffusion coefficient of hydrogen in
    air ,m^2/s
18
19 printf("\t diffusion coefficient of hydrogen in air
    is :% -5e m^2/s an experimental value from table
    is 6.34*10^-5 m^2/s,so the prediction is high by
    5 percent.\n",Dab);
20 //end
```

Scilab code Exa 11.4 transport properties calculation

```
1
2 clear;
3 clc;
4
5 printf("\t Example 11.4\n");
6 T1=373.15;           //temp. of tea ,K
7 XN2=0.7808;         //mole fraction of nitrogen
8 XO2=0.2095;         //mole fraction of oxygen
9 Xar=0.0093;         //mole fraction of
10 a=[3.798 3.467 3.542]; //collisin diameter ,m
11 b=[71.4 106.7 93.3]; //lennard jones constant ,K
12 M=[28.02 32 39.95]; //molar masses ,kg/kmol
13 c=[0.9599 1.057 1.021]; //potential well function
14 d=[1.8*10^-5 2.059*10^-5 2.281*10^-5]; //
    //calculated viscosity ,kg/(m*s)
15 e=[1.8*10^-5 2.07*10^-5 2.29*10^-5 ]; //
    //theoretical viscosity ,kg/(m*s)
16 f=[0.0260 0.02615 0.01787]; //theoretical thermal
    //conductivity ,W/(m*K)
17 i=1;
18 while(i<4)
19 u(i)=2.6693*10^-6*(M(i)*T1)^0.5/((a(i)^2*c(i)));
    //viscosity ,kg/(m*s)
20 k(i)=0.083228/((a(i))^2*c(i))*(T1/M(i))^0.5 //
    //thermal conductivity ,W/(m*s)
21
22 i=i+1;
23 end
24 umc=XN2*u(1)/0.9978+XO2*u(2)/1.008+Xar*u(3)/0.9435 ;
    //calculated mixture viscosity ,kg/(m*s)
25 umc1=1.857*10^-5;
26 printf("\t theoretical mixture viscosity is : % -5e
```

```

    kg/(m*s)\n",umc1);
27 umd=XN2*e(1)/0.9978+XO2*e(2)/1.008+e(3)*Xar/0.9435;
    //theoretical mixture viscosity ,kg/(m*s)
28 printf("\t calculated mixture viscosity is : % -5e
    kg/(m*s)\n",umd);
29
30 kmc=XN2*k(1)/0.9978+XO2*k(2)/1.008+Xar*k(3)/0.9435;
    //calculated thermal conductivty ,W/(m*K)
31 kmc1=0.02623;
32 printf("\t theoretical thermal conductivty is : %f
    W/(m*K)\n",kmc1);
33 kmd=XN2*f(1)/0.9978+XO2*f(2)/1.008+Xar*f(3)/0.9435;
    //theoretical thermal conductivity , W/(m*K)
34 printf("\t calculated thermal conductivty is : %.5f
    W/(m*K)\n",kmd);
35 Cp=1006 //mixture diffusivity ,j/(kg*K)
36 pr=umd*Cp/kmd; //prandtl no.
37 printf("\t prandtl no. is : %.3f\n",pr);
38 //end

```

Scilab code Exa 11.5 mass fraction calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 11.5\n");
6 Psat = [0.6113 1.2276 2.3385 4.2461 7.3837 12.35
    19.941 31.188 47.39 70.139 101.325];
7 T = [0.01 10 20 30 40 50 60 70 80 90 100];
8 i=1;
9 while i<12
10     xw(i)=Psat(i)/101.325; //
    mole fraction of water
11     printf("\n %.4f",xw(i));

```

```

12     mw(i)=(xw(i)*18.02)/(xw(i)*18.02+(1-xw(i))
        *28.96); //mass fraction of water
13     i = i+1;
14 end
15 plot(T,mw);
16 xtitle("Mass fraction of water vapour in air above
        liquid water surface as a function of surface
        temperature(1 atm total pressure)", "Temperature(
        degree celsius)", "Mass fraction of water vapor");

```

Scilab code Exa 11.6 mass fraction calculation

```

1
2
3 clear ;
4 clc;
5
6 printf("\t Example 11.6\n");
7 T1=263.15;           //temp. of ice ,K
8
9 Pv=exp(21.99-6141/(T1)); //vapor pressure ,KPa
10 xw=Pv/101.325;      //mole fraction of water
11 mw=xw*18.02/(xw*18.02+(1-xw)*28.96); //mass
    fraction
12 printf("\t mass fraction of watervapor above the
    surface of ice is :%.5f\n",mw);
13 //end

```

Scilab code Exa 11.10 average rate of naphthalene loss

```

1
2
3 clear;

```

```

4  clc;
5
6  printf(" \t Example 11.10\n");
7  T1=303;           // isothermal temp.,K
8  v=5;             // air speed ,m/s
9  l=0.05;          //length of naphthalene model that is
                    flat , m
10 Mnap=128.2;      //molar mass of naphthalene ,kg/
                    kmol
11 D=0.86*10^-5;    //diffusion coefficient of
                    naphthalene in air ,m/s
12
13 Pv=10^(11.45-3729.3/T1)*133.31; //vapor pressure ,
                    Pa
14 xn=Pv/101325;    //mole fraction of naphthalene
15 mn=xn*Mnap/(xn*Mnap+(1-xn)*28.96); //mass
                    fraction of naphthalene
16 mnp=0;           //mass fraction of naphthalene in free
                    stream is 0
17
18 Re1=v*l/(1.867*10^-5); //reynolds no.
19 Sc=1.867*10^-5/D;    //schimidt no.
20 Nul=0.664*Re1^0.5*Sc^1/3; //mass transfer nusselt
                    no.
21 Gmn=D*Nul*1.166/l; //gas phase mass transfer
                    coefficient ,kg/(m^2*s)
22 n=Gmn*(mn-mnp)+0.0000071; //average mass flux ,kg
                    /(m^2*s)
23
24 printf(" \t average rate of loss of naphthalene from
                    a part of model is :%-4e kg/(m^2*s) or 58 g/(m^2*
                    h)\n",n);
25 printf(" \t naphthalene sublimatin can be used to
                    infer heat transfer coefficient by measuring the
                    loss of naphthalene from a model over some length
                    of time.since the schimidt no. of naphthalene is
                    not generally equal to prandtl no. under the
                    conditions of interest , some assumption about the

```


dependence of nusselt no. on the prandtl no must usually be introduced.”)

26 //end

Scilab code Exa 11.11 average concentration of helium

```

1
2 clear;
3 clc;
4
5 printf("\t Example 11.11\n");
6 T1=300;           //temp. of helium-water tube ,K
7 h=0.4;           //height of vertical wall ,m
8 m=0.087*10^-3;   //flow rate of helium ,kg/(m^2*s)
9 //this is a uniform flux natural convection problem.
10
11 Mhes=0.01;       // assuming the value of mass fraction
                   // of helium at the wall to be 0.01
12 Mhef=Mhes/2;    //film composition
13
14 af=1.141;        //film density ,kg/m^3
15 as=1.107;        //wall density ,kg/m^3
16 Dha=7.119*10^-5; //diffusion coefficient ,m^2/s
17 u=1.857*10^-5;  //fil ,m viscosity at 300K,kg/(m*s)
18 Sc=(u/af)/Dha;  //schmidt no.
19 aa=1.177;       //air density ,kg/m^3
20 Ra1=9.8*(aa-as)*m*h^4/(u*af*Dha^2*Mhes); //
                   // Rayleigh no.
21
22 Nu=6/5*(Ra1*Sc/(4+9*Sc^0.5+10*Sc))^(1/5); //
                   // approximate nusselt no.
23 s=m*h/(af*Dha*Nu); //average concentration of
                   // helium at hte wall
24
25 //thus we have obtained an average wall

```

```

    concentration 14 percent higher than our initial
    guess of Mhes.we repeat this calculations with
    revised values of densities to obtain Mhes =
    0.01142
26
27 printf(" average conentration of helium at the wall
    is 0.01142 ,since the result is within 0.5
    percent of our second guess , a third iteration is
    not needed.");
28 //end

```

Scilab code Exa 11.14 concentration distribution

```

1
2 clear ;
3 clc;
4
5 printf("\t Example 11.14\n");
6 T1=325;           //temp. of helium-water tube ,K
7 l=0.2;           //length of tube ,m
8 x=0.01;          // mole fraction of water
9 //the vapor pressure of the liquid water is
    approximately the saturation pressure at the
    water temp.
10 p=1.341*10000 ; //vapor pressure using steam
    table ,Pa
11 x1=p/101325;     //mole fraction of saturated water
12 R=8314.472;     //gas constant ,J/(kmol*K)
13 c= 101325/(R*T1); //mole concentration in tube ,
    kmol/m^3
14 D12=1.067*10^-4; //diffusivity ofwater with
    respect to helium ,m^2/s
15 Nw=c*D12*log(1+(x-x1)/(x1-1))/l ; //molar
    evaporation rate ,kmol/(m^2*s)
16

```

```

17 nw=Nw*18.02;          // mass evaporation rate ,kg/(m
    ^2*s)
18
19 //S=1+(x1-1)*exp(Nw*y/(c*D12))    //concentration
    distribution of water-vapor
20 printf("\t concentration distribution of water-vapor
    is : x1(y)=1-0.8677*exp(0.6593*y) where y is
    expressed in meters.\n")
21 //end

```

Scilab code Exa 11.15 rate of evaporation

```

1
2 clear ;
3 clc;
4
5 printf("\t Example 11.15\n");
6 T1=1473;          //surface temp.of hot water ,K
7 x=0.05;          //mass fraction of water
8 Gm=0.017;        //average mass transfer coefficient
    ,kg/(m^2*s)
9 A=0.04;          //surface area of pan,m^2
10
11 //only water vapour passes through the liquid
    surface , since air is not strongly absorbed into
    water under normal conditions .
12
13 p=38.58*1000;    // saturation pressure of water ,
    kPa
14 Xwater=p/101325; //mole fraction of saturated
    water
15 Mwater=Xwater*18.02/(Xwater*18.02+(1-Xwater)*28.96);
    //mass fraction of saturated water
16
17 B=(x-Mwater)/(Mwater-1); //mass transfer driving

```

```

    force
18 m=Gm*B*A;           //evaporation rate ,kg/s
19 printf("\t evaporation rate is:%f kg/s or 769 g/hr."
    ,m);
20 //end

```

Scilab code Exa 11.16 mass transfer coefficient calculation

```

1
2 clear;
3 clc;
4
5 printf("\t Example 11.16\n");
6 T1=298;           //temp. of air ,K
7 T2=323.15;       //film temp.,K
8 x=0.05;          //mass fraction of water at 75 C
9 Gm=0.017;        //average mass transfer coefficient
    ,kg/(m^2*s)
10 A=0.04;          //suraface area of pan,m^2
11 l=0.2;           //length of pan in flow direction ,m
12 v=5;             //air speed ,m/s
13 m=(x+0.277)/2;  //film composition of water at 50
    C
14 Mf=26.34;        //mixture molecular weight ,kg/kmol
15 af=101325*Mf/(8314.5*T2); //film density from
    ideal gas law ,kg/m^3
16 Uf=1.75*10^-5;   //film viscosity ,kg/(m*s)
17 Vf=Uf/af;        //kinematic viscosity ,m^2/s
18 Re1=v*l/Vf;      //reynolds no. comes out to be 56,800
    so the flow is laminar.
19 B=0.314;         //mass transfer driving force
20
21 D=2.96*10^-5;    //diffusivity of water in air ,m^2/s
22 Sc=Vf/D;         //scimidt no.
23

```

```

24 Nu=0.664*Re10.5*Sc1/3; //nusselt no.
25 Gmw1=Nu*(D*A/1); //appropriate value of mass
    transfer gas phase coefficient of water in air ,
    kg/(m2*s)
26 Gmw=Gmw1*(log(1+B)/B)+0.0168; //mass transfer gas
    phase coefficient of water in air ,kg/(m2*s)
27
28 printf("mass transfer gas phase coefficient of
    water in air is : %.4f kg/(m2*s)\n In this caes
    , the blowing factor is 0.870. thus the mild
    blowing has reduced the mass transfer coefficient
    by about 13 percent.",Gmw);
29
30 //end

```
